Department of the Army
U.S. Army Corps of Engineers
Washington, DC 20314-1000

EC 1165-2-211

CECW-CE

Circular
No. 1165-2-211

1 July 2009

EXPIRES 1 JULY 2011
WATER RESOURCE POLICIES AND AUTHORITIES INCORPORATING SEA-LEVEL CHANGE CONSIDERATIONS IN CIVIL WORKS PROGRAMS

1. Purpose. This circular provides United States Army Corps of Engineers (USACE) guidance for incorporating the direct and indirect physical effects of projected future sea-level change in managing, planning, engineering, designing, constructing, operating, and maintaining USACE projects and systems of projects. Recent climate research by the Intergovernmental Panel on Climate Change (IPCC) predicts continued or accelerated global warming for the 21st Century and possibly beyond, which will cause a continued or accelerated rise in global mean sea-level. Impacts to coastal and estuarine zones caused by sea-level change must be considered in all phases of Civil Works programs.

2. Applicability. This Circular applies to all USACE elements having Civil Works responsibilities and is applicable to all USACE Civil Works activities. This guidance is effective immediately, and supersedes all previous guidance on this subject. Districts and Divisions shall inform CECW of any problems with implementing this guidance.

3. Distribution Statement. This publication is approved for public release; distribution is unlimited.

4. References. Required and related references are at Appendix A. A glossary is included at the end of this document.

5. Geographic Extent of Applicability.

a. USACE water resources management projects are planned, designed, constructed and operated locally or regionally. For this reason, it is important to distinguish between global mean sea level (GMSL) and local (or "relative") mean sea level (MSL). At any location, changes in local MSL reflect the integrated effects of GMSL change plus changes of regional geologic, oceanographic, or atmospheric origin as described in Appendix B and the Glossary.

b. Potential relative sea-level change must be considered in every USACE coastal activity as far inland as the extent of estimated tidal influence. Fluvial studies (such as flood studies) that include backwater profiling should also include potential relative sea-level change in the starting water surface elevation for such profiles, where appropriate. The base level of potential relative sea-level change is considered the historically recorded changes for the study site. Areas already experiencing relative sea-level change or where changes are predicted should analyze this as part of the study.

6. Incorporating Future Sea-Level Change Projections into Planning, Engineering Design, Construction, and Operating Projects.

a. Planning, engineering, and designing for sea level change must consider how sensitive and adaptable 1) natural and managed ecosystems and 2) human systems are to climate change and other related global changes. To this end, consider the following two documents:

(1) The Climate Change Science Program (CCSP) Synthesis and Assessment Product 4.1 (SAP 4.1) *Coastal Sensitivity to Sea-Level Rise: A Focus on the Mid-Atlantic Region* details both how sea-level change affects coastal environments and what needs to be addressed to protect the environment and sustain economic growth. SAP 4.1 represents the most current knowledge on implications of rising sea levels and possible adaptive responses.

(2) The National Research Council's 1987 report *Responding to Changes in Sea Level: Engineering Implications* recommends a multiple scenario approach to deal with key uncertainties for which no reliable or credible probabilities can be obtained. In the context of USACE planning, multiple scenarios address uncertainty and help us develop better risk-informed alternatives.

b. Planning studies and engineering designs should consider alternatives that are developed and assessed for the entire range of possible future rates of sea-level change. These alternatives will include structural and nonstructural solutions, or a combination of both. Evaluate alternatives using "low," "intermediate," and "high" rates of future sea-level change for both "with" and "without" project conditions. Use the historic rate of sea-level change as the "low" rate. Base "intermediate" and "high" rates on the following:

(1) Estimate the "intermediate" rate of local mean sea-level change using the modified NRC Curve I and equations 2 and 3 in Appendix B (see Figures B-9 and B-11). Consider both the most recent IPCC projections and modified NRC projections and add those to the local rate of vertical land movement.

(2) Estimate the "high" rate of local sea-level change using the modified NRC Curve III and equations 2 and 3 in Appendix B (see Figures B-9 and B-11). Consider both the most recent IPCC projections and modified NRC projections and add those to the local rate of vertical land movement. This "high" rate exceeds the upper bounds of IPCC estimates from both 2001 and 2007 to accommodate for the potential rapid loss of ice from Antarctica and Greenland.

c. Determine how sensitive alternative plans and designs are to these rates of future local mean sea-level change, how this sensitivity affects calculated risk, and what design or operations and maintenance measures should be implemented to minimize adverse consequences while maximizing beneficial effects. Consider sensitivity relative to human health and safety, economic costs and benefits, environmental impacts, and other social effects. Address risks for each alternative and each potential future rate of sea-level change (“low,” “intermediate,” and “high”). For those alternatives sensitive to sea-level change, evaluate the potential timing and cost consequences during the plan formulation process.

FOR THE COMMANDER:

ALEX C. DORNSTAUDER
Colonel, Corps of Engineers
Executive Director of Civil Works

4 Appendices:
APPENDIX A: References
APPENDIX B: Technical Supporting Material
APPENDIX C: Flowchart to Account for Changes in Mean Sea Level
Glossary

APPENDIX A

References

A-1. Required References.

ER 1105-2-100
Planning Guidance Notebook (22 APR 2000). http://140.194.76.129/publications/eng-regs/er1105-2-100/toc.htm

EC 1110-2-6065
Comprehensive Evaluation of Project Datum: Guidance for a Comprehensive Evaluation of Vertical Datums on Flood Control, Shore Protection, Hurricane Protection, and Navigation Projects. http://140.194.76.129/publications/eng-circulars/ec1110-2-6065/toc.htm

Environmental Protection Agency 2009
Climate Change Science Program (CCSP) (2009) Synthesis and Assessment Product 4.1: Coastal Sensitivity to Sea-Level Rise: A Focus on the Mid-Atlantic Region. A report by the U.S. Climate Change Program and the Subcommittee on Global Change Research. [J. G. Titus (Coordinating Lead Author), E. K. Anderson, D. Cahoon, S. K. Gill, R. E. Thieler, J. S. Williams (Lead Authors)], U.S. Environmental Protection Agency, Washington, D.C. (http://www.climatescience.gov/Library/sap/sap4-1/final-report/default.htm

National Research Council 1987
Responding to Changes in Sea Level: Engineering Implications. National Academy Press: Washington, D.C. http://www.nap.edu/catalog.php?record_id=1006

Bindoff et al. 2007
Bindoff, N.L., J. Willebrand, V. Artale, A, Cazenave, J. Gregory, S. Gulev, K. Hanawa, C. Le Quéré, S. Levitus, Y. Nojiri, C. K. Shum, L. D. Talley, and A. Unnikrishnan (2007) Chapter 5, Observations: Oceanic Climate Change and Sea Level. In: Climate Change 2007: The Physical Science Basis. Contribution of Working Group I to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change [Solomon, S., D. Qin, M. Manning, Z. Chen, M. Marquis, K. B. Averyt, M. Tignor, and H. L. Miller (eds.)]. Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA. http://www.ipcc.ch/pdf/assessment-report/ar4/wg1/ar4-wg1-chapter5.pdf

Nicholls et al. 2007
Nicholls, R. J., P. P. Wong, V. R. Burkett, J. O. Codignotto, J. E. Hay, R. F. McLean, S. Ragoonaden, and C. D. Woodroffe (2007) Chapter 6, Coastal Systems and Low-lying Areas. In: Climate Change 2007: Impacts, Adaptation and Vulnerability. Contribution of Working Group II to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change [M. L.

Parry, O. F. Canziani, J. P. Palutikof, P. J. van der Linden, and C. E. Hanson (eds.)]. Cambridge University Press, Cambridge, UK, 315-356. http://www.ipcc.ch/pdf/assessment-report/ar4/wg2/ar4-wg2-chapter6.pdf

A-2. Related References.

USACE 1996
USACE (1996) Poplar Island, Maryland Environmental Restoration Project Feasibility Report and Environmental Impact Statement.

USACE 2004
USACE (2004) Poplar Island Environmental Restoration Project Adaptive Management Plan.

National Ocean Service 2009
National Ocean Service (NOS) (2009) Sea Levels Online Web Product. http://tidesandcurrents.noaa.gov/sltrends/index.shtml

National Research Council 1987
National Research Council (1987) Responding to Changes in Sea Level: Engineering Implications. National Academy Press: Washington, D.C.

Intergovernmental Oceanographic Commission 1985
Intergovernmental Oceanographic Commission (1985) Manual on Sea Level Measurement and Interpretation, Volume I. Intergovernmental Oceanographic Commission Manuals and Guides-14. http://unesdoc.unesco.org/images/0006/000650/065061eb.pdf

Intergovernmental Panel on Climate Change 2000
Intergovernmental Panel on Climate Change (2000) Special Report on Emissions Scenarios. (Nakicenovic, N., and R. Swart, eds.). Cambridge University Press, Cambridge, United Kingdom. http://www.grida.no/climate/ipcc/emission/

Intergovernmental Panel on Climate Change 2001
IPCC (2001) The Scientific Basis. Contribution of Working Group I to the Third Assessment Report of the Intergovernmental Panel on Climate Change (Houghton, J. T.,Y. Ding, D. J. Griggs, M. Noguer, P. J. van der Linden, X. Dai, K. Maskell, and C. A. Johnson, eds.). Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA. http://www.ipcc.ch/ipccreports/tar/wg1/index.htm

Intergovernmental Panel on Climate Change 2007a
IPCC (2007a) Climate Change 2007: The Physical Science Basis, Contribution of Working Group I to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change. (Solomon, S., D. Qin, M. Manning, Z. Chen, M. Marquis, K. B. Averyt, M. Tignor, and H. L.

Miller, eds.).Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA. http://ipcc-wg1.ucar.edu/wg1/wg1-report.html

Intergovernmental Panel on Climate Change 2007b
IPCC (2007b) IPCC Fourth Assessment Report Annex 1: Glossary. In: Climate Change 2007: The Physical Science Basis. Contribution of Working Group I to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change (Solomon, S., D. Qin, M. Manning, Z. Chen, M. Marquis, K. B. Averyt, M. Tignor, and H. L. Miller, eds.). Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA. http://ipcc-wg1.ucar.edu/wg1/Report/AR4WG1_Print_Annexes.pdf

Intergovernmental Panel on Climate Change 2007c
IPCC (2007c) Climate Change 2007: Impacts, Adaptation and Vulnerability. Contribution of Working Group II to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change." (M. L. Parry, O. F. Canziani, J. P. Palutikof, P. J. van der Linden and C. E. Hanson, eds.). Cambridge University Press, Cambridge, UK. http://www.ipcc.ch/ipccreports/ar4-wg2.htm

Bell 1982
Bell, D. E. (1982) Regret in Decision Making under Uncertainty. *Operations Research*, vol. 30, no. 5, p. 961-981. http://www.jstor.org/stable/170353)

Bruun 1962
Bruun, P. M. (1962) Sea-Level Rise as a Cause of Shore Erosion. *Journal of Coastal Engineering*, vol. 7, no. 1, p. 77-89.

Cahoon et al. 1999
Cahoon, D. R., J. W. Day, and D. J. Reed (1999) The Influence of Surface and Shallow Subsurface Soil Processes on Wetland Elevation: A Synthesis. *Current Topics in Wetland Biogeochemistry*, vol. 3, p. 72-88.

Cahoon et al. 2009
Cahoon, D. R., D. J. Reed, A. S. Kolker, M. M. Brinson, J. C. Stevenson, S. Riggs, R. Christian, E. Reyes, C. Voss, and D. Kunz (2009) Coastal Wetland Sustainability. In: Coastal Sensitivity to Sea-Level Rise: A Focus on the Mid-Atlantic Region. A report by the U.S. Climate Change Science Program and the Subcommittee on Global Change Research. [J. G. Titus (coordinating lead author), K. E. Anderson, D. R. Cahoon, D. B. Gesch, S. K. Gill, B. T. Gutierrez, E. R. Thieler, and S. J. Williams (lead authors)]. U.S. Environmental Protection Agency, Washington DC, p. 57-72.

Erwin et al. 2007
Erwin, R. M, J. Miller, and J. G. Reese (2007) Poplar Island Environmental Restoration Project: Challenges in Waterbird Restoration on an Island in Chesapeake Bay. *Ecological Restoration* vol. 25, no. 4, p. 256- 262.

Flessa et al. 1977
Flessa, K. W., K. J. Constantine, and M. K. Cushman (1977) Sedimentation Rates in Coastal Marshes Determined from Historical Records. *Chesapeake Science*, vol. 18, no. 2 (June 1977), p. 172-176.

Haimes 1991
Haimes, Y. Y. (1991) Total Risk Management. *Risk Analysis*, vol. 11, no. 2, p. 169-171.

Hicks et al. 2000
Hicks, S. D., R. L. Silcox, C. R. Nichols, B. Via, and E. C. McCray (2000) Tide and Current Glossary. NOAA National Ocean Service Center for Operational Oceanographic Products and Services (http://tidesandcurrents.noaa.gov/publications/glossary2.pdf).

Hulme et al. 2002
Hulme, M., G. J. Jenkins, X. Lu, J. R. Turnpenny, T. D. Mitchell, R. G. Jones, J. Lowe, J. M. Murphy, and co-authors (2002) Climate Change Scenarios for the United Kingdom: The UKCIP02 Scientific Report. Tyndall Centre for Climate Change Research, University of East Anglia, Norwich, Norfolk. http://www.ukcip.org.uk/images/stories/Pub_pdfs/UKCIP02_tech.pdf

Kaplan and Garrick 1981
Kaplan, S., and B. J. Garrick (1981) On the Quantitative Definition of Risk. *Risk Analysis*, vol. 1, no. 1, p. 11-27.

Kendall 2007
Kendall, T. R. (2007). Planning for Sea-level Rise. Presentation at the Climate Change and Coastal Systems Symposium: ASCE SF Section 2007 Annual Meeting, Burlingame, CA, Sept. 28, 2007.

Knuuti 2002
Knuuti, K. (2002) Planning for Sea-Level Rise: U.S. Army Corps of Engineers Policy. Solutions to Coastal Disasters ’02, ASCE 2002.

Leatherman et al. 1995
Leatherman, S.P., R. Chalfont, E.C. Pendleton, T.L. McCandless, and S. Funderburk (1995). Vanishing Lands: Sea Level, Society and Chesapeake Bay. Laboratory of Coastal Research, University of Maryland.

Morris et al. 2002
Morris, J. T., P. V. Sundareshwar, C. T. Nietch, B. Kjerfve, and D. R. Cahoon (2002) Responses of Coastal Wetlands to Rising Sea Level. *Ecology*, vol. 83, no. 10, p. 2869-2877.

Proshutinsky et al. 2004
Proshutinsky, A., I. M. Ashik, E. N. Dvorkin, S. Hakkinen, R. A. Krishfield, and W. R. Peltier (2004), Secular Sea-Level Change in the Russian Sector of the Arctic Ocean. *Journal of Geophysical Research*, vol. 109, no. C03042, doi:10.1029/2003JC002007

Pugh 1987
Pugh, D. T (1987) Tides, Surges, and Mean Sea Level. John Wiley and Sons: Chichester, England.

Science Applications International Corporation 2007
Science Applications International Corporation (2007) Data Report for the Analysis of the Poplar Island Tidal Data from October thru December 2006.

Zervas 2001
Zervas, C. (2001) Sea Level Variations of the United States 1854-1999. NOAA Technical Report NOS CO-OPS 36 and updates. http://tidesandcurrents.noaa.gov/publications/techrpt36doc.pdf

APPENDIX B

Technical Supporting Material

B-1. Background on Sea-Level Change.

a. In the preparation of this document USACE has relied entirely on climate change science performed and published by agencies and entities external to USACE. The conduct of science as to the causes, predicted scenarios, and consequences of climate change is not within the USACE mission. The USACE is a user of the currently accepted community consensus on the state of climate science knowledge and applicable USACE policies will be periodically reviewed and revised as the accepted consensus changes.

b. Global mean sea level (GMSL) over the past several million years has varied principally in response to global climate change (NRC 1987, IPCC 2007a). For example, at the peak of the most recent glacial period about 20,000 years ago, global MSL is inferred to have been on the order of 100-120 meters lower than at present (NRC 1987, IPCC 2007a). As global climate warmed and the glaciers retreated, water stored as continental ice was released, adding to the mass of water in the oceans and causing a corresponding rise in global MSL.

c. Geologic evidence suggests global sea level has fallen and risen with minimums and maximums occurring during cold glacial and inter-glacial warm periods respectively. During the last inter-glacial period, about 125,000 years ago, sea level was 4m to 6m higher than at present. The earth entered the present inter-glacial warm period following the peak of the last Ice Age about 12,000 years ago (CCSP 2009). After a rapid initial rise, GMSL is interpreted as having approximately stabilized within a meter or so of its present value over the last several thousand years (NRC 1987, IPCC 2007a). IPCC (2007a) concludes that global mean sea level rose at an average rate of about 1.7 ± 0.5 mm/year during the twentieth century.

d. Recent climate research has documented global warming during the 20th Century, and has predicted either continued or accelerated global warming for the 21st Century and possibly beyond (IPCC 2007a). One impact of continued or accelerated climate warming is thus continued or accelerated rise of GMSL.

e. Sea-level change can cause a number of impacts in coastal and estuarine zones, including changes in shoreline erosion, inundation or exposure of low-lying coastal areas, changes in storm and flood damages, shifts in extent and distribution of wetlands and other coastal habitats, changes to groundwater levels, and alterations to salinity intrusion into estuaries and groundwater systems (e.g., CCSP 2009).

f. Geologic factors can drive local sea-level change. Vertical land movement can occur due to tectonics (earthquakes, regional subsidence or uplift), compaction of sedimentary strata, crustal rebound in formerly glaciated areas, and withdrawal of subsurface fluids. Networks of long-term Continuously Operating Reference Stations (CORS) are being monitored by NOAB-NGS and when co-located with tide stations will begin to provide direct estimates of vertical land uplift or subsidence.

g. Atmospheric factors can affect local or regional water levels. Decadal-scale phenomena include El Niño-Southern Oscillation (ENSO) in the Pacific and North Atlantic Oscillation (NAO) in the Atlantic, among others (see IPCC 2007a for a more complete discussion). Climate change may also alter the frequency and severity of tropical storms which could secondarily influence sea level. This is currently the subject of scientific research. Although the coupled effects of decadal and seasonal water level variations and episodic storm events are important to consider in project planning and design, the incorporation of the influence of tropical storm on the application of sea level trends is outside the scope of this document.

B-2. Determination of Historic Trends in Local MSL.

a. *The planning and design of USACE water resource projects in and adjacent to the coastal zone must consider the potential for future accelerated rise in GMSL to affect the local MSL trend.* At the same time, USACE project planners and engineers must be aware of the *historic* trend in local MSL, because it provides a useful minimum baseline for projecting future change in local MSL. Awareness of the historic trend of local MSL also enables an assessment of the impacts that sea-level change may have had on regional coastal resources and problems in the past.

b. Historic trends in local MSL are best determined from tide gauge records. The Center for Operational Oceanographic Products and Services (CO-OPS), of the National Oceanographic and Atmospheric Administration (NOAA), provides historic information and local MSL trends for tidal stations operated by NOAA/NOS in the US (see http://www.co-ops.nos.noaa.gov/index.shtml). Most U.S. tide stations experienced a rise in local MSL during the 20th Century. Note the dominance of green and yellow symbols along much of the Atlantic and Pacific coasts of the continental US (Figure B-1). These stations exhibit local MSL trends between 0 and +2 feet per century. The highest rates of local MSL rise in the US have occurred along the Gulf Coast (red symbols), whereas most stations in Alaska exhibit a falling trend of local MSL. Discrete shifts in sea level data or changes in relative sea level trends due to earthquakes are monitored by NOAA at their tide stations, and trends are recomputed from data after a known significant earthquake event (such as the 1964 Alaska earthquake). Trends are not computed from pre- and post event data. Post-event data analyses and surveys from the tide gauges to local bench marks and geodetic bench marks are used to estimate vertical movement. Data from nearby CORS are also now being used to estimate local vertical land motion to help monitor magnitude of the effect of earthquake events on sea level data.



Figure B-1. Mean Sea Level Trends for U.S. Tide Stations (Oct 2008) (see http://tidesandcurrents.noaa.gov/sltrends/slrmap.html for updated information).

c. It is important to consider the length of tide station record required to obtain a robust estimate of the historic relative mean sea-level change. The length of the record is important because interannual and decadal variations in sea level are sufficiently large that misleading or erroneous sea level trends can be derived from periods of record that are too short.

d. The Manual on Sea Level Measurement and Interpretation (Intergovernmental Oceanographic Commission 1985) suggests that a tidal record should be of at least of two-tidal epoch duration (about 40 years) before being used to estimate a local relative mean sea level trend. Figure B-2 (from Zervas 2001) shows the relationship between period of record and the standard error of the trend for selected US tide stations. Note the significant decrease in standard error approximately at the 40- or 50-year period of record. Record lengths shorter than 40-years in duration could have significant uncertainty compared to their potential numerical trend values of a few millimeters per year.

e. Figure B-2 indicates that standard error can be can be large for tide stations with shorter records compared to those with longer records. As a practical approximation, a tide station should have a minimum of 40 years of data to justify using the station trend to extrapolate into the future and use as a minimum baseline for projected future change in local MSL. For project planning and design, the actual standard error of the estimate should be calculated for each tide gauge data trend analysis and the estimates in Figure B-2 should not be used as the sole supporting data.



Figure B-2. Standard Error of Linear Trend of Sea-level rise vs. Period of Record, U.S. Tide Stations.

f. Using trends in relative mean sea level from records shorter than 40 years is not advisable. In addition to interpretations by the International Oceanographic Commission and NOAA (Figure B-2), Pugh (1987) demonstrates that 10-year records at some stations show trends of opposite sign depending upon the interval selected. If estimates based on shorter terms are the only option, then the local trends must be viewed in a regional context, considering trends from simultaneous time periods from nearby stations to ensure regional correlation and to minimize anomalous estimates. The nearby stations should have long enough records (greater than 40 years) to determine reasonable trends, which can then be compared to the shorter, local sea-level records (see paragraph B-2(h)(2)). Experts at NOAA/NOS should be able to assist in cases of short periods of record or where records are otherwise ambiguous.

g. The Permanent Service for Mean Sea Level (PSMSL), which is a component of the UK Natural Environment Research Council’s Proudman Oceanographic Laboratory, has been collecting, publishing, analyzing, and interpreting sea-level data from the global network of tide stations since 1933. Global sea level data can be obtained from PSMSL via their web site (http://www.pol.ac.uk/psmsl/). PSMSL should be considered as a source of information for non-US stations not contained in the NOAA report. Please note that the periods of record of PSMSL gauges vary; some gauges have shorter periods of record than are recommended for relative sea-level change trend analysis.

h. The historic rate of relative sea-level change at relevant local tide stations shall be used as the low rate for analysis. The current, historically-based rate of change shall be estimated from local tide station records if oceanographic and geologic conditions at the tide station are determined to be similar to and consistent with those at the project site (Appendix C). For many locations along the U.S. Atlantic and Gulf of Mexico coastlines, there are probably adequate tide station data from perspectives of both spatial density and record duration to permit extrapolating with an adequate degree of confidence. Recognized exceptions are the coastlines between Mobile, Alabama and Grand Isle, Louisiana, and in Pamlico/Albemarle Sounds, North Carolina, which contain no acceptable long-term tide-gauge records. Louisiana is also subject to extreme rates of subsidence. In the case where there is a tidal station that is close to a project but has a short historic data range, and another tidal station that is farther away but has a longer historic data range, a tidal hydrodynamics expert should be consulted.

(1) Figures B-3 through B-6 show the magnitude and confidence limits (based on standard error of the estimate) of trends for Atlantic coast, Gulf of Mexico, and tropical NOS tide stations (from Zervas, personal communication, see updated information online at http://tidesandcurrents.noaa.gov/sltrends/slrmap.html). A pair of stations useful for illustrating the effect of record length on confidence limits is Galveston Pier 21 and Galveston Pleasure Pier (Figure B-6). These stations are located within approximately one mile of each other, with Pleasure Pier on the ocean side and Pier 21 on the navigation waterway side of Galveston Island. The Pier 21 station was established in 1908 and Pleasure Pier station in 1957, thus Pier 21 has approximately 101 years of record and Pleasure Pier approximately 51 years. The confidence limits on Pier 21 are significantly narrower than for Pleasure Pier.

(2) Figures B-7 and B-8 show sea level trends and confidence limits for U.S. Pacific coast stations. Because of the scatter of trends and confidence limits, estimating historical sea-level change for many sites along the U.S. Pacific coast may be problematic. Confidence limits are not as uniform as for the Atlantic and tropical stations. Estimating and extrapolating trends based upon available data will require engineering judgment on a case-by-case basis, and to be robust, should take advantage of interdisciplinary and interagency subject matter expertise. It may be possible depending upon station location and proximity to nearby stations with longer records, to use the longer record trend as a proxy providing the two records are well correlated for the concurrent period of record.

i. Regional sea-level change rates should be evaluated as well as rates of local sea-level change and global sea-level change. Regional sea-level change rates are expected to be close to global sea-level change rates, but differences may be found in large, semi-enclosed water bodies. Areas which could experience regional rates different than global rates include the northern Gulf of Mexico, the Gulf of Maine, and the Gulf of Alaska. Large embayments such as Chesapeake Bay may also experience rates that are slightly different than global rates due to regional effects.



Figure B-3. Magnitude and confidence limits of trends for northern Atlantic coast NOS tide stations. (NOS 2009, http://tidesandcurrents.noaa.gov/sltrends/index.shtml).



Figure B-4. Magnitude and confidence limits of trends for Southern Atlantic coast NOS tide stations. (NOS 2009, http://tidesandcurrents.noaa.gov/sltrends/index.shtml).



Figure B-5. Magnitude and confidence limits of trends for ocean island NOS tide stations. (NOS 2009, http://tidesandcurrents.noaa.gov/sltrends/index.shtml).



Figure B-6. Magnitude and confidence limits of trends for Florida Keys and Gulf of Mexico coast NOS tide stations. (NOS 2009, http://tidesandcurrents.noaa.gov/sltrends/index.shtml).



Figure B-7. Magnitude and confidence limits of trends for southern Pacific coast NOS tide stations. (NOS 2009, http://tidesandcurrents.noaa.gov/sltrends/index.shtml).



Figure B-8. Magnitude and confidence limits of trends for northern Pacific coast NOS tide stations. (NOS 2009, http://tidesandcurrents.noaa.gov/sltrends/index.shtml)

j. The length of time that the historical record rate of change can be validly projected into the future depends upon at least the following factors:

(1) the confidence of the present trend

(2) local relative rate of change (little or no acceleration)

(3) global rate of change (little or no acceleration)

(4) absence of dramatic geologic or oceanographic events.

B-3. Estimating Future Change in Local MSL.

a. In USACE activities, analysts shall consider what effect higher relative sea-level rise rates could have on design alternatives, economic and environmental evaluation, and risk. The analysis shall include, as a minimum, a low rate which shall be based on an extrapolation of the historical rate, and intermediate and high rates, which include future acceleration of sea-level rise. The analysis may also include additional intermediate rates, if the project team desires. The sensitivity of each design alternative to the various rates of sea-level rise shall be considered. Designs should be formulated using currently accepted design criteria. A step-by-step approach is presented in a flow chart in Appendix C.

b. Since 1987 NRC study on sea-level change was completed, the IPCC has produced four editions of its projections for future climate change and sea-level rise. The NRC study and the IPCC Third and Fourth Assessment Reports, dated 2001 and 2007 are useful in estimating future changes in local MSL (see http://www.ipcc.ch/).

c. The 1987 NRC report reviews data on relative sea-level changes and the resulting effect on engineering structures and coastal wetlands. Despite its age, the information and guidance presented in this study, in terms of considering how different types of projects may be affected by sea-level rise, are useful and should be considered by USACE planners and engineers in both the planning and design phases of studies and projects. An additional factor is that the NRC report includes a range of possible future sea-level rise scenarios that is much greater than those presented in the 2007 IPCC report. The 2007 IPCC report has received some criticism for not fully considering the possibility of rapid ice loss in Antarctica due to massive failures of the West Antarctic Ice Sheet. Including the upper scenarios from the NRC report allows planners and engineers to consider the possibility of much greater rates of sea-level rise than those presented in the 2007 IPCC report and to thus accommodate some of the criticism directed at the 2007 IPCC report.

d. The NRC report recommended that feasibility studies for coastal projects consider the high probability of accelerating global sea-level rise (SLR) and provided three different accelerating eustatic sea-level rise scenarios. The NRC described these three scenarios using the following equation:

$$E(t) = 0.0012t + bt^2 \qquad (1)$$

in which t represents years, starting in 1986, b is a constant, and $E(t)$ is the eustatic sea-level rise, in meters, as a function of t. The NRC committee recommended "projections be updated approximately every decade to incorporate additional data." At the time the NRC report was prepared, the estimate of global mean sea-level change was approximately 1.2 mm/year. Using the current estimate of 1.7 mm/year for global mean sea-level change, as presented by the IPCC (IPCC 2007), results in this equation being modified to be:

$$E(t) = 0.0017t + bt^2 \qquad (2)$$

(1) The three scenarios proposed by the NRC result in global eustatic sea-level rise values, by the year 2100, of 0.5 meters, 1.0 meters, and 1.5 meters. Adjusting the equation to include the historic global mean sea-level change rate of 1.7 mm/year results in updated values for the variable b being equal to 2.36E-5 for modified NRC Curve I, 6.20E-5 for modified NRC Curve II, and 1.005E-4 for modified NRC Curve III. The three global eustatic sea-level rise scenarios updated from NRC (1987) are depicted in Figure B-9.

(2) Manipulating equation (2) to account for the fact that it was developed for eustatic sea-level rise starting in 1986, while projects will actually be constructed at some date after 1986, results in equation (3):

$$E(t_2) – E(t_1) = 0.0017(t_2 – t_1) + b(t_2^2 – t_1^2) \qquad (3)$$

where t_1 is the time between the project's construction date and 1986 and t_2 is the time between a future date at which one wants an estimate for sea-level rise and 1986 (or $t_2 = t_1 +$ number of years after construction (Knuuti, 2002) For example, if a designer wants to know the projected eustatic sea-level rise at the end of a project's period of analysis, and the project is to have a fifty year life and is to be constructed in 2008, $t_1 = 2008 – 1986 = 22$ and $t_2 = 2058 – 1986 = 72$.



Figure B-9. Scenarios for Eustatic Sea-level Rise (based on updates to NRC 1987 equation).

e. From the Special Report on Emissions Scenarios (SRES) (IPCC 2000), six emissions scenarios were used to develop six SLR projections. A suite of numerical models that model air-ocean global circulation, with varying degrees of robustness, were used to provide a range of results. For each of these models, IPCC used the six different climate change scenarios for input (see Appendix B-3 for other contributing factors). Sea-level rise was calculated for each of the six scenarios by averaging the modeled sea-level values at every model grid cell, for every numerical model.

(1) IPCC used the different emissions scenarios and the range of values obtained from the different numerical models to develop ranges of future sea-level rise values, and used this as a way to describe the uncertainty associated with projecting future sea-level rise. These ranges are shown in Table B-1 (for two climate change scenarios, B1 and A1FI, the least and most extreme.

(2) An example of an IPCC intermediate level of model-derived sea-level rise (scenario A1B) is shown in Figure B-10. Note that the blue shaded area of this figure represents a potential level of uncertainty for the scenario shown, based on the range of model predictions, and does not provide a quantitative estimate. Figure B-11 presents the modified NRC curves of Figure B-9 plus the reported 95% confidence limits of the B1 and A1FI scenarios shown in Table B-1 (IPCC 2007a). It should be noted that the confidence limits shown in these tables only describe the confidence of the range of model results and do not actually represent the confidence of what could physically occur in the future.

Table B-1. Projected global average sea-level rise components during the 21st century for the B1 and A1FI scenarios. The table gives the IPCC's reported 5% and 95% confidence limit (m) of the estimated rise in sea level between 1980 to 1999 and 2090 to 2099 based on the SRES models (excerpted from IPCC 2007a, Table 10.7). The confidence limits shown in these tables only describe the confidence of the range of model results and do not actually represent the confidence of what could physically occur in the future.

	B1		A1FI	
	5% CL	95% CL	5% CL	95% CL
Sea-level rise, 2090-2099(m)	0.18	0.38	0.26	0.59



Figure B-10. Illustration of global mean sea level (deviation from the 1980-1999 mean) as observed since 1870 and projected for the future. The future projections have been calculated independently from the observations (after IPCC 2007a, FAQ 5.1, Figure 1).



Figure B-11. Modified NRC (1987) eustatic sea-level rise scenarios and the IPCC (2007) scenario estimates for use in predicting future sea-level change.

APPENDIX C

Flowchart to Account for Changes in Mean Sea Level

C-1. Premise. Global mean sea level (MSL) has risen over the past century, and the rate of rise will continue and may accelerate in the future. USACE projects need to be planned, designed, constructed, and operated with the understanding that the rate of rise of global MSL may accelerate and affect USACE water resource projects in and adjacent to the nation's coastal zone. In other locations, the relative sea-level is dropping, and USACE projects must account for the decrease in water levels and must balance this with the potential for increasing global MSL. The steps below are shown graphically in Figure C-1.

C-2. Flowchart.

Step 1. Is the project in the coastal/tidal/estuarine zone, or does it border those zones such that project features or outputs are now, or may be in the future, subject to influence by continued or accelerated rate of sea-level rise? YES-NO?

a. If YES, go to Step 2.
b. If NO, continue with product development process without considering sea-level change.

Step 2. Locate nearest tide station(s) with a current period of record. Is the period of record at least 40 years? YES-NO?

a. If YES, go to Step 4.
b. If NO, go to Step 3.

Step 3. Identify next closest long-term gauge. Assess whether or not the long-term gauge can be used to artificially extend the record of the short-term gauge. YES-NO?

a. If YES, go to Step 4.
b. If NO, Consult with a tidal hydrodynamics expert, such as CO-OPS[1].

Step 4. Assess whether identified long-term gauges can be used to adequately represent local sea-level conditions at project site. YES-NO?

a. If YES, go to Step 5.
b. If NO, Consult with a tidal hydrodynamics expert, such as CO-OPS.

---

[1] CO-OPS: Center for Operational Oceanographic Products and Services, National Ocean Service, National Oceanographic and Atmospheric Administration, Silver Spring, MD 301-7132981. http://tidesandcurrents.noaa.gov

Step 5. Assess whether the project site and gauge site have similar physical conditions (coastal/estuarine location, bathymetry, topography, shoreline geometry, and hydrodynamic conditions). YES-NO?

a. If YES, go to Step 6.
b. If NO, Consult with a tidal hydrodynamics expert, such as CO-OPS.

Step 6. Calculate local historic trends for MSL, MHW, and MHHW at long-term gauge. Use CO-OPS values, if available. If not available, use CO-OPS method for sea-level trend analysis.[1] This historic trend is now the low or baseline trend rate for project alternative analysis (see 8(a)). Go to Step 7.

Step 7. Calculate standard error of the linear trend line (use CO-OPS values, if available). Go to Step 8.

Step 8. We must now evaluate whether there is a regional mean sea-level trend (see definition) that is different from the eustatic mean sea-level trend of 1.7 mm/year (+/- 0.5 mm/year, IPCC 2007a). See Figure C-2 for one example of such a region. Considering regional geology, is it possible to identify a vertically stable geologic platform within the same region as the project site? YES-NO?

a. If YES, go to Step 9.
b. If NO, go to Step 11.

Step 9. Calculate regional MSL trend for the identified vertically stable geologic platform within the region, and go to Step 10.

Step 10. Estimate local rate of vertical land movement by subtracting regional MSL trend from local MSL trend. Go to Step 12.

Step 11. Assume the regional mean sea-level trend is equal to the eustatic mean sea-level trend of 1.7 mm/year (+/-0.5mm/year) and estimate local rate of vertical land movement by subtracting eustatic MSL trend from local MSL trend. Go to Step 12.

Step 12. Calculate future values for sea-level change for low (historic or baseline) rate: extrapolate historic linear trend into future at 5-year increments, OR reasonable increments based on both period of analysis and scope of study[2]. Go to Step 13.

---

[1] CO-OPS method for sea-level trend analysis is described in NOAA Technical Report NOS CO-OPS 36, "**Sea Level** Variations of the United States 1854-1999.”.

[2] Use 5-yr increments unless alternate reasonable increments based on both period of analysis and scope of study can be justified. The number of scenarios may be determined through exploratory or iterative analysis.

Step 13. Calculate future values for sea-level change for intermediate rate (modified NRC Curve I), see 8(a)(1): calculate future sea-level change values at 5-year increments OR reasonable increments based on both period of analysis and scope of study by combining incremental values from equations A-2 and A-3 with values obtained by extrapolating rate of local vertical land movement. Go to Step 14.

Step 14. Calculate future values for sea-level change for high rate (modified NRC Curve III), see 8(a)(2): calculate future sea-level change values at 5-year increments OR reasonable increments based on both period of analysis and scope of study by combining incremental values from equations A-2 and A-3 with values obtained by extrapolating rates of local vertical land movement. Go to Step 15.

Step 15. Assess project performance for each sea-level change scenario developed in Steps 12, 13, and 14. Go to Step 16.

Step 16. Calculate the risk for each project design alternative combined with each sea-level rise scenario, as developed in Steps 12, 13, and 14 at 5-year increments OR reasonable increments based on both period of analysis and scope of study. Go to Step 17.

Step 17. Assess risk[1] and reevaluate project design alternatives. Consider at a minimum: planning for adaptive management[1], designing to facilitate future modifications, and designing for a more aggressive future sea-level change scenario. Go to Step 18.

Step 18. Select project designs that best accommodate the range of sea-level change scenarios.

---

[1] Policies are under development at the time of this EC.



Figure C-1. Graphical illustration of process to account for changes in mean sea level.

a) Is my project in or bordering coastal/tidal/estuarine (CTE) zone such that project features or outputs are now, or may be in the future, subject to influence by continued or accelerated rate of rise?
b) Discuss with tidal hydrodynamics expert, such as CO-OPS (NOAA).
c) Similar physical conditions such as coastal/estuarine location, bathymetry, topography, shoreline geometry, and hydrodynamic conditions.
d) Use CO-OPS (NOAA) values, if available.
e) Low rate: extrapolate historic linear trend into future at selected increments.
f) Intermediate rate (IPCC-2007, or modified NRC-Curve-I: calculate future SLR values at selected increments by combining incremental values from equations A-2 and A-3 with value obtained by extrapolating rate of local vertical land movement.
g) High rate (modified NRC-Curve-III): calculate future SLR values at selected increments by combining incremental values from equations A-2 and A-3 with value obtained by extrapolating rate of local vertical land movement.
h) Consider project design function: performance, design issues; project stability; and project operation and maintenance.
i) Calculate the risk for each project alternative at selected increments.
j) Consider at a minimum: planning for adaptive management (updating operational strategies based on new information); designing to facilitate future modifications; and adaptive engineering (designing for a more aggressive future SLR scenario



Figure C-2. Example of a region (northern Gulf of Mexico) that may exhibit a regional rate of mean sea-level rise that is different than the eustatic rate of mean sea-level rise. Red numbers represent the rate of local mean sea-level change (mm/yr) at NOAA tide stations, yellow numbers represent the same at USACE tide stations. The rectangle represents an area with a geologic platform that is generally thought to be vertically stable (Step 8). While local mean-sea level trends within this rectangle vary, they are consistently higher than the rate of eustatic mean sea-level rise (1.7 mm/year) and are thought to be indicative of the rate of regional mean sea-level rise (Step 9). This higher rate of regional mean sea-level rise could be used, along with rates of local mean sea-level rise, to estimate rates of local vertical land movement for studies and projects within the region, such as in Mississippi and Louisiana (Step 10). (From Knuuti, 2006[1]).

---

[1] Figure prepared by Kevin Knuuti for oral presentation, 2006.

Glossary

Coastal. The term coastal as used in this EC refers to locations with oceanic astronomical tidal influence, as well as connected waterways with base-level controlled by sea-level. In these latter waterways, influence by wind-driven tides may exceed astronomical tidal influence. Coastal areas include marine, estuarine, and riverine waters and affected lands. (The Great Lakes are not considered "coastal" for the purposes of this EC.)

Eustatic sea-level rise. Eustatic sea-level rise is a change in global average sea level brought about by an increase in the volume of the world ocean [Intergovernmental Panel on Climate Change (IPCC) 2007b].

Global mean sea-level (GMSL) change. Sea level can change globally due to (i) changes in the shape of the ocean basins, (ii) changes in the total mass of water and (iii) changes in water density. Sea-level changes induced by changes in water density are called steric. Density changes induced by temperature changes only are called thermosteric, while density changes induced by salinity changes are called halosteric (IPCC 2007b). See Figure B-10.

Local (i.e., "relative") sea level. Sea level measured by a tide gauge with respect to the land upon which it is situated. See mean sea level (MSL) and sea-level change (SLC). Relative sea-level change occurs where there is a local change in the level of the ocean relative to the land, which might be due to ocean rise and/or land level subsidence. In areas subject to rapid land-level uplift, relative sea level can fall (IPCC 2007b). Relative sea level change will also affect the impact of any regional sea level change.

Mean sea level (MSL). A tidal datum. The arithmetic mean of hourly heights observed over the National Tidal Datum Epoch (~19 years). Shorter series are specified in the name; e.g., monthly mean sea level and yearly mean sea level (Hicks et al 2000).

Post-glacial rebound. The vertical movement of the land and sea floor following the reduction of the load of an ice mass, for example, since the last glacial maximum (~21,000 years ago). The rebound is an isostatic land movement (IPCC 2007b).

Regional sea-level change. An increase or decrease in the mean level of the ocean's surface over a specific region. Global sea level has regional variations and regional sea-level change may be equal to, greater than, or less than global sea-level change due primarily to regional differences in ocean heating and cooling or to changes in bathymetry. Regional sea-level change as used here does not include local geologic effects, such as subsidence or tectonic movement.

Risk. Risk is a measure of the probability and severity of undesirable consequences (including, but not limited to, loss of life, threat to public safety, environmental and economic damages).

Sea-level change. A change in the mean level of the ocean.

Tide station. A device at a coastal location (and some deep-sea locations) that continuously measures the level of the sea with respect to the adjacent land. Time averaging of the sea level so recorded gives the observed secular changes of the relative sea level (IPCC 2007b).

Uncertainty. Uncertainty is the result of imperfect knowledge concerning the present or future state of a system, event, situation, or (sub) population under consideration. There are two types of uncertainty: aleatory and epistemic. Aleatory uncertainty is the uncertainty attributed to inherent variation which is understood as variability over time and/or space. Epistemic uncertainty is the uncertainty attributed to our lack of knowledge about the system (e.g., what value to use for an input to a model or what model to use). Uncertainty can lead to lack of confidence in predictions, inferences, or conclusions.