(12)

(16)

(19)

(22)

# **Boston Harbor and Approaches**

This chapter describes Boston Harbor, its approaches and tributaries, and the major commercial facilities in the port of Boston. The more important tributaries include Charles, Chelsea, Mystic and Weymouth Fore Rivers and Dorchester and Hingham Bays.

#### **COLREGS Demarcation Lines**

The lines established for Boston Harbor are described in **33 CFR 80.130**, chapter 2.

# **No-Discharge Zone**

The State of Massachusetts, with the approval of the Environmental Protection Agency, has established a No-Discharge Zone (NDZ) in all coastal waters of Massachusetts described in this volume, extending about 3 miles offshore.

Within the NDZ, discharge of sewage, whether treated or untreated, from all vessels is prohibited. Outside the NDZ, discharge of sewage is regulated by **40 CFR 140** (see chapter 2).

#### **Boston Harbor**

(11)

**Boston Harbor**, the largest seaport in New England, includes all the tidewater lying within a line from the southern extremity of Deer Island to Point Allerton, about 4 miles to the southeastward. Numerous dangers lie in the approaches to the harbor. The northeastern approach is obstructed by islands and shoals that extend 4 miles from the entrance; between them are the dredged channels which lead into the harbor. In the southeastern approach, broken ground extends as much as 3 miles from shore. The approaches are marked by a number of powerful lights, and the principal dangers are buoyed.

**Traffic Separation Scheme (Boston)** has been established in the approach to Boston Harbor; see charts for limits.

The Scheme is composed basically of **directed traffic lanes** each with one-way inbound and outbound traffic lanes separated by a **defined separation zone** and two **precautionary areas**. The Scheme is recommended for use by vessels approaching or departing from Boston Harbor but is not necessarily intended for tugs, tows or other small vessels which traditionally operate outside of the usual steamer lanes or close inshore.

The Traffic Separation Scheme has been designed to aid in the prevention of collisions at the approaches to major harbors but is not intended in any way to supersede or alter the applicable Navigation Rules. Separation zones are intended to separate inbound and outbound traffic lanes and to be free of ship traffic and should not be used except for crossing purposes. Mariners should use extreme caution when crossing traffic lanes and separation zones. (See 33 CFR 167.1 through 167.15 and 167.75 through 167.77, chapter 2, for limits and regulations and Traffic Separation Schemes, chapter 1, for additional information.)

A **precautionary area** is at the junction of Traffic Separation Scheme (Boston) and the Eastern Approach Off Nantucket to Traffic Separation Scheme Off New York. (See U.S. Coast Pilot 2, Atlantic Coast, Cape Cod to Sandy Hook, for a description of Traffic Separation Scheme Off New York. Consult the charts for the Off New York Scheme. The precautionary area is bounded on the east by a circle with a radius of 15.5 miles centered in

(13) 40°35'01"N., 69°59'58"W. and intersected by the Traffic Separation Schemes at points in

(14) 40°23'45"N., 69°13'57"W. and

(15) 40°50'28"N., 68°58'40"W., and is bounded on the west by a line connecting the schemes at points in

40°36'46"N., 69°15'08"W. and

(17) 40°48'02"N., 69°02'57"W.

The **precautionary area** in the approach to Boston Harbor has a radius of 6.17 miles centered on Boston Lighted Whistle Buoy B (42°22'42"N., 70°46'58"W.), excluding that area of the circle bounded by an imaginary line extending between the outer limits of the inbound and outbound traffic lanes.

The **separation zone** is a 1-mile zone centered in the following positions:

(20) (i) 42°20'44"N., 70°39'04"W.

(ii) 42°18'17"N., 70°01'08"W., and

(iii) 40°49'15"N., 69°00'49"W.

**Inbound traffic lane** is a 1.5-mile-wide lane with a length of about 129 miles. Entering the traffic lane at a point in about 40°50'00"N., 68°59'30"W., a course of **333**° for about 100 miles, thence a course of **275**° for about 29 miles follows the centerline of the traffic lane to the junction with the precautionary area.

**Outbound traffic lane** is a 1.5-mile-wide lane with a length of about 127 miles. Entering the traffic lane at a point in about 42°19'30"N., 70°39'50"W., a course of **95°** for about 28 miles, thence a course of **153°** for about 99 miles follows the centerline of the traffic lane to the junction with the precautionary area; thence steer usual courses to destination.

The Traffic Separation Scheme is buoyed.

**346** ■ U.S. Coast Pilot 1, Chapter 11

(Boston) is an important feeding ground for North Atlantic right whales. All vessels 65 feet or greater in length overall (LOA) and subject to the jurisdiction of the United States are restricted to speeds of 10 knots or less in three seasonal management areas. The first, near Great South Channel, is defined as the waters bounded by:

```
(27) 42°30'N., 69°45'W.;

(28) 42°30'N., 67°27'W.;

(29) 42°09'N., 67°08'24"W.;

(30) 41°00'N., 69°05'W.;
```

(31) 41°40'N., 69°45'W.; thence back to starting point and the restrictions apply between April 1 and July 31. The second area, off Race Point, is defined as the waters bounded by:

```
(32) 42°04'56.5"N., 70°12'W.;

(33) 42°12'N., 70°12'W.;

(34) 42°12'N., 70°30'W.;

(35) 42°30'N., 70°30'W.;

(36) 42°30'N., 69°45'W.;
```

41°41'N., 69°45'W.; thence due west to the shore and the restrictions apply between March 1 and April 30. The final area is defined as all waters of Cape Cod Bay with a northern boundary of 42°41'56.5"N., 70°12'W., to 42°12'N., 70°12'W., thence due west back to shore and the restrictions apply between January 1 and May 15. (See **50 CFR 224.105** in chapter 2 for regulations, limitations and exceptions.)

Approaches to Boston Harbor lie within the WHALESNORTH Mandatory Ship Reporting Area. Each self-propelled ship of 300 gross tons or greater entering WHALESNORTH must participate in the Mandatory Ship Reporting System (See 33 CFR 169, chapter 2, for limits and regulations, and chapter 3 for sample reports). Sovereign immune vessels are exempt from the requirement to report but are encouraged to participate.

# **Regulated Navigation Areas**

(39)

Safety and security zones, no-anchoring areas and areas to be avoided are in the vicinity of the Neptune Deepwater Port and the Northeast Gateway Deepwater Port located northeast and east of the Traffic Separation Scheme (Boston) precautionary area in the approach to Boston Harbor. (See 33 CFR 150.940 and 165.117, chapter 2, for limits and regulations.)

#### Area to be avoided

(42) In order to significantly reduce the risk of ship strikes to the North Atlantic right whale, an area to be avoided was established in the Great South Channel, east of the Boston Harbor traffic lanes. Ships of 300 gross tons and above should avoid the area bounded by lines connecting the following geographical positions:

```
(43) 41°44'08"N., 69°34'50"W.;
(44) 42°10'00"N., 68°31'00"W.;
```

 (45) 41°24'53"N., 68°31'00"W.; and
 (46) 40°50'28"N., 68°58'40"W. between the period of April 1 through July 31.

28 SEP 2025

#### **Prominent features**

(47)

(48)

(49)

(50)

(51)

(52)

**Boston Lighted Whistle Buoy B** (42°22'42"N., 70°46'58"W.) is about 7.8 miles east-northeastward of Deer Island. The buoy is equipped with a sound signal and racon. (See Light List for details of operation.)

Conspicuous to a vessel approaching Boston Harbor from northeastward is the tall red, white and blue standpipe on Winthrop Head. From eastward, the most prominent island in the entrance is Great Brewster. On the south side of the entrance, a turreted tower is conspicuous on Point Allerton; also prominent are the tank and standpipe on Strawberry Hill. Two miles south of Point Allerton are two radio towers which are illuminated at night.

The outstanding landmarks in the city of **Boston** are the John Hancock Building, the Prudential Building, the bridge over Mystic River, the control tower at Logan International Airport, the pointed tower of the customhouse and a large gas tank in Everett. Also prominent is the John F. Kennedy Federal Building in Boston.

Security Broadcast System, Boston Harbor. In conjunctionwith various maritime interests, the Coast Guard has developed a system of recommended radiotelephone procedures for Boston Harbor that is designed to supplement the Vessel Bridge-to-Bridge Radiotelephone Regulations (33 CFR 26) (see chapter 2). These voluntary procedures consist of security calls to be made by vessel masters, pilots or operators on VHF-FM channel 13 at designated points. The procedures are designed to give notice of unseen vessels, give notice of intended movement, clear channel 13 of traffic unrelated to navigation and give each vessel information on all others in the immediate vicinity and to do so at little cost and with as little radiotelephone traffic as possible. These recommendations do not relieve a master, pilot or operator of any requirements of law or regulation. There is no guarantee that every vessel will follow them. These security calls are also repeated on VHF FM channel 16.

Vessels inbound for Boston should make Security calls when boarding a pilot (1.5 miles east of Boston Approach Lighted Buoy BG at 42°23'27"N., 70°51'29"W.), when entering Boston North Channel at Entrance Lighted Gong Buoy NC, in President Roads abreast Deer Island, in the vicinity of Commonwealth Pier in South Boston (state whether bound for Mystic River or Chelsea River) and near the confluence of Mystic and Chelsea Rivers. Outbound vessels should make Security calls when singled up, when underway off their dock, near the confluence of Mystic and Chelsea Rivers, in the vicinity of Commonwealth Pier in South Boston, when approaching Deer Island in President Roads and when disembarking the pilot (give destination information).

(61)

(65)

(66)

(67)

(68)

Vessels inbound for Quincy or Braintree should make security calls when approaching the pilot pickup point in the vicinity of Thieves Ledge, when approaching Boston Light and when picking up tugs in Nantasket Roads off Georges Island. Outbound vessels should make Security calls when singled up, when underway off the dock, abreast Germantown Point starting out the channel and when approaching Hull.

### Northeastern approach

(56)

(58)

**Deer Island**, on the northwest side of the entrance to Boston Harbor, is about 1 mile long and is joined to the mainland by a fill. A sewage treatment facility with numerous egg-shaped holding tanks is a conspicuous landmark on the south part of the island.

**Deer Island Light** (42°20′22"N., 70°57′16"W.), 53 feet above the water, is on the outer end of a ledge that extends 0.3 mile southward from the island. A mariner radio activated sound signal at the light is initiated by keying the microphone five times consecutively on VHF-FM channel 83A.

Winthrop Head, about 1 mile northward of the northwestern end of Deer Island, is a 100-foot hill covered with buildings and a tall red, white and blue standpipe on top that is the most prominent mark in the vicinity. Sewage pump-out is available. Winthrop Beach lies along the shore just northward of Winthrop Head. About 0.2 mile off and parallel to Winthrop Beach is a breakwater about 0.4 mile long which is bare several feet at the highest tides and is fairly prominent. Small craft moor behind the breakwater; there are no landings or facilities.

Great Faun, the inner part of the shoal ground extending from the northeastern side of Deer Island, is a partly drying flat, marked on its outer part by a buoy that is about 1 mile northeastward of Deer Island Light and 0.3 mile northwestward of Boston North Channel. Little Faun, which uncovers on its inner part, extends 0.5 mile eastward from the southern end of Deer Island.

Finns Ledge, covered 27 feet, lies on the western side of the entrance to Boston North Channel, the principal approach to the harbor. The ledge, marked by a lighted bell buoy, is at the outer end of shoal ground covered less than 36 feet. The shoal ground extends about 2 miles northeastward from Deer Island. Careful navigation is required in the channel entrance, especially when incoming and outgoing vessels meet.

The Graves, a group of bare rocks and ledges about 4 miles east-northeastward of the southern point of Deer Island, extend 0.5 mile north-northeastward and 0.1 mile south-southwestward from The Graves Light. Northeast Grave, the northernmost of these rocks, uncovers 3 feet, and from it shoal ground extends about 0.3 mile northeastward; a lighted whistle buoy is moored 0.5 mile northeast of Northeast Grave. The Graves Light (42°21'54"N., 70°52'09"W.), 98 feet above the water, is shown from a light gray conical granite tower. A

mariner-activated sound signal at the light is initiated by keying the microphone five times on VHF-FM channel 83A.

**Roaring Bulls**, which partly uncover, are a group of rocks which lie from 0.5 to 0.9 mile southwestward of The Graves Light; the highest rocks uncover 8 feet.

**Green Island**, 44 feet high, is 1.2 miles southwestward of The Graves Light and 0.4 mile west-southwestward of the Roaring Bulls. The island is on a drying reef, with several other islets on it, which extends 0.3 mile southwestward from the island.

Commissioners Ledge, Devils Back and Aldridge Ledge lie 0.5 to 1 mile westward of Green Island and close southeastward of Boston South Channel; Devils Back is covered less than 1 foot over its northeast end. Between these ledges and Green Island are Maffitt Ledge, covered 17 feet, and Halftide Rocks, which uncover 3 feet. A dangerous wreck and a reported submerged obstruction are 250 to 300 yards south-southwestward of Maffitt Ledge.

Between Boston South Channel and Boston North Channel is a large area of shoal ground. The shoalest spot in this area is covered 11 feet and lies 1.6 miles northeastward of Deer Island Light.

#### Southeastern approach

**Point Allerton**, on the southeast side of the entrance to Boston Harbor, is 3.7 miles from the southern end of Deer Island. On the point is a 100-foot hill covered with buildings; a seawall protects the seaward base of the hill. A turreted tower on the hill is conspicuous.

From Point Allerton the shore extends westward for 2 miles to **Windmill Point**, which is marked by a light. A sound signal at the light is operated by keying the microphone five times consecutively on VHF-FM channel 83A. The Coast Guard has a boathouse on the southern side of Windmill Point and another about 0.3 mile eastward of the point at the **Point Allerton Coast Guard Station. Telegraph Hill**, 1 mile west of Point Allerton, is about 100 feet high and is marked by a stone tower with a conical top; the town of **Hull** is on the western slopes of the hill. Excursion vessels from Boston call at the town wharf in summer and stop at Georges Island on the way.

Nantasket Beach, extending about 3 miles south-southeastward from Point Allerton, is covered with buildings. Grassy Strawberry Hill, 1.2 miles southward of Point Allerton, is about 100 feet high. Two other grassy hills, White Head and Sagamore Hill, are on the southern part of the beach 2 and 2.4 miles, respectively, from Point Allerton. From Nantasket Beach to Cohasset Harbor, about 3 miles to the east-southeastward, the coast presents a general hilly appearance, and rocks and sunken ledges extend 0.5 mile offshore in places.

Atlantic Hill, Center Hill, and Green Hill are prominent on the stretch of coast between Nantasket Beach and Cohasset Harbor. Gun Rock is off the west

point of the entrance of a cove off **Crescent Beach**, between Center Hill and Green Hill. The cove is protected by a breakwater extending 135 yards northward from the foreshore at Green Hill; thence 330 yards westward to the vicinity of **Seal Rock**, which is about 500 yards eastward of Gun Rock.

**Black Rocks** are a group of rocky islets off Green Hill. The large 20-foot-high islet has a house on it.

(79)

Shoals extend eastward and northward from Point Allerton. Two drying rocks, about 0.1 mile apart, lie about 0.2 mile northward of the point; the eastern rock uncovers 5 feet. A lighted bell buoy is moored about 0.5 mile northward of the point. **Ultonia Ledge**, the eastern end of the broken ground, has unmarked spots covered 13 to 24 feet extending 1.3 miles east-northeastward from the point.

(72) **Harding Ledge**, 1.5 miles eastward of Point Allerton, uncovers before low water. A detached rock, which uncovers 1 foot, is 300 yards southwest of the ledge. Between Harding Ledge and Point Allerton, the bottom is very uneven, and vessels should pass outside the lighted bell buoy that is moored 0.3 mile northeast of the ledge.

Thieves Ledge, 2.3 miles east-northeastward of Point Allerton, has a least depth of 27 feet and is marked on its northeast side by a lighted whistle buoy. Patches covered 33 feet and 34 feet are 0.5 mile east by northeastward and 1 mile east-southeastward, respectively, of the lighted whistle buoy. In heavy easterly gales the sea sometimes breaks on the ledge and the patches.

Three and One-half Fathom Ledge, cleared to a depth of 18 feet, about 3 miles northeastward of Point Allerton, is marked by a lighted bell buoy about 0.2 mile southeastward of the ledge. Martin Ledge, covered 16 feet, is 0.8 mile southwest of Three and One-half Fathom Ledge and is marked on its eastern side by a buoy. Boston Ledge, covered 17 feet, is 1.4 miles southwest of Three and One-half Fathom Ledge and is marked by a buoy.

(75) Shag Rocks, 1.2 miles northward of Point Allerton and 0.3 to 0.6 mile east-northeastward of Boston Light, are 20 feet high and surrounded by extensive covered ledges and foul ground. Reefs and foul ground extend 0.5 mile east-northeastward to within 0.2 mile of Boston Ledge and west-southwestward to within 0.2 mile of Boston Light.

Nash Rock Shoal, covered 19 feet, lies about 0.4 mile southwest of Boston Light.

Boston Light (42°19'41"N., 70°53'24"W.), 102 feet above the water, is shown from an 89-foot white conical tower, on the southeast side of Little Brewster Island, about 1 mile northward of Point Allerton. A mariner radio-activated sound signal at the light is initiated by keying the microphone five times on VHF-FM channel 83A.

Great Brewster Island, 0.4 mile northwest of Little Brewster Island, is 103 feet high and has a bluff at the north end. Little Brewster and Great Brewster Islands lie on the northern side of the southeastern approach

on a drying bank, of which **Great Brewster Spit**, the western part, extends about 1 mile west-southwestward from Great Brewster Island. The western end of the spit is marked by **The Narrows Light 4**. Shoal ground extends about 0.3 mile southward from Great Brewster Spit, and on this extension are **Kelp Ledges**, awash, about 0.8 mile westward of Boston Light.

From the northern end of the bank on which Great Brewster Island lies, reefs extend about 1 mile east-northeastward and 0.7 mile northward; on the eastern extension are **Middle Brewster Island** and **Outer Brewster Island**, and on the northern extension are **Calf Island** and **Little Calf Island**. On these reefs are several islets, and off-lying them are numerous shoals, the area between the Brewsters and Shag Rocks being particularly foul. Among these dangers is **Tewksbury Rock**, covered 9 feet, which is about midway between Outer Brewster Island and Martin Ledge.

Georges Island is about 1.6 miles west-southwestward of Boston Light and 0.8 mile north-northwestward across Nantasket Roads from Windmill Point. The island is the site of historic Fort Warren and has several other buildings on it. A state recreation park is on the island, and a state landing is in a protected basin at the wharf on the west shore of the island. Daytime berthing and a limited amount of water are available. A seasonal ferry runs from the Boston waterfront to this wharf and from here to several nearby islands and to Boston.

Lovell Island is 0.3 mile northward across The Narrows from Georges Island and on the south side of Boston South Channel. A pier is on the southwest side of the island. The ruins of Fort Standish are on the island, and a cement lookout tower on the southern end of the island is prominent. Ram Head Flats and Ram Head extend up to 0.8 mile northeastward from the island; Ram Head partly uncovers.

Gallops Island, 0.3 mile northwestward of Georges Island and 0.2 mile westward across The Narrows from Lovell Island, is high with trees and brush on its northern side. The island is marked by a light off its eastern end. A sound signal at the light is operated by keying the microphone five times consecutively on VHF-FM channel 83A. A pier, protected by a breakwater, is on the southwest side. A reef named **Nixes Mate** lies on the outer part of the shoal ground that extends 0.4 mile northwestward from Gallops Island; near the center of the reef is a low islet marked by a daybeacon.

Long Island, 0.6 mile westward of Gallops Island and 0.8 mile southward across President Roads from Deer Island, is 1.5 miles long in a northeast-southwest direction and has a greatest width of about 0.25 mile. A large standpipe and the buildings of Long Island Hospital are prominent. There is a wharf on the northwest side of the island. Long Island Head Light (42°19'49"N., 70°57'28"W.), 120 feet above the water, is shown from a white brick tower on the north side of the island. The piers of a former fixed bridge are between West Head,

(93)

(97)

the south end of Long Island, and Moon Head. Private lights mark the main channel through the piers and the remaining piers are marked by private white lights.

**Spectacle Island** is on the south side of President Roads and 0.7 mile westward of Long Island. A marina and ferry dock are on the southwest side of the island; sewage pump-out is available. The island is open to the public via ferry for recreational activities.

#### Channels

(85)

Boston North Channel, Boston South Channel, and The Narrows are the main entrances from the sea to President Roads. Several other channels of less importance are used by local vessels.

Boston North Channel leads from Broad Sound to President Roads from the northeastward. It is the principal entrance to Boston Harbor. A Federal project provides for a channel 1,500 feet wide dredged to 40 feet in the eastern 900 feet and 35 feet in the western 600 feet. The channel is well marked by lighted buoys. (See Notice to Mariners and the latest edition of the chart for controlling depths.)

Boston South Channel leads from Broad Sound in a southwesterly and westerly direction to President Roads. A Federal project provides for a channel 1,200 feet wide dredged to 30 feet deep. The channel is marked by lighted and unlighted buoys. (See Notice to Mariners and the latest edition of the chart for controlling depths.)

(89) Pilots of deep-draft vessels use the North Channel most of the time. The South Channel is rarely, if ever, used, because deep-draft vessels have a tendency to feel the bottom, making steering difficult.

President Roads is the area between Deer Island and Governors Island Flats, north of Long Island, and north-northeastward of Spectacle Island. A Federal project provides for a channel 40 feet deep. (See Notice to Mariners and the latest edition of the chart for controlling depths.) North Channel, South Channel, The Narrows, Nubble Channel and Sculpin Ledge Channel are entrances to Boston Main Channel and converge at President Roads. This is a dense traffic area for fast ferries, merchant ships, tug and barge units and recreational boaters. Tug and barge units frequent the sewage treatment plant on Deer Island at the northeast end of President Roads. Its northern part is used as a general and quarantine anchorage for ships awaiting berth in Boston or Nantasket Roads. President Roads has a sand and mud bottom. The south part of President Roads is Boston Main Channel and the entrance into Boston Inner Harbor.

**Nantasket Roads**, westward of the southern entrance to The Narrows, is a good anchorage with depths up to 50 feet. There are numerous shoals in it that must be avoided by deep-draft vessels; the chart is the guide.

The Narrows is a channel that extends from Nantasket Roads northwest to President Roads. It is bounded on the northeast side by Great Brewster Spit and Lovell Island and on the southwest side by Georges Island and Gallops Island. Depths of about 26 feet can be carried in the well-marked channel; however, shoals with considerably lesser depths are along the edges of the channel.

Because of the strong currents and sharp turns, it is necessary to conn a ship by eye through the approaches and in The Narrows channel. The navigator must take precautions to prevent being set off course by crosscurrents sweeping in or out of Black Rock Channel and the channel between Gallops Island and Georges Island.

**Hypocrite Channel** is a natural channel leading between Green Island on the north and Little Calf Island on the south. The channel has several unmarked dangers and is not recommended for strangers or for large vessels.

**Black Rock Channel** leads into The Narrows from northeastward between Great Brewster Spit on the southeast and Lovell Island and Ram Head Flats on the northwest. The channel is marked by buoys. There is an unmarked rock covered 8 feet nearly in midchannel. The channel is used only by small local craft and is not recommended for strangers.

A channel 250 yards wide leads into The Narrows from westward between Georges Island and Gallops Island. A light is on the north side of the channel near the end of the shoal off the southeast end of Gallops Island. The channel is suitable only for quick-working vessels on account of the sharp turn into The Narrows.

**Nubble Channel** leads from Nantasket Roads to President Roads between Nixes Mate and Long Island; the channel is marked by buoys.

(98) Sculpin Ledge Channel leads between Long Island and Spectacle Island. It will accommodate vessels of about 8-foot draft to Hingham Bay by the passage southward of Peddocks Island. The deeper water favors Long Island, and in coming from President Roads the island should be followed at a distance of about 400 yards until up with the buoy southward of Sculpin Ledge. Pass about 300 yards southeastward of the buoy and round the southwesterly end of Long Island at a distance of 300 yards. The channel then leads between the piers of a former fixed bridge; the piers are marked by lights.

(99) A fish haven, covered 14 feet, is in Sculpin Ledge Channel. The reef is west of the standpipe on Long Island along a northeast-southwest axis in about 42°19'26"N., 70°58'15"W.

(100) A rock, covered 2 feet, is about 200 yards northeast of Sculpin Ledge.

(101) The channel leading from Nantasket Roads to Boston, southward of Long Island and Spectacle Island, is partially marked by buoys and can be used by boats of 8-foot draft with the aid of the chart.

Roads to the mouths of the Chelsea and Mystic Rivers and to Charlestown Bridge on the Charles River. The federal project depth in this channel is 35 to 40 feet.

(103) The waters adjacent to the piers and wharves extending northward from Northern Avenue Bridge to

**350** ■ U.S. Coast Pilot 1, Chapter 11 28 SEP 2025

and including Pier 4 along the Boston waterfront, west of the Boston Main Channel, are declared **nonnavigable** through Public Law 90-312. Uncharted hazards or dangers may exist in these waters. Strangers are advised to seek local knowledge before entering, and all mariners are advised to exercise caution in the area.

(104)

#### **Anchorages**

General, explosives and special anchorages are in Boston Harbor. (See **33 CFR 110.1**, **110.29**, **110.30** and **110.138**, chapter 2, for limits and regulations.)

(106) The anchorage on the north side of President Roads is the most commonly used anchorage for ships and barges in Boston Harbor. The anchorage in Nantasket Roads north of Peddocks Island has scattered shoal areas and rocks. The anchorage on the westerly side of Georges Island has a better bottom and is frequently used by vessels seeking shelter from easterly winds.

A buried high-pressure natural gas pipeline extends along the sea floor from the northwest quadrant of the precautionary area, southwest toward the south side of Georges Island, and through Anchorage 5 to West Gut. The pipeline then travels to the south, and southwest along the north side of Weymouth Fore River. Mariners are advised to use extreme caution when anchoring in these areas.

(108)

#### Currents

(109) See the Tidal Current prediction service at *tidesandcurrents.noaa.gov*. for specific information about times, directions, and velocities of the current at numerous locations throughout the area. Links to a user guide for this service can be found in chapter 1 of this book.

(110) For some distance northwestward of Cape Cod the tidal currents have a slight set into Cape Cod Bay on the flood and out of the bay on the ebb. Along the north shore of Massachusetts Bay the flood sets in a general southwesterly direction and the ebb in a northeasterly direction. The velocity of the currents is influenced greatly by the force and direction of the wind. Off the entrance to Boston Harbor, the flood sets westward and the ebb eastward, increasing slightly in velocity as the entrance is approached.

(III) The currents at Boston Lighted Whistle Buoy B are described in chapter 3.

In Broad Sound the velocity of the current at strength in most places is less than 0.8 knot. This increases to about 1 knot or more on approaching the entrances of the channels leading into Boston Harbor.

In Boston South Channel, north of Ram Head, the velocity at strength is about 1.2 knots. In the channel between Deer Island Light and Long Island Head the velocity at strength is about 1.4 knots. In Hypocrite Channel the velocity at strength is about 1 knot. In Black Rock Channel the velocity at strength is between 0.5 and 1 knot. The flood sets southwestward through the channel

and the ebb northeastward. This should be kept in mind when passing through The Narrows.

Light and Point Allerton the velocity at strength is about 1.5 knots. On the northern side of the channel southward of Great Brewster Spit the velocity is about half as great. In the middle of the channel in Nantasket Roads the velocity at strength is about 1.5 knots. In Nantasket Gut the velocity at strength is about 2.5 knots.

(115) Between Georges Island and Gallops Island the velocity at strength is about 1 knot. The flood sets westward and the ebb northeastward.

(116) Between Gallops Island and Long Island Head the velocity at strength is about 1 knot. The flood current sets southward to southwestward and the ebb in the opposite directions.

(117) Between Moon Head and Long Island, the current is rotary, turning counterclockwise. The average velocity at strength is about 0.2 knot. Usually, strength of flood sets southwestward and strength of ebb eastward. Between Thompson Island and Spectacle Island the velocity at strength is about 0.5 knot. The flood sets northwestward and the ebb southeastward.

In Boston Main Channel from Spectacle Island to the mouth of the Charles River the velocity at strength varies between 0.5 and 1 knot.

(119) Weather, Boston and vicinity

Three important influences are responsible for the main features of Boston's climate. First, the latitude (42°N.) places the city in the zone of prevailing west to east atmospheric flow in which are encompassed the northward and southward movements of large bodies of air from tropical and polar regions. This results in variety and changeability of the weather elements. Secondly, Boston is situated on or near several tracks frequently followed by systems of low air pressure. The consequent fluctuations from fair to cloudy or stormy conditions reinforce the influence of the first factor, while also assuring a rather dependable precipitation supply. The third factor, Boston's east-coast location, is a moderating factor affecting temperature extremes of winter and summer.

Hot summer afternoons are frequently relieved by the locally celebrated "sea-breeze," as air flows inland from the cool water surface to displace the warm westerly wind component. This refreshing east wind is more commonly experienced along the shore than in the interior of the city or the western suburbs. In winter, under appropriate conditions, the severity of cold waves is reduced by the nearness of the then relatively warm water. The average date of the last occurrence of freezing temperature in spring is April 8; the latest is May 3, 1874 and 1882. The average date of the first occurrence of freezing temperature in autumn is November 7; the earliest on record is October 5, 1881. In suburban areas, especially away from the coast, these dates are later in spring

and earlier in autumn by up to one month in the more susceptible localities. The average annual temperature in Boston is 51.8 °F. July is the warmest month with an average maximum of 82 °F and an average minimum of 65 °F. January is the coolest with an average high of 37 °F and an average low of 22 °F. Extremes include 102 °F in August 1975 and again in July 1977 and an extreme minimum of -12 °F in January 1957.

is 42.9 inches (1090 mm). For most years the longest run of days with no measurable precipitation does not extend much more than 2 weeks. This "dry spell" may occur at any time of year. Precipitation falls an average of 187 days each year. November is the wettest month averaging 4.4 inches (112 mm) and July the driest averaging 2.8 inches (71 mm). On 28 days each year precipitation can be expected to surpass one-half inch (13 mm) in a 24-hour period.

from showers and thunderstorms. During the rest of the year, low-pressure systems pass more or less regularly and produce precipitation on an average of roughly one day in three. Coastal storms, or "nor easters," are prolific producers of rain and snow. The main snow season extends from December through March. The average annual snowfall total is 43 inches (1092 mm). Snow falls an average 50 days in any given year and has fallen during each month October through May. The number of days with 1.5 inches (38 mm) or more of snowfall is eight per season. Periods when the ground is bare or nearly bare of snow may occur at any time in the winter.

Relative humidity has been known to fall as low as 5 percent (May 10, 1962), but such desert dryness is very rare. Heavy fog occurs on an average of about 2 days per month with its prevalence increasing eastward from the interior of Boston Bay to the open waters beyond. Fog, in whatever thickness, occurs an average of 135 days each year. Winds from the east to southwest bring fog; westerly and northerly winds clear it away.

(125) At all seasons the heaviest gales are usually from the northeastward or eastward. Although winds of 27 knots (about 32 miles per hour) or higher may be expected on at least one day in every month of the year, gales are both more common and more severe in winter. The predominant wind direction is west through northwest.

The National Weather Service office is in the Customhouse. Barometers may be compared at the Logan International Airport in East Boston.

(127) **Fogs** are prevalent throughout the year. Winds from the east to southwest bring fog; westerly and northerly winds clear it away.

# (128) **Ice**

(129) The channels of Boston Harbor are navigable throughout the year. Ice rarely forms in the main channel. Occasionally during severe winters the greater part of the harbor is frozen, but towboats and steamers keep the main

channels open. The Charles, Mystic and Chelsea Rivers and the minor passages in the harbor sometimes are frozen during severe winters. They are almost invariably kept open, however, by tugboat traffic. When ice is prevalent, the buoys may be displaced or even carried away. Local towboats can be employed for breaking ice.

# (130) Routes

(132)

(131) Boston Harbor and approaches have very broken rocky bottom, and caution is required.

# **Approaching Boston from Cape Ann**

The soundings in the vicinity of Cape Ann are very irregular and cannot be depended on to locate even approximately the vessel's position. A **228°** course from 0.2 mile off the lighted whistle buoy, 2.5 miles eastward of Cape Ann Light, clears the offshore dangers between Cape Ann and Nahant, and leads close to the lighted gong buoy marking the entrance to Boston North Channel.

(134) At night the lighted aids are sufficiently numerous to locate the position by cross bearings. In clear weather the course should be shaped to pass well northward of The Graves Light and enter through Boston North Channel.

# **Approaching Boston from Cape Cod**

Approaching the easterly side of the cape, soundings of 20 fathoms indicate a distance of 3 to 3.5 miles from shore, but off the north side of the cape, the 20-fathom curve draws closer inshore and the soundings are not so regular. Vessels standing to clear Boston Lighted Whistle Buoy B on a course of 297° from the locality of Peaked Hill Bar Lighted Whistle Buoy 2 PH will cross the southwesterly end of Stellwagen Bank in depths of 12 to 15 fathoms. Soundings on Stellwagen Bank cannot be depended on to locate a position, except near the extreme southwest end of the bank where the shoalest depth of 10 fathoms is found. The recommended route, however, for deep-draft vessels is via the Boston Traffic Separation Scheme, which is described at the beginning of this chapter.

As the entrance to Boston Harbor is approached, after crossing Stellwagen Bank, soundings of 20 fathoms or more ensure a distance of at least 5 miles from the shore and well outside of outlying rocks. Inside the depths of 20 fathoms, the soundings are very irregular and cannot be depended upon as a rule to keep a vessel out of danger. Northeast of Nahant the 20-fathom curve runs closer inshore and some of the dangers extend offshore nearly to the curve.

(138) In the approach to Boston Lighted Whistle Buoy B from the southward, the coast from Scituate to Minots Ledge Light should be given a berth of 4 miles to avoid the broken ground of Stellwagen Ledges.

#### **North Atlantic Right Whales**

(139)

(140) Endangered North Atlantic right whales may occur in the Stellwagen Bank and Jefferys Ledge area

**352** U.S. Coast Pilot 1, Chapter 11 28 SEP 2025

(153)

year-round (peak season for Jefferys Ledge: October through December; peak season in the Stellwagen Bank: early spring). This area has been designated as the Gerry E. Studds-Stellwagen Bank National Marine Sanctuary and includes the North Atlantic Right Whale Critical Habitat Northeastern Foraging Area (See 50 CFR 226.203, chapter 2, for limits and regulations.) The Pilots distribute educational material to mariners in an effort to reduce right whale ship strikes. (See North Atlantic Right Whales, indexed as such, chapter 3, for more information on right whales and recommended measures to avoid collisions with whales.)

and subject to the jurisdiction of the United States are restricted to speeds of 10 knots or less in two Seasonal Management Areas. The first area is defined as all waters of Cape Cod Bay with a northern boundary of 42°04'56.5"N., 70°12'W., to 42°12'N., 70°12'W., thence due west back to shore, and the restrictions apply between January 1 and May 15. The second area, off Race Point, is defined as the waters bounded by:

- (142) 42°04'56.5"N., 70°12'W.
- (143) 42°12'N., 70°12'W.
- (144) 42°12′N., 70°30′W.
- (145) 42°30'N., 70°30'W.
- (146) 42°30'N., 69°45'W.
- (147) 41°41'N., 69°45'W.; thence due west to the shore, and the restrictions apply between March 1 and April 30. (See 50 CFR 224.105 in chapter 2 for regulations, limitations and exceptions.)
- (148) The waters of Cape Cod Bay lie within the WHALESNORTH Mandatory Ship Reporting Area. Each self-propelled ship of 300 gross tons or greater entering WHALESNORTH must participate in the Mandatory Ship Reporting System (See 33 CFR 169, chapter 2, for limits and regulations, and chapter 3 for sample reports). Sovereign immune vessels are exempt from the requirement to report but are encouraged to participate.
- (149) The **Outer Boston Harbor Restricted Area**, a Marine Protected Area (MPA), extends 5.5 miles offshore from Hull to Nantasket.

# Entering Boston Harbor in fog

(150)

Boston Lighted Whistle Buoy B by a safe distance when approaching from either Cape Ann or Cape Cod, and the water should not be shoaled to less than 20 fathoms until the buoy is located by radar or other means. Occasionally, vessels anchored in Broad Sound have been mistaken on radar for navigational aids; caution is advised. From the buoy, steer a course to pass 0.4 mile northward of Boston Approach Lighted Buoy BG and enter the harbor via Boston North Channel. Unless Boston Lighted Whistle Buoy B is located, no attempt should be made to enter the harbor.

fog or thick weather, she may find it convenient to anchor in Provincetown Harbor or on the west side of the cape south of Provincetown, where there is a good lee and the holding ground is in 7 to 12 fathoms.

# Pilotage, Boston and vicinity

U.S. vessels under register in the foreign vessels and for U.S. vessels under register in the foreign trade. Pilotage is available for coastwise vessels not carrying an officer licensed as a pilot by the federal government for these waters. Pilots for Boston, Mystic, Chelesa River, Quincy, Weymouth, Weymouth Fore River, Back River, Town River, Lynn, Saugus and Saugus River are available from Boston Pilot Association, Pier No. 1, S. Bremen Street, East Boston, MA 02128. Telephone: office, 617–569–4500; FAX 617–569–4502; Pilot boats, 617–962–4670 (night); Internet address, bostonpilots.com. The pilot office and boats monitor and work on VHF-FM channels 13, 16 and 20 INT. Pilot services are generally arranged for in advance through ship's agents.

The pilot boats meet vessels 1.5 miles east of Boston Approach Lighted Whistle Buoy BG at 42°23'27"N., 70°51'29"W. During winter, the pilot boats may seek shelter from northwest winds under Nahant Head.

(156) The pilot boats, CHELSEA and MYSTIC, both 53 feet, have black hulls with orange superstructure and the word PILOT in black letters on the sides; both are equipped with DSC and AIS. The pilot boats will provide boarding instructions by radiotelephone on VHF-FM channel 20 INT.

(157) When about 2 hours away vessels are requested to provide an updated ETA.

### Towage

(158)

(160)

maintain radio communications on VHF-FM channels 18A and 5A. Tugs are available from Boston Towing and Transportation Co., telephone 617–567–9100 and Constellation Towing, telephone 617–561–0223. Inbound vessels are usually met in the vicinity of Anchorage areas 1 or 2. Arrangements for tugs are usually made in advance through ships' agents. Fireboats are also available; the call for the fireboat is five prolonged blasts of the ship's whistle.

# Quarantine, customs, immigration and agricultural quarantine

- (161) (See chapter 3, Vessel Arrival Inspections, and Appendix A for addresses.)
- 62) Quarantine is enforced in accordance with regulations of the U.S. Public Health Service. (See Public Health Service, chapter 1.) Quarantine anchorages for Boston Harbor are on the north side of President Roads and on Bird Island Flats.
- (163) Boston is a customs port of entry.

(164)

#### **Coast Guard**

end of Boston (see Appendix A for address). Coast Guard Station Boston is located on the south side of the mouth of the Charles River. Coast Guard Station Port Allerton is located at the end of Windmill Point in Hull. Coast Guard Station Scituate is located at the entrance to Scituate Harbor (seasonal station).

(166)

#### **Harbor regulations**

The rules and regulations of the Commonwealth of Massachusetts, the city of Boston and metropolitan area communities are enforced by the Harbor Patrol Unit of the Boston Police Department, the Massachusetts State Police Marine Unit and the Massachusetts Environmental Police. The harbor patrol boathouse is on the south side of Charles River, about 0.5 mile above the entrance. Information on boating laws can be obtained from the Massachusetts Environmental Police at 617–727–8760 or 508–790–9360 or from the Boat and Recreation Vehicle Safety Bureau, 1019 Iyanough Road (Rt 132), 2nd floor, Hyannis, MA 02601 or the Department of Fish and Game, 251 Causeway Street, Suite 400, Boston, MA 02114.

on Mystic River is within a **safety zone**. Additionally, the waters surrounding loaded LNG vessels transiting Boston Harbor are a **safety zone**. (See **33 CFR 165.110**, chapter 2, for limits and regulations.)

(169)

#### **Wharves**

(170) The Port of Boston has many piers and wharves, most of which are located on the main channel at South Boston, East Boston and Charlestown and on the Chelsea River and Mystic River.

The piers and wharves generally are of open-pile concrete deck construction, extending from stone or timber bulkheads with solid fill. Only the deep-draft facilities are described; the other active facilities in the port are used as repair berths and by government vessels, fishing vessels, small craft and barges. The alongside depths for the facilities described are reported; for information on the latest depths contact the Massachusetts Port Authority or the private operator. All of the facilities have direct highway connections, and some have railroad connections. Water connections are available at most piers and wharves.

(172) General cargo at the port is usually handled by ship's tackle, except container vessels use shore side equipment; special handling equipment, if available, is mentioned in the description of the particular facility.

Numerous warehouses and cold storage facilities adjacent to the waterfront are available.

All of the large general cargo terminals are owned or leased by the Massachusetts Port Authority. Containerized cargo is handled at the Paul W. Conley Marine Terminal. Most of the deepwater oil and bulk terminals are on the Chelsea River and Mystic River.

The office of the Port Director is at One Harborside Drive, Suite 200S, East Boston, MA 02128-2909; telephone 617–946–4413.

(176) **Facilities at South Boston**:

# 77) Massachusetts Port Authority, Paul W. Conley Marine Terminal, Berths 11-15:

Berth 15 (42°20′25"N., 71°00′41"W.): southwest side of Boston Main Channel; 570-foot face, 35 feet alongside; deck height, 15 to 16 feet; owned and operated by Massachusetts Port Authority.

(179) Berth 14 (42°20'29"N., 71°00'47"W.): southwest side of Boston Main Channel; 630-foot face, 35 feet alongside; deck height, 15 to 16 feet; owned and operated by Massachusetts Port Authority.

Berth 13: adjacent westward of Berth 14 on south side of Reserved Channel; 1,000 feet of berthing space; 40 feet alongside; deck height, 15 to 16 feet.

side of Reserved Channel; 2,040 feet of berthing space; 45 feet alongside; deck height, 15 to 16 feet; 101 acres open storage; two 40-ton container cranes and two 50-ton container cranes; owned and operated by Massachusetts Port Authority.

B2) Coastal Oil New England, South Boston Ship Dock (42°20'30"N., 71°01'37"W.): south side of Reserved Channel; 85-foot, 700 feet of berthing space with dolphins; 38 feet alongside; deck height, 14 feet. Owned by El Paso Gas Company. This facility is presently closed.

#### (183) **Boston Marine Industrial Park, Berths 1-9:**

(184) Berth 6 (42°20'37"N., 71°01'31"W.): north side of Reserved Channel, 540-foot face; 35 feet alongside; deck height, 17½ feet; owned by Massachusetts Port Authority.

(185) Berths 1-3 (42°20'38"N., 71°01'17"W.): 964-foot face (upper side), 352-foot face (lower side); 35 feet alongside; deck height, 17½ feet; pipelines extend to storage silos with capacity of 18,700 tons of cement at a rate of 420 tons per hour; receipt of bulk cement; owned by Massachusetts Port Authority and operated by Boston Marine Industrial Park, Massachusetts Port Authority, and Coastal Cement Corp.

Black Falcon Cruise Terminal Berths 7, 8 and 9 (42°20'36"N., 71°01'56"W.): north side of Reserved Channel, approximately 2,000 feet from the entrance, 2,100-foot face; 35 feet alongside; deck height 17½ feet; passenger terminal for cruise vessels; owned and operated by Massachusetts Port Authority. A security zone is in effect around cruise ships moored at this facility (See 33 CFR 165.116, chapter 2).

Massachusetts Port Authority, Marine Terminal Wharf North Jetty (42°20'57"N., 71°01'44"W.): 800-foot face; 35 feet alongside; deck height, 16 feet; 47 acres of open storage; receipt of miscellaneous dry bulk commodities; owned by Massachusetts Port Authority. This wharf is closed to all vessels except government vessels.

**354** U.S. Coast Pilot 1, Chapter 11 28 SEP 2025

Massachusetts Port Authority, Commonwealth Pier (42°21'11"N., 71°02'21"W.): 400-foot face, southeast and northwest sides, 1,200 feet long; 33 to 38 feet alongside; deck height, 18 feet; mooring excursion vessels and passenger ferry terminal for cruise vessels; owned by Massachusetts Port Authority and operated by World Trade Center.

#### (189) Facilities at Charlestown:

(190) Mystic Piers 48-50 (42°22'58"N., 71°02'51"W.): 423-foot face (northeast side), 360-foot face (east side), 560-foot face (south side); 25 feet alongside; deck height, 18 feet; open storage; receipt of dry bulk cargo; owned by Massachusetts Port Authority. This facility is closed.

(191) Facilities on Mystic River, south bank:

United States Gypsum Co. Wharf (42°23'02"N., 71°02'58"W.): immediately westward of Mystic River-Tobin Memorial Bridge; 492 feet of berthing space; 27 feet alongside; deck height, 14½ feet; open storage for 38,000 tons; storage silos for 25,000 tons; receipt of gypsum rock from self-unloading vessels; owned and operated by United States Gypsum Co.

(193) **John F. Moran Terminal Wharf** (42°23'04"N., 71°03'12"W.): immediately westward of United States Gypsum Co. Wharf; 1,100-foot face, 40 feet alongside; deck height, 17½ feet; 50 acres open storage; receipt and shipment of automobiles and general cargo; owned by Massachusetts Port Authority and operated by Boston Autoport, LLC.

(194) **Lafarge Cement Boston Terminal** (42°23'05"N., 71°03'35"W.): approximately 0.5 mile above Mystic River - Tobin Memorial Bridge; 610-foot face, 31 feet alongside; deck height, 16.4 feet.

(195) **Medford Street Terminal** (42°23'06"N., 71°03'41"W.): approximately 0.6 mile above Mystic River-Tobin Memorial Bridge; this facility is closed.

(196) Facilities on Mystic River, north bank:

Global Companies, Chelsea Terminal Wharf (42°23'06"N., 71°02'40"W.): 560 feet of berthing space with dolphins; 35 feet alongside; deck height, 14 feet; storage tanks with 630,500-barrel capacity; receipt and shipment of petroleum products; bunkering vessels; owned and operated by Global Companies.

(198) Exxon Co., U.S.A., Everett Terminal Wharf, Berth 1 (42°23'17"N., 71°03'21"W.): on west side of Island End River at junction with Mystic River; 300 feet of berthing space; 21 feet alongside; deck height, 15 feet; receipt and shipment of petroleum products; owned and operated by Exxon Co., U.S.A.

Exxon Co., U.S.A., Everett Terminal Wharf, Berths 3 and 4 (42°23'17"N., 71°03'29"W.): Berth 3, 155-foot face; Berth 4, 90-foot face; 950 feet total berthing space with dolphins; 35 to 40 feet alongside; deck height, 15 feet; pipelines extend to storage tanks with 2½-million-barrel capacity; receipt and shipment of petroleum products,; receipt of asphalt; owned and operated by Exxon Co., U.S.A.

00) **Distrigas of Massachusetts Corp. Wharf** (42°23'19"N., 71°03'43"W.): 0.1 mile west of Exxon Co.,

U.S.A. Wharf; 67-foot face, 1,000 feet of berthing space with dolphins; 36 feet alongside; deck height, 17 feet; pipelines to storage tanks with 974,000-barrel capacity; receipt of liquefied natural gas; owned and operated by Distrigas of Massachusetts Corp.

O.2 mile west of Exxon Co., U.S.A. Wharf; 320-foot face, 820 feet of berthing space with dolphins; 40 feet alongside; deck height, 14 feet; 35-ton crawler crane; conveyor system with loading rate of 1,000 tons per hour; shipment of scrap metal; owned by Hugo Neu Steel Products, Inc., and Prolerized Transport Systems, Inc., and operated by Prolerized New England Co.

(202) Facilities on Chelsea River, north bank:

Gulf Oil Limited Partnership, Chelsea Terminal Tanker Wharf (42°23'35"N., 71°01'03"W.): 60-foot face, 710 feet of berthing space; 36 feet alongside; deck height, 14 feet; pipelines extend to storage tanks with 1.1-million-barrel capacity; receipt and shipment of petroleum products; bunkering vessels; owned and operated by Gulf Oil Limited Partnership.

Facilities on Chelsea River, south bank:

(42°23'06"N., 71°01'28"W.): 600 feet of berthing space; 38 feet alongside; deck height, 16 feet; pipelines extend to storage tanks with 1-million-barrel capacity; receipt and shipment of petroleum products; owned and operated by Mobil Oil Corp.

1 Irving Oil Co., Revere Marine Terminal, Ship Pier (42°23'48"N., 71°00'44"W.): north side has 600 feet of berthing space; 36 feet alongside; south side has 21 feet alongside; deck height, 15 feet; pipelines extend to storage tanks with 760,000-barrel capacity; receipt and shipment of petroleum products; bunkering vessels.

(207) Global Revco Terminal, Ship Pier (42°23'51"N., 71°00'48"W.): south side has 600 feet of berthing space; 37 feet alongside; deck height, 15 feet; pipelines extend to storage tanks with 1¼-million-barrel capacity; receipt and shipment of petroleum products; bunkering vessels.

BP Oil Co. Pier (42°23'48"N., 71°00'45"W.): north and south sides 550 feet of berthing space; north side 10 to 21 feet alongside, south side 10 to 35 feet alongside; deck height, 15 feet; pipelines extend to storage tanks with 1½-million-barrel capacity; receipt and shipment of petroleum products; owned and operated by BP Oil Co. and Global Petroleum Co.

(209) Coastal Oil New England, Ship Pier (42°23'51"N., 71°00'48"W.): south side has 600 feet of berthing space; 37 feet alongside; deck height, 15 feet; pipelines extend to storage tanks with 1¼-million-barrel capacity; receipt and shipment of petroleum products; bunkering vessels; owned and operated by Coastal Oil New England, Inc.

#### **Supplies**

(210)

(211) Provisions and marine supplies of all kinds are available in the port of Boston. All grades of heavy marine bunker fuel, lubricants and diesel fuel can be obtained.

Vessels may bunker directly at several of the marine oil terminals or may be serviced by barges at anchor or at loading berths. Gasoline can be obtained at the marinas or from barges anchored in the stream in the summer.

(212)

# Repairs

The port of Boston has excellent facilities for making all types of hull and engine repairs to vessels of all sizes. Several of these firms operate waterfront facilities for the construction, repair and conversion of oceangoing vessels, tugs and towboats, barges and various types of small vessels. In addition, there are a number of firms without waterfront facilities that are engaged in marine repair work. These companies maintain shops and portable equipment for making above-waterline repairs and for installing equipment, gear and machinery on all types of craft at their berths. There are several drydocks and marine railways available in the port. The largest repair facility is located in South Boston. The South Boston yard has a graving dock with a length of 1,175 feet and a width of 127 feet at the entrance and a depth of 36 feet over the sill. Cranes to 50 tons are at the yard.

(214) A marine railway in the port can handle vessels to 180 feet long and 1,000 tons.

(215) Several smaller repair facilities in the port cater to yachtsmen and small-craft operators.

(216)

# **Communications**

Boston is the terminus of two trunk railroads. About 35 commercial shipping lines serve the port in foreign trade to or from over 175 world ports. There is little or no coastwise traffic except in bulk gypsum, liquid sulfur, cement and petroleum.

(218) Several major airlines provide frequent scheduled services between Logan International Airport in East Boston and domestic and overseas points.

(219) Boston has through bus and rail service to all points. There are numerous trucking firms engaged in long- and short-haul freight service from the port.

(220)

#### **Small-craft facilities**

Open Public float landings for small craft are at Summer Street, Northern Avenue, on Charles River, and several other places along the waterfront. Small-craft facilities at Boston and Charlestown can provide berths with electricity, water, ice, marine supplies, wet storage and sewage pump-out; complete hull, engine and electronic repairs are available.

(222)

# **Boston Habor**

(223) **East Boston**, on the northeastern side of Boston Harbor, is separated from the city of Chelsea by Chelsea River. The waterfront has modern piers and a large ship repair yard. These facilities were described earlier in this chapter under Wharves, Boston Harbor.

The Jeffries Yacht Club is in the cove adjacent westward of Logan International Airport. A boatyard, close southwestward of the yacht club, has pump-out facilities and a marine railway that can handle vessels up to 100 tons for hull and engine repairs; a 10-ton crane is also available. A **fireboat** moors on the east side of the cove.

(225) Chelsea is separated from Charlestown, on the western side of the harbor, by the Mystic River. Charlestown is separated from Boston proper by the Charles River. Charleston Navy Yard is located on the north side of the mouth of the Charles River and is home to the U.S.S. Constitution and U.S.S. Cassin Young.

A **safety zone** has been established around the Constitution when moored and underway and the Cassin Young while underway. (See **33 CFR 165.20**, **165.23**, **165.111**, and **165.112**, chapter 2, for limits and regulations.)

(227) South Boston is on the peninsula southeast of the city proper, from which it is separated by Fort Point Channel.

(228) A "no-wake" **speed limit** is enforced in the inner harbor from Pier #7 in South Boston to the northwest corner of Logan International Airport.

Logan International Airport is between Governors Island Flats and East Boston. The airport area, almost entirely filled land, is low, flat and quite extensive. The airport control tower is conspicuous. Governors Island, on the northeast side of Boston Main Channel and at the southerly end of the airport, is a low grass-covered peninsula.

Vessel Reporting Advisory: Operations in Vicinity of Logan International Airport. Vessels operating near Boston's Logan International Airport have the potential to affect procedures for aircraft landing and departing at the airport. Vessels with an air draft of 85 feet or greater require that advisories be issued to aircraft by air traffic controllers and in some instances that runway use be restricted. Notification by these vessels of maximum air draft when operating in the vicinity of the airport is intended to provide aircraft important notice of potential obstructions.

Wessels with an air draft height of 85 feet (26 meters) or greater are advised to report their maximum air draft heights (including masts, cranes, antenna or other projections) when anchored or in transit in Boston Harbor between Deer Island and the World Trade Center. Notification is to be made to the Massachusetts Port Authority's Communication Center, preferably via telephone, at 617–561–1919. Vessels without telephone capability are requested to provide notification to Coast Guard Sector Boston on VHF channel 81, to be relayed via telephone to the Massachusetts Port Authority's Communication Center.

Please supply the vessel's name, maximum air draft (including masts, cranes, antenna and other projections), destination, and estimated time that the vessel will be transiting/anchored/moored in Boston Harbor between

(235)

Name∙Description•Type	Location	Clear Width of Draw or Span Opening (feet)	Clear Height above Mean High Water (feet)	Information
Reserved Channel				
Summer Street Bridge (fixed)	42°20'32"N., 71°02'10"W.	40	6	
Fort Point Channel				
Northern Avenue Bridge (fixed)	42°21'16"N., 71°02'58"W.	76	7	
Northern Avenue Bridge (fixed)	42°21'14"N., 71°03'00"W.	75	16	
Congress Street Bridge (fixed)	42°21'07"N., 71°03'04"W.	75	6	
Summer Street Bridge (fixed)	42°21'03"N., 71°03'05"W.	51	8	
Charles River				
Charlestown Bridge (fixed)	42°22'06"N., 71°03'34"W.	50	23	Bridge is under construction (2018)
I-93 Mainline Bridge (fixed)	42°22'09"N., 71°03'49"W.	581	38*	
Storrow Drive Bridge (fixed)	42°22'08"N., 71°03'52"W.	344	44**	
MBTA/Amtrak Bridges (bascule)	42°22'08"N., 71°03'55"W.	65	3***	Note 1
Charles River Dam Bridges (bascule)	42°22'02"N., 71°04'08"W.	50	5***	Note 1
Longfellow Bridge (fixed)	42°21'41"N., 71°04'31"W.	187	29*	Bridge is under construction (2017)
Little Mystic Channel				
Chelsea Street Bridge (fixed)	42°22'48"N., 71°03'07"W.	75	9	
Route 1 Bridge (fixed)	42°22'48"N., 71°03'07"W.	75	100	
Mystic River				
Mystic River-Tobin Memorial Bridge (fixed)	42°23'05"N., 71°02'51"W.	600	135	
Malden/Alford Street Bridges (highway/bascule)	42°23'22"N., 71°04'16"W.	74	12	Note 2
MBTA Railroad Bridge (fixed)	42°23'35"N., 71°04'28"W.	74	30	
railroad bridge (fixed)		74	30****	
Wellington/Middlesex Avenue Bridge (fixed)	42°23'58"N., 71°05'01"W.	50	16****	Note 2
Harvard Street-General Lawrence Bridge (fixed)	42°24'22"N., 71°05'51"W.	50	13****	
Route 93 Bridge (fixed)	42°24'53"N., 71°06'14"W.	81	16****	
Malden River				
Woods Memorial/Revere Beach Pkwy (fixed)	42°24'14"N., 71°04'21"W.	80	21*	Bridge is under construction
Chelsea River				
Andrew P. McArdle Bridge (bascule)	42°23'08"N., 71°02'21"W.	175	20	Notes 4 and 5
Chelsea Street Bridge (vertical lift)	42°23'10"N., 71°01'22"W.	175	9 (down), 175 (up)	Notes 4 and 5

<sup>\*\*\*\*</sup> Vertical clearances are referenced to Normal Pool Elevation, which is 6.2 feet above mean low water.

Deer Harbor and the World Trade Center. Also supply a point of contact and call-back method of communication for the vessel while operating in the specified area.

Castle Island, on the southwest side of Boston Main
Channel 1 mile northwestward of Spectacle Island, is
marked by Fort Independence. It is connected to the
shore westward by filled land. Several boulders bare at
low water are a short distance southeastward of Castle
Island. This area should be avoided. On the northeast
corner of the island is the 52-foot granite Donald McKay
Monument, erected in 1933 to commemorate the famous
East Boston builder of clipper ships.

(234) Pleasure Bay, just westward of Castle Island, is closed by an earth-filled dam extending from the southern end of the island to the jetty light southeastward of **City Point.** 

(236) **Reserved Channel**, 0.5 mile northwestward of Castle Island, is a dredged unmarked channel that leads westward from the Boston Main Channel for about 1 mile.

There are modern and extensive freight terminals on the north and south sides of Reserved Channel; these facilities were described earlier in this chapter under Wharves, Boston Harbor.

(238) **Fort Point Channel** separates Boston proper from South Boston. A dredged channel leads from the entrance to the Summer Street Bridge. Vessels bound for Fort Point Channel may require the assistance of a tug.

Note 1 – See 33 CFR 117.1 through 117.59 and 117.591, chapter 2, for drawbridge regulations.

Note 2 – See 33 CFR 117.1 through 117.59 and 117.609, chapter 2, for drawbridge regulations.

Note 3 – See 33 CFR 117.1 through 117.59 and 117.593, chapter 2, for drawbridge regulations.

Note 4 – The bridgetender monitors VHF-FM channel 16 and works on channel 13.

(239)

# **Anchorage**

A special anchorage is just north of the entrance to Fort Point Channel. (See 33 CFR 110.1 and 110.29, chapter 2, for limits and regulations.)

Charles River, on the western side of the harbor (241)between Boston proper and Charlestown, is the approach by water to Cambridge and Watertown. There are two dams over the Charles River. The first is about 0.5 mile above the entrance to the river. The dam has three locks; the large north lock has a usable length of 300 feet and width of 40 feet with 14 feet over the sill; the other two locks have usable lengths of 200 feet with widths of 25 feet and 6 feet over the sills. The second dam is about 1 mile above the entrance. This dam has a single lock with usable dimensions of 350 feet by 45 feet with 17 feet over the sill; the lock is no longer in use and is maintained in the open position. (See 33 CFR 207.10, chapter 2, for regulations governing the use, administration and navigation of the locks.) A no wake speed limit is enforced between the entrance to Charles River and the first Charles River Dam.

Charles River above the dams is maintained at a height of 7.2 feet above mean low water. The river above the dams is used by many yachts and small craft. No toll is charged for passage through the locks. There are four yacht clubs on the river, some college sailing and rowing clubs, a large marina below the dams and two public float landings above the dams. Pump-out facilities are available at Cambridge and Watertown.

3) **Little Mystic Channel** is a slip about 0.5 mile long 0.2 mile south-southeast of the mouth of the Mystic River at Charlestown. A wreck, covered 18 feet, is just eastward of the bridge in the middle of the channel and a wreck, covered 12 feet, is about 0.2 mile westward of the bridge.

4) Chelsea River, locally known as Chelsea Creek, emptying into Boston Harbor from eastward between East Boston and Chelsea, is the approach to important wharves and facilities and to the city of Revere at the head, 2.6 miles above the entrance. The dredged channel and turning basin in the river have a project depth of 38 fact.

(245) Chelsea River has a heavy traffic of deep-draft oil tankers. The tankers berth at the oil company terminals and storage areas on both banks of the river. These facilities were described earlier in this chapter under Wharves, Boston Harbor.

(246) Mystic River, which empties into Boston Harbor opposite Chelsea River, is the approach by water to the towns of Medford and Malden.

(247

#### **Anchorages**

Special anchorages are on either side of the north end of the Mystic River-Tobin Memorial Bridge. (See 33 CFR 110.1 and 110.29, chapter 2, for limits and regulations.)

locks, crosses the Mystic River about 1.6 miles above the mouth. The largest lock, a commercial-vessel type, has a length of 325 feet, a width of 45 feet, and depths of 15.5 feet over the lower sill and 11.5 feet over the upper sill. Two smaller parallel locks just westward have lengths of 120 feet, widths of 22 feet, and depths of 6.5 feet over the lower sills and 0.5 foot over the upper sills. (See 33 CFR 207.9, chapter 2, for regulations governing the use, administration and navigation of the locks.) There are no overhead vertical restrictions on any of the locks.

Just westward of the railroad bridge. Gasoline, water, ice, marine supplies, storage facilities, a small-craft launching ramp and a 15-ton mobile hoist are available; hull, engine and electronic repairs can be made.

There are two yacht clubs on the river above the mouth of the Malden River: the Winter Hill at Somerville and the Riverside at Medford. The Chelsea Yacht Club is on the north bank on the east side of the Mystic River-Tobin Memorial Bridge. Gasoline, diesel fuel, water and electricity are available at the floats, which have 30 feet alongside.

Island End River is a tributary of the Mystic River entering from northward, 0.5 mile above the entrance. Three companies maintain wharf facilities on the west side of the river. A rocky area on the east side of the entrance, and the current of Mystic River running across the entrance, make navigation difficult for large vessels. A tug usually is employed to assist such vessels. A dredged channel leads to a marina basin near the head of the river; the channel is marked by daybeacons. A pump-out facility is available at the marina.

Malden River, a tributary of Mystic River from northward, has a privately dredged channel for a distance of 1.6 miles upstream.

(254)

# **Winthrop to Worlds End**

North and west of President Roads is an area of flats, much of which bares at low water. Between **Deer Island Flats** and **Governors Island Flats**, a buoyed channel leads to Cottage Park Yacht Club at **Winthrop**. Another buoyed channel, branching to the east, leads to Winthrop Head and is marked by a light just west of the entrance. **Snake Island**, on the westerly side of the channel, is 10 feet high with low trees.

(256) The Winthrop Yacht Club, a wharf with depths of about 5 feet alongside its floats, and a marina are on the east bank of Winthrop Head. Gasoline, diesel fuel, water, ice, a 10-ton lift, a small-craft launching ramp, some marine supplies, and limited overnight berthage are available at the marina; hull and engine repairs can be made. Pumpout service is available from the Town of Winthrop.

(257) The westerly channel leading to **Belle Isle Inlet** has a controlling depth of about 15 feet. A **special anchorage** 

Structures across Neponset River							
Name•Description•Type	Location	Clear Width of Draw or Span Opening (feet)	Clear Height above Mean High Water (feet)	Information			
Dorchester Bay Basin							
William T. Morrisey Boulevard Bridge (bascule)	42°18'14"N., 71°02'53"W.	65	12	Note 1			
Neponset River							
Old Colony Railroad Bridge (fixed)	42°17'08"N., 71°02'18"W.	109	30				
Route 3A Bridge (fixed)	42°17'04"N., 71°02'24"W.	80	30				
Neponset River Bridge (highway/fixed)	42°16'39"N., 71°02'56"W.	130	33				
Granite Avenue Bridge (bascule)	42°16'39"N., 71°03'12"W.	50	6	Note 2			
Note 1 – See 33 CFR 117.1 through 117.59 and 117.597, chapter 2, for drawbridge regulations.  Note 2 – See 33 CFR 117.1 through 117.59 and 117.611, chapter 2, for drawbridge regulations.							

is off the Pleasant Park Yacht Club, just south of the inlet. (See **33 CFR 110.1** and **110.29**, chapter 2, for limits and regulations.) The highway bridge over the mouth of the inlet has a 35-foot fixed span with a clearance of 7 feet. Marinas near the yacht club can provide berths, some marine supplies, covered storage, a 50-foot marine railway; hull and engine repairs. Farther west of the mouth of the inlet are the Orient Heights and East Boston Yacht Clubs. Fuel, water and various services are available at the yacht clubs.

President Roads between **Spectacle Island** and **Thompson Island** on the east and South Boston on the west. The bay is filled with extensive flats, large areas of which are nearly bare at low water and rise abruptly from the edge of the channel. There is no deep-draft vessel traffic in Dorchester Bay. The John F. Kennedy Memorial Library on **Columbia Point** (42°18'54"N., 71°02'22"W.) is prominent. A state-maintained small boat channel leads from the main channel in Dorchester Bay to a turning basin near the JFK Memorial Library.

(259)

#### Anchorages

Special and general anchorages are in Dorchester
 Bay. (See 33 CFR 110.1, 110.30 and 110.138, chapter
 2, for limits and regulations.) The yacht anchorage most commonly used is south and east of City Point, clear of the cable area.

Old Harbor, on the west side of Dorchester Bay, just south of South Boston, is filled with flats having little water over them. A channel with a least depth of 5 feet leads to the yacht clubs and the public float in the northeastern part of the harbor, westward of City Point. Gasoline and diesel fuel are available.

(262) **Squantum Channel** leads from the main channel in Dorchester Bay to a marina east of **Squantum Point**. The channel to the basin, which is enclosed and protected by stone breakwaters, is marked by buoys. Gasoline, diesel fuel, water and electricity can be obtained at the floats, and a 30-ton mobile hoist, storage facilities, marine supplies and a pump-out facility are available; hull, engine and electronic repairs can be made.

Dorchester Bay Basin, on the southwest side of Dorchester Bay, is entered about 0.2 mile westward of Commercial Point, the western entrance point to Neponset River. A channel, privately marked by seasonal buoys, leads to a yacht club on the northwest side of the basin. Gasoline, water, ice and a pump-out station are available. A rock awash is reported immediately eastward of the north draw of the highway bridge.

Neponset River enters Dorchester Bay from the south between Commercial Point and Squantum Point. A dam is at Milton, 3 miles above the mouth. Small craft with local knowledge navigate to Milton during times of high water.

(266) Several yacht clubs are on the river. Gasoline, diesel fuel, water, ice, marine supplies, a pump-out facility, storage facilities and lifts up to 40 tons are available at a large marina on the west side about 1 mile above the mouth; complete hull, engine and electronic repairs can be made.

Quincy Bay indents the southerly shore of Boston Harbor between the peninsulas of Squantum and Houghs Neck. Depths in the bay are in general 8 to 10 feet, but shoals partly bare at low water extend 0.5 to 0.7 mile from its southerly side.

#### **Anchorages**

(268)

(269) Special anchorages are in Quincy Bay. (See 33 CFR 110.1 and 110.30, chapter 2, for limits and regulations.)

The wharf extending from the south side of **Rainsford**Island, at the northeastern entrance to Quincy Bay, is in ruins. Quarantine Rocks extend 0.5 mile southward of the island

(271) Sunken Ledge, bare at low water, is about 1 mile southward of Rainsford Island. A daybeacon is on the ledge, and a lighted buoy is 0.2 mile southeast of it. A buoy marks a channel west of the ledge.

Hangman Island, small and rocky, is near the middle of the entrance to Quincy Bay, 0.6 mile southwestward of Sunken Ledge. The end of a reef extending 0.2 mile southwestward from the islet is marked by a daybeacon. Two charted rocks with depths of 6 feet and 4 feet are 0.4 mile northward of the daybeacon.

(286)

(273) **Wreck Rock**, 0.6 mile southeast of Hangman Island, is covered 3 feet and marked on the north end by a buoy.

Squantum is on the west side of Quincy Bay. Moon Head, which can be recognized by the grassy hill and bluff on its easterly end, is connected to Squantum by a causeway. A Boston Fire Department training center is prominent on the northeast side.

(275) Achannel leads northward from Quincy Bay between Moon Head and Long Island, and the piers of a former fixed bridge. The piers on either side of the channel are marked by private lights. The channel continues northwesterly and connects with Presidents Roads via Western Way, between Thompson and Spectacle Islands, or by Sculpin Ledge Channel, westward of Long Island.

(276) Wollaston Channel, privately maintained, leads southwestward from the westerly end of Quincy Bay to the small basin of the Squantum and Wollaston Yacht Clubs. With local knowledge, 6 feet was reported to be carried in the entrance channel and basin. The channel is marked by buoys.

Houghs Neck, on the southeast side of Quincy Bay, is marked at its northeasterly end by Quincy Great Hill, 100 feet high and mostly settled. Nut Island, marked by a power station and stack, is connected by a causeway 300 yards northward of Quincy Great Hill.

A private daybeacon marks the outer end of an overflow pipeline extension with riprap cover, off the northeast end of Nut Island. The pipeline extends 150 yards into the bay and is submerged at high water. **Pig Rock**, about 0.6 mile eastward of Nut Island, is visible at all stages of the tide. Rocks awash are close east of Pig Rock.

(279) The Quincy Yacht Club is on the eastern side of Houghs Neck. A channel, marked by buoys, leads to the club wharf.

#### **Anchorages**

A **special anchorage** is off the east side of Houghs Neck. (See **33 CFR 110.1** and **110.30**, chapter 2, for limits and regulations.)

off the east side of Houghs Neck and is marked by buoys off its north and south ends. Give Spiers Stand a wide berth, as several groundings have been reported in its vicinity.

Peddocks Island, 0.5 mile northeast of Houghs Neck, is long and narrow with hills in the middle and at both ends, with low land between. The remains of the brick buildings of old Fort Andrews are visible. Caution is advised against approaching the island too closely because of rocks awash. West Head is reserved as a bird sanctuary.

West Gut is a buoyed channel leading into Hingham Bay between Nut Island and Peddocks Island. The channel through West Gut has a controlling depth of about 19 feet. A rock covered 17 feet is in the channel about 0.3 mile east-northeastward of Nut Island.

Hingham Bay is that part of Boston Harbor southeastward of Peddocks Island. It is the approach to Weymouth Fore River, Weymouth Back River, Hingham Harbor and Weir River. Extensive shoals make out from the southerly shore and surround the islands in the bay. Hull Bay, the eastern part of the bay, also has many shoal areas.

# Anchorages

Special anchorages are in Hull Bay. (See 33 CFR 110.1 and 110.31, chapter 2, for limits and regulations.)

(288) The easterly entrance to Hingham Bay is through Hull Gut, but the entrance through West Gut, southward of Peddocks Island, is frequently used by vessels bound into Weymouth Fore or Weymouth Back Rivers.

(289) Hull Gut, a dredged channel between Peddocks Island and Windmill Point, leads into Hingham Bay from Nantasket Roads and is a section of the Weymouth Fore River Channel improvement. Unmarked submerged rocks cleared to a depth of 16 feet are about 500 yards southward of Windmill Point Light WP.

# Current

(290)

(293)

(291) The tidal currents have an average velocity of about 2 knots at strength and generally follow the direction of the channel; the flood sets southward and the ebb northward.

(292) A channel about 13 feet deep, commencing just southward of the buoy marking **Inner Seal Rock**, about 0.6 mile southeastward of Windmill Point Light, leads to a wharf on the northwest side of **Spinnaker (Hog) Island**. The island is connected to the mainland by a causeway and fixed bridge.

### **Anchorages**

(294) A channel, privately marked by seasonal buoys, eastward of Spinnaker Island, leads northward to a special anchorage in Allerton Harbor. (See 33 CFR 110.1 and 110.31, chapter 2, for limits and regulations.) The Hull Yacht Club is on the north side of the harbor.

A marina with depths of about 6 feet alongside its floats is at **Waveland**, about 0.7 mile southeastward of Spinnaker Island. Gasoline, diesel fuel, water, ice, electricity, marine supplies, a small-craft launching ramp and lifts up to 30 tons are available; hull, engine and electronic repairs can be made.

Weymouth Fore River has its entrance on the southwest side of Hingham Bay between Houghs Neck and Grape Island and is the approach by water to Quincy Point, Weymouth, East Braintree and several landings. An electric power plant and several other industries are on the river. Waterborne commerce is principally in petroleum products.

7) **Grape Island**, on the south side of Hingham Bay, has a recreational pier on the southerly side of the island. Ruins of several buildings, nature trails and picnic areas are on the island. Primitive camping is permitted.

**360** U.S. Coast Pilot 1, Chapter 11

(304)

Structures across Weymouth Fore and Weymouth Back Rivers						
Name+Description+Type	Location	Clear Width of Draw or Span Opening (feet)	Clear Height above Mean High Water (feet)	Information		
Weymouth Fore River						
State Route 3A Bridge (vertical lift)	42°14'39"N., 70°58'03"W.	175	175 (open) 60 (closed)	Notes 1 and 2		
Overhead power cable	42°14'10"N., 70°57'51"W.		150			
Overhead power cable	42°13'53"N., 70°57'42"W.		100			
Overhead power cable	42°13'40"N., 70°57'40"W.		60			
State Route 53 Bridge (fixed)	42°13'25"N., 70°58'08"W.	51	11			
Weymouth Back River						
Lincoln Street Bridge (fixed)	42°14'49"N., 70°55'54"W.	70	36			
Overhead power cables	42°14'49"N., 70°55'54"W.		55			
Note 1 – See 33 CFR 117.1 through 117.59 and 117.621, chapter 2, for drawbridge regulations.  Note 2 – The Bridgetender monitors VHF-FM channel 16 and works on channel 13; call sign WRD-634						

(298) The following are prominent upon entering Weymouth Fore River; a tank on Weymouth Great Hill, the bridge at Quincy Point and the large stacks of the power plant on the east side of the river just above the bridge.

(299) Sewage pump-out is available at the Wessagusset Yacht above Weymouth Great Hill.

(300)

#### Channels

Nantasket Roads, Hull Gut and Hingham Bay, thence into Weymouth Fore River; a turning basin is on the south side of the channel at Kings Cove. The channel through West Gut is described earlier in the chapter. For detailed channel information and minimum depths as reported by the U.S. Army Corps of Engineers (USACE), use NOAA Electronic Navigational Charts. Surveys and channel condition reports are available through a USACE hydrographic survey website listed in Appendix A.

(302)

# **Anchorages**

(303) **Special anchorages** are in Weymouth Fore River. (See **33 CFR 110.1** and **110.30**, chapter 2, for limits and regulations.)

(305)

# Weather, South Weymouth and vicinity

South Weymouth is about 3 miles south-southwest of Weymouth. South Weymouth averages about 11 days each year with maximum temperatures in excess of 90 °F. July is the warmest month with an average high of 82 °F and an average minimum of 63 °F. January is the coolest month with an average high of 36 °F and an average minimum of 19 °F. The highest temperature on record for South Weymouth is 102 °F recorded in August 1975 and the lowest temperature on record is -15 °F recorded in January 1981. About 121 days each year see temperatures below 32 °F and an average seven days each year record temperatures below 5 °F. Every month except July has seen temperatures below 40 °F and every month except

June, July and August has recorded temperatures below freezing.

The average annual precipitation for South Weymouth is 44.3 inches (1125 mm), which is fairly evenly distributed throughout the year. Precipitation falls on about 188 days each year. The wettest month is November with 4.6 inches (117 mm) and the driest, July, averages only 2.8 inches (71 mm). An average of 20 thunderstorm days occur each year with June, July and August being the most likely months. Snow falls on about 51 days each year and averages about 43 inches (1092) mm) each year. Due to the strong maritime influence. only January and February average greater than one-foot (305 mm) of snow. One-foot (305 mm) snowfalls in a 24-hour period have occurred in each month December through April and 19 inches (483 mm) fell in one 24-hour period during February 1994. About eight days each year have a snowfall total greater than 1.5 inches (38 mm) and snow has fallen in every month, October through May. Fog is present on average 204 days each year and is evenly distributed throughout the year with a slight maximum during mid-summer.

The prevailing wind direction in South Weymouth is west-northwest during the winter and south-southwest during the warmer months. March is the windiest month—see the South Weymouth climatological table in this chapter.

north of Quincy Point. A Federal project provides for a channel 35 feet deep from the junction with Weymouth Fore River to a point 1 mile upstream, with a turning basin 35 feet deep at the inner end; thence 15 feet deep to a point just below the Quincy Electric Light & Power Company plant, 1.2 miles above the mouth. (See Notice to Mariners and latest edition of the chart for controlling depths.) About 175 yards above the head of the project on Quincy Reach, an overhead power cable has a clearance of 35 feet.

(310)

#### Wharves

(311) There are two deep-draft facilities on Weymouth Fore River and two on Town River Bay.

Twin Rivers Technologies (TRT), consists of East and North Docks. East Dock (42°14'49"N., 70°58'00"W.): 150-foot face with 435 feet berthing space with dolphins; 30 feet alongside; deck height, 15½ feet; receipt of vegetable oil and caustic soda. North Dock (42°14'54"N., 70°58'04"W.): 90-foot face with 600 feet berthing space with dolphins; 29 feet alongside; deck height, 16½ feet; pipelines extend to storage tanks in rear with 22½-million-gallon capacity; receipt of coconut oil, vegetable oil and caustic soda; owned and operated by Twin Rivers Technologies.

Wharf (42°14'12"N., 70°58'05"W.): 248-foot face, 700 feet berthing space; 38 feet alongside; deck height, 14 to 16 feet; pipelines extend to storage tanks with a 1½-million barrel capacity; receipt and shipment of petroleum products; owned and operated by Citgo Petroleum Corp.

Sprague Energy, Quincy Terminal Wharf (42°15'12"N., 70°59'10"W.): 77-foot face with 700 feet berthing space with dolphins; 35 feet alongside; deck height, 14 feet; receipt and shipment of petroleum products; bunkering vessels; owned and operated by Sprague Energy, Inc.

occasionally for mooring barges and small vessels on Town River Bay.

(316) A marina and a yacht club are on the south bank about 0.5 mile and 0.7 mile, respectively, above the entrance. Gasoline, diesel fuel, ice, supplies, pump-out facilities and a 15-ton hoist are available; hull and engine repairs can be made.

Weymouth Back River is just eastward of Weymouth Fore River and southward of Grape Island. A wharf, in ruins, of a former fertilizer works is on the north side of the river on Eastern Neck. The channel is buoyed.

(318)

#### Anchorages

(319) A **special anchorage** is in Weymouth Back River. (See **33 CFR 110.1** and **110.30 (l)**, chapter 2, for limits and regulations.)

(320)

# **Small-craft facilities**

Small-craft facilities on Weymouth Back River can provide berths with electricity, gasoline, diesel fuel, water, ice, marine supplies, a launching ramp and lifts to 37 tons; hull, engine and electronic repairs are available. Sewage pump-out is available on the south side of the

river near the end of the channel. A public launching ramp is on the north side of the river about 1.5 miles above the entrance.

(322) Hingham Harbor and Weir River in the southeasterly end of Hingham Bay are shallow. Their common entrance is close westward of Bumkin Island. The channel leads in a southeasterly direction for about 0.5 mile from the westerly end of **Bumkin Island** and then divides. The branch leading eastward is Weir River. Bumkin Island has a recreational pier on the southwest side. Ruins of several buildings, nature trails and picnic areas are on the island. Primitive camping is permitted.

(323) The narrow channel leading to Hingham Harbor trends southward to **Crow Point** and is marked by buoys. The Hingham Yacht Club has a clubhouse, pier and floats at Crow Point. It is reported that considerable shoaling has occurred along the face of the pier and the northern half cannot be approached by large vessels, except at half tide or higher; water is available at the pier.

(324) **Hingham Harbor** is a cove 1 mile in length, with an average width of about 0.6 mile. At low water it is a dry flat through which a narrow and tortuous buoyed channel winds to the town of Hingham.

(325

# **Anchorages**

(326) **Special anchorages** are eastward of Crow Point at the entrance to Hingham Harbor and at the southern end of the harbor. (See **33 CFR 110.1** and **110.32**, chapter 2, for limits and regulations.)

(327) The small-boat basin at the south end of the harbor has depths of 2 to 7 feet. A town float landing and ramp are on the south side of the basin, and there are two service wharves where gasoline, diesel fuel by truck, water and most other services are obtainable. Boat rental and a pump-out facility are available; outboard repairs are made.

Extensive flats, mostly bare at low water, are on both sides of the river. The channel is marked by buoys and is used by excursion boats running from Boston to Nantasket Beach during the summer. In 2000, the large wharf at Nantasket Beach had depths of 10.9 and 9.2 feet alongside the 175-foot southwest and northwest faces, respectively. Two small marinas, one north and one south of the wharf can provide berths with electricity, gasoline, ice, a launching ramp, pump-out, a 5-ton lift for emergencies, open and covered storage.

A safe anchorage for small craft with good holding ground, mud bottom, is reported close eastward of **Worlds End**, the south entrance point to Weir River. The anchorage is unmarked; local knowledge is advised.