
U.S. Chart No. 1

Symbols, Abbreviations and Terms used on Paper and Electronic Navigational Charts



Prepared Jointly by

Department of Commerce National Oceanic and Atmospheric Administration

Department of Defense National Geospatial-Intelligence Agency



ECDIS Symbols and Other ECDIS Information

Symbology for displaying Electronic Navigational Charts (ENCs) on Electronic Chart Display and Information Systems (ECDIS) has been added to U.S. Chart No. 1. In addition to the ECDIS symbols shown in the traditional lettered sections of U.S. Chart No. 1, there are now several special pages devoted exclusively to providing important details about ECDIS. These pages are distinguished by the ECDIS icon, as shown in the top left corner of this page. The ECDIS pages are also listed in the table of contents in italic type.



One major difference in the use of paper charts and ENCs is the ability of ECDIS to display the same feature differently depending on user settings and other conditions, such as a ship's draft. An important example is that ECDIS displays wrecks, rocks and other obstructions with their traditional "paper chart" symbols if they are at or deeper than the depth of the safety contour set for the ship. Dangers that are shoaler are portrayed with the unique ECDIS "isolated danger" symbol shown at left. (See the ECDIS Portrayal of Depths page for more information about the ECDIS safety contour.)



Another advantage that ECDIS provides over paper charts is enabling users to obtain more information about a feature through a "cursor pick." Some feature attribute values that can be obtained by cursor pick are noted throughout U.S. Chart No. 1. This is especially true if a particular value, such as height, vertical clearance or the like is included in the INT symbol description. The cursor pick icon, shown at left, is used to indicate when a reference to a cursor pick is made.

There are many other attribute values that users may obtain through a cursor pick that are not specifically noted. These include, but are not limited to, the purpose, seasonality, periodicity, status, color, height, type of structure and the visual or radar conspicuousness of features; shape, color or color pattern of buoys; characteristics of lights; category of obstructions and wrecks; radar wave length, radio frequency, communication channel and call signs; the presence of AIS transmitted signals; information regarding pilotage services and many more.

U.S. Chart No. 1 is a handy guide for ECDIS users, but it is no substitute for mandated ECDIS training.

The ECDIS user and developer communities are invited to help improve the presentation of ECDIS symbology and information in U.S. Chart No. 1. Please let us know what additional information you would like to see in the next edition.

Corrections, comments, or questions regarding U.S. Chart No. 1 may be submitted through ASSIST, the NOAA Coast Survey stakeholder engagement and feedback website

at www.nauticalcharts.noaa.gov/customerservice/assist,

or mailed to:

National Ocean Service, NOAA (N/CS2) Attention: U.S. Chart No. 1 1315 East West Highway Silver Spring, MD 20912-3282

SYMBOLS, ABBREVIATIONS AND TERMS

Contents

Document Sections and ECDIS Pages

Introduction	5
Schematic Layout	8
Day, Dusk and Night Color Palettes	9
Conspicuous and Non-Conspicuous Features	28
ECDIS Portrayal of Depths	47
Examples of Routing Measures in ECDIS	69
Simplified and Traditional "Paper Chart" Symbols	90
Index of Abbreviations	111
Index	117
Appendix 1, IALA Maritime Buoyage System	128

Symbol Sections

GENERAL

- A Chart Number, Title, Marginal Notes
- B Positions, Distances, Directions, Compass

TOPOGRAPHY

- C Natural Features
- D Cultural Features
- E Landmarks
- F Ports
- G (Not currently used)

HYDROGRAPHY

- H Tides, Currents
- I Depths
- J Nature of the Seabed
- K Rocks, Wrecks, Obstructions, Aquaculture
- L Offshore Installations
- M Tracks, Routes
- N Areas, Limits
- O (Not currently used)

NAVIGATION AIDS AND SERVICES

- P Lights
- Q Buoys, Beacons
- R Fog Signals
- S Radar, Radio, Satellite Navigation Systems
- T Services
- U Small Craft (Leisure) Facilities

INTRODUCTION

Two Symbology Types Comprising Four Symbology Sets

U.S. Chart No. 1 presents two types of symbology used for marine navigation – the symbols used on paper nautical charts (and their digital raster image equivalents) and the corresponding symbols used to portray Electronic Navigational Chart (ENC) data on Electronic Chart Display and Information Systems (ECDIS).

Within these two types, four separate symbology sets are shown. These are described below:

Paper Chart Symbols

- INT The international or "INT" symbols specified in the Regulations for International (INT) Charts and Chart Specifications of the IHO (International Hydrographic Organization). These symbols are used by many countries around the world, including the United States.
- NOAA Symbols used on charts produced by the National Oceanic and Atmospheric Administration (NOAA) when an INT symbol is not used. NOAA produces nautical charts for all U.S. waters, including the Great Lakes and U.S. Territories.
- NGA Symbols used on charts produced by the National Geospatial-Intelligence Agency (NGA) when an INT symbol is not used. NGA produces nautical charts for the U.S. military and for areas outside of U.S. waters.

ECDIS Symbols

ECDIS — Symbols used to portray ENCs on ECDIS navigation systems. Use of ECDIS is required for large commercial ships on international voyages. These symbols are specified in *IHO Specifications for Chart Content and Display Aspects of ECDIS*.

Other Non-ECDIS Digital Displays May Portray Data Differently

Navigation systems certified to meet the exacting performance standards established by the International Maritime Organization (IMO) are said to be ECDIS "type approved." The symbology used to display ENCs or other non-ENC navigational data on non-ECDIS systems, such as geographic information systems, recreational GPS and other chart display systems can differ significantly from the symbology specified for ECDIS type approved systems. U.S. Chart No. 1 only shows the symbology used on ECDIS.

U.S. Chart No. 1 and Typical Chart Layouts

A brief description of the columns on each symbol description page is provided here. A detailed schematic layout of U.S. Chart No. 1 is on page 8. Section A, on pages 10 and 11 presents schematics showing typical layouts of the major elements of NOAA and NGA charts.

- Col 1 Symbol number. The number together with the section letter which appears at the top of each page constitutes a unique identifier for each symbol, such as C1 for the "Coastline, surveyed" symbol.
- Col 2 INT symbol example.
- Col 3 Description of the feature or real world phenomenon being portrayed.
- Col 4 NOAA symbol example. This column will be blank if NOAA uses the INT symbol shown in column 2.
- Col 5 NGA symbol example. This column will be blank if NGA uses the INT symbol shown in column 2.

If columns 4 and 5 are combined, then NOAA and NGA both use the same symbol, which is different from the INT symbol.

- Col 6 Other NGA symbol examples. NGA produces facsimiles of some foreign charts. If the depiction on the chart is different than the INT or NGA symbols (shown in Cols 2 and 5, respectively) then the additional foreign symbols are shown here.
- Col 7 ECDIS symbol example in the day color palettes. (See page 9 for a description of ECDIS color palettes.)
- Col 8 The ECDIS description usually provides the generic symbol name given in the *IHO Specifications for Chart Content and Display Aspects of ECDIS*, although sometimes other clarifying terms are also provided.

The schematic layout on page 7 shows a typical symbol table page and provides more details about the table headers and the types of information presented in each of the columns.

INFORMATION ON SELECTED CHART FEATURES

Soundings

The sounding datum reference is stated in the chart title. Soundings on NOAA and NGA charts may be shown in fathoms, feet, fathoms and feet, fathoms and fractions, or meters and decimeters. In all cases the unit of depth used is shown in the chart title and outside the border of the chart in bold type (see item b in Section A). For ECDIS, the sounding datum is part of the ENC metadata, which can be retrieved through a cursor inquiry.

Heights

Heights of lights, landmarks, structures, etc. refer to the shoreline plane of reference. The unit of height is shown in the chart title. When the elevations of islets or bare rocks are offset into the adjacent water, they are shown in parentheses. For ECDIS, the unit of height is meters.

Drying Heights

For rocks and banks that cover and uncover, elevations are underlined and are referenced to the sounding datum as stated in the chart title (or in the ENC metadata). When the heights of rocks that cover and uncover are offset into the adjacent water, they are shown in parentheses.

Shoreline

Shoreline shown on charts represents the line of contact between the land and a selected water elevation. In areas affected by tidal fluctuation, this line of contact is usually the mean high water line. In confined coastal waters of diminished tidal influence, a mean water level may be used. The shoreline of interior waters (rivers, lakes) is usually a line representing a specified elevation above a selected datum. Shoreline is symbolized by a heavy line (symbol C 1). Apparent shoreline is used on charts to show the outer edge of marine vegetation where the limit would be expected to appear as the shoreline to the mariner or where it prevents the shoreline from being clearly defined. Apparent shoreline is symbolized by a light line (symbols C 32, C 33, C p, C q and C r).

Landmarks

A structure or a conspicuous feature on a structure may be shown by a landmark symbol with a descriptive label (see Section E). Prominent buildings that could assist the mariner may be shown by actual shape as viewed from above (see Sections D and E).

On NGA charts, landmark legends shown in capital letters indicate that a landmark is conspicuous; the landmark may also be labeled "CONSPICUOUS" or "CONSPIC." On NOAA charts, all landmarks are considered to be conspicuous, and landmark legends shown in all capital letters indicate a landmark has been positioned accurately; legends using both upper and lower case letters indicate an approximate position.

ECDIS portrays conspicuous features with black symbols and non-conspicuous features with brown symbols. Only the conspicuous version is shown in the lettered sections of U.S. Chart No. 1. See the ECDIS "Conspicuous and Non-Conspicuous Features" page in front of Section E for more information.

IALA Buoyage System

The International Association of Marine Aids to Navigation and Lighthouse Authorities (IALA) Maritime Buoyage System is followed by most of the world's maritime nations; however, systems used in some foreign waters may be different. IALA buoyage is divided into two regions: Region A and Region B. All navigable waters of the United States follow IALA Region B rules, except U.S. possessions west of the International Date Line and south of 10° north latitude, which follow IALA Region A rules.

The major difference between the two buoyage regions is the color of the lateral marks. Region A uses red to port and Region B uses red to starboard (red-right-returning). The shapes of the lateral marks are the same in both regions, can to port and cone (nun) to starboard, when entering from seaward. Cardinal and other marks, such as those for isolated dangers, safe water and special marks are also the same in both regions. Section Q and Appendix 1 illustrate the IALA buoyage system for both Regions A and B.

U.S. Lateral Marks

Most of U.S. waters are in IALA Region B. In the U.S. system, on entering a channel from seaward, buoys and beacon dayboards on the starboard side are red with even numbers and have red lights, if lit. Buoys and beacon dayboards on the port side are green with odd numbers and have green lights, if lit. Preferred channel buoys have red and green horizontal bands with the top band color indicating the preferred side of passage.

Light Range (Visibility)

A light's range or visibility is given in nautical miles, except on the Great Lakes and adjacent waterways, where light ranges are given in statute miles. For lights having more than one color, NOAA charts give only the shortest range of all the colors. On NGA charts, multiple ranges may be shown using the following convention. For lights with two colors, the first number indicates the range of the first color and the second number indicates the range of the second color. For example, FI WG 12/8M means the range of the white light is 12 nautical miles and the range of green light is 8 nautical miles. For lights with three colors, only the longest and shortest ranges are given and the middle range is indicated by a dash. For example, FI WRG 12-8M means that the range of the white light is 12 nautical miles, the range of green light is 8 nautical miles and the range of the white light is 12 nautical miles. The range of green light is 8 nautical miles and the range of the white light is 12 nautical miles. The range of green light is 8 nautical miles and the range of the white light is 12 nautical miles. The range of green light is 8 nautical miles and the range of the white light is 12 nautical miles. The range of green light is 8 nautical miles and the range of the red light is between 8 to 12 nautical miles. The dash can appear in any of the three positions.

Aids to Navigation Positioning

The fixed and floating aids to navigation depicted on charts have varying degrees of reliability. Floating aids are moored to sinkers by varying lengths of chain and may shift due to sea conditions and other causes. Buoys may also be carried away, capsized or sunk. Lighted buoys may be extinguished and sound signals may not function, because of ice or other causes. Therefore, prudent mariners will not rely solely on any single aid to navigation, particularly on floating aids, but will also use bearings from fixed objects and aids to navigation on shore.

Colors

Color conveys the nature and importance of features found on nautical charts. Chart elements significant to marine navigation, such as lights, compass roses and regulated areas, are emphasized with magenta. Lateral marks on NOAA charts are shown with a red or green fill. Shades of blue depict potential hazards to navigation, typically shallow water and submerged obstructions. Areas of deeper water believed to be clear of obstructions are shown as white. Land, and other features that are always dry, are depicted with buff on NOAA charts and gray on NGA charts. Foreshore and other intertidal features are portrayed with a green tint. Other colors may be used to provide additional information, such as protected areas, which are outlined in blue or green.

Traffic Separation Schemes

Traffic separation schemes show recommended lanes to increase safety of navigation, particularly in areas of high density shipping. These schemes are described in the International Maritime Organization (IMO) publication, *Ships Routeing*. Traffic separation schemes are generally shown on nautical charts at scales of 1:600,000 and larger. When possible, traffic separation schemes are plotted to scale and shown as depicted in Section M.

Conversion Scales

Depth conversion scales are provided on all charts to enable the user to work in meters, fathoms or feet.

Correction Date

The date of each new chart edition is shown below the lower left border of the chart. The date of the latest NGA issued U.S. Notice to Mariners applied to the chart is shown after the edition date. NOAA charts also show the date of the latest U.S. Coast Guard Local Notice to Mariners applied to the chart.

ADDITIONAL RESOURCES

Information on the use of nautical charts, aids to navigation, sounding datums and the practice of navigation in general is in *The American Practical Navigator* (Bowditch), available through the "Publications" link on the NGA Maritime Safety Information portal at https://msi.nga.mil/NGAPortal/MSI.portal.

Tide and current data over U.S. waters is available from the NOAA Center for Operational Oceanographic Products and Services at <u>https://tidesandcurrents.noaa.gov</u>.

Detailed information about specific lights, buoys, and beacons and general information about the U.S. Aids to Navigation System and the Uniform State Waterway Marking Systems is in the U.S. Coast Guard *Light List,* at https://www.navcen.uscg.gov/?pageName=lightLists.

Information about aids to navigation in foreign waters is in the NGA *List of Lights,* available through the "Publications" link on the NGA Maritime Safety Information portal at <u>https://msi.nga.mil/NGAPortal/MSI.portal</u>.

Other important information that cannot be shown conveniently on nautical charts can be found in the NOAA *U.S. Coast Pilot*[®], at

https://nauticalcharts.noaa.gov/publications/coast-pilot/index.html

and NGA Sailing Directions, available through the "Publications" link on the NGA Maritime Safety Information portal at https://msi.nga.mil/NGAPortal/MSI.portal.

U.S. Nautical Chart Catalogs and Indexes

NGA catalogs are available through the "Product Catalog" link on the NGA Maritime Safety Information portal at <u>https://msi.nga.mil/NGAPortal/MSI.portal</u>.

NOAA catalogs are available at the NOAA Chart Locator at

www.charts.noaa.gov/InteractiveCatalog/nrnc.shtml and the NOAA Nautical Chart Catalog and Chart Viewer at www.charts.noaa.gov/ChartCatalog/MapSelect.html.

A list of the dates of the latest editions of NOAA charts is at https://nauticalcharts.noaa.gov/charts/list-of-latest-editions.html.

CORRECTIONS AND COMMENTS

Corrections to U.S. Chart No. 1 will appear in the weekly U.S. Notice to Mariners, available through the "Notice to Mariners" link on the NGA Maritime Safety Information portal at <u>https://msi.nga.mil/NGAPortal/MSI.portal</u>.

Corrections, comments, or questions regarding U.S. Chart No. 1 may be submitted through ASSIST, the NOAA Coast Survey stakeholder engagement and feedback website at www.nauticalcharts.noaa.gov/customer-service/assist.

or to:

National Ocean Service, NOAA (N/CS2) Attention: U.S. Chart No. 1 1315 East West Highway Silver Spring, MD 20910-3282

Schematic Layout of U.S. Chart No. 1: Rocks, Wrecks, Obstructions^(B) \bigcirc Rocks Supplementary national symbol: a (E Plane of Reference for Heights \rightarrow H Plane of Reference for Depths \rightarrow H No. INT Description NOAA NGA Other NGA ECDIS rock which covers and × uncovers or is awash at low water $2_7 * (1_6) \oplus (1_6)$ underwater hazard which Rock which covers and uncov-11 * (<u>2</u>) \$**7**(2) • (*)covers and uncovers with ers, height above chart datum (0₆) Uncov 1m drying height isolated danger of depth less than the safety contour (3) (4a) (4b) (5)(6)2 7 (A)Section designation (B) Section (C)Sub-section Reference to "Supplementary national symbols" at the end of each section (E) Cross-reference to terms in other sections (1)Column 1: Numbering system following the "Chart Specification of the IHO". A letter in this column indicates a supplementary national symbol or abbreviation for which there is no international equivalent. (2) Column 2: Representation that follows the "Chart Specifications of the IHO" (INT 1 symbol) (3) Column 3: Description of symbol, term, or abbreviation (4a)* Column 4a: Representation used on charts produced by the National Oceanic and Atmospheric Administration (NOAA) (4b) Column 4b: Representation used on charts produced by the National Geospatial-Intelligence Agency (NGA) (5) Column 5: Representation of symbols that may appear on NGA reproductions of foreign charts **6**** Column 6: Representation used to portray ENC data on ECDIS (7)****** Column 7: Description of ECDIS symbols * When columns 4a and 4b are combined then NOAA and NGA both use the same symbol. When either column 4a or 4b is blank then the respective agency uses the INT 1 symbol shown in column 2. When columns 6 and 7 have several rows for the same symbol number, then ECDIS portrays this feature differently depending on the ship's draft and other conditions as defined in ECDIS by the mariner (as is the ** case for K 11). When columns 6 and 7 combine rows to span across several symbol numbers then ECDIS portrays all of the grouped symbol numbers the same way (see C 5-C 7). + Signifies that this representation is obsolete, but it may appear on older charts. Å Signifies that a feature attribute value, such as a height, distance or name, may be obtained through an ECDIS cursor pick report. There are many attribute values that may be obtained in this manner, but the cursor pick icon is only used to note values that are specifically referred to in the description of symbols column and that ECDIS does not display next to the symbol. Height of trees in C 14 is an example.

Day, Dusk and Night Color Palettes




ECDIS allows the mariner to change the color palette that is used to display an ENC. Three different color tables have been designed to provide the maximum clarity and contrast between features on the display under three different lighting conditions on the bridge, namely Day, Dusk and Night.

Each symbol is rendered in a different color appropriate for the lighting condition that the color table is meant for. This design provides maximum contrast for the display on a sunny day, as well as preserving night vision on a dimly lit bridge in the evening. This allows the mariner to look back and forth between the chart on the ECDIS display and out to sea through the bridge window without the mariner's eyes needing to readjust to a difference in light intensity.

- The Day Color Table, meant to be used in bright sunlight, uses a white background for deep water and looks the most like a traditional paper chart.
- The Dusk Color Table uses a black background for deep water and colors are subdued, but slightly brighter than those used in the Night Color Table.
- The Night Color Table, meant to be used in the darkest conditions, uses a black background for deep water and muted color shades for other features.


The images on the right show each of the three color palettes. The symbols shown in the remainder of this document use the day color palette.



DUSK




A Chart Number, Title, Marginal Notes



	Magnetic Features \rightarrow B Tidal Data \rightarrow H							
1	Chart number in national chart series							
2	Chart number in international (INT) series (if any)							
3	Reference ellipsoid of the chart							
4	Publication note (imprint)							
5	Copyright note							
6	Date of current edition							
7	Notice to Mariners corrections							
8	Dimensions of inner borders							
9	Corner coordinates							
10	Chart title							
(11)	Explanatory notes on chart construction, etc. To be read before using chart.							
12	Seal(s)							
13	Scale of chart. Some charts have scale at a stated latitude.							
(14)	Linear scale on large scale charts							

Chart Number, Title, Marginal Notes A

(15)	Linear border scale on large scale charts. On smaller scales use latitude borders for sea miles.
(16)	Cautionary notes (if any). Information on particular fea- tures, to be read before using chart.
17	Source Diagram (if any). Navigators should be cautious where surveys are inadequate.
(18)	Reference to a larger scale chart
(19)	Reference to an adjoining chart of similar scale
a	Conversion scales
b	Reference to the units used for depth measurement
C	Compass rose
d	Bar code and stock number
e	Glossary: Translation of words on chart that are not in English
9	Tidal and Tidal Stream information within the chart coverage



B Positions, Distances, Directions, Compass


No.	INT	Description	NOAA	NGA	Other NGA		ECDIS
Geogra	phical Positions						
1	Lat	Latitude					
2	Long	Longitude					
4		Degree(s)	d	eg			
5		Minute(s) of arc					
6		Second(s) of arc					
						PA	Position approximate
7	PA	Position approximate (not accurately determined or does not remain fixed)	PA	(PA)		Š	Point feature or area of low accuracy
						21	Sounding of low accuracy
8	PD	Position doubtful (reported in various positions)	PD	(PD)		S	Point feature or area of low accuracy
		,				21	Sounding of low accuracy
9	Ν	North					
10	E	East					
11	S	South					
12	W	West					
13	NE	Northeast					
14	SE	Southeast					
15	NW	Northwest					
16	SW	Southwest					

Positions, Distances, Directions, Compass $\,B\,$

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Control	Points				^ 	- -	
20	۵	Triangulation Point					
21	† [⊕]	Observation spot	0b	s Spot		o	Position of an elevation or control point
22	⊙ o	Fixed point	G)			
25.1	o km 32	Distance along waterway, no visible marker	St M 32			km 7	Canal and distance point with no mark
25.2	o km 46	Distance along waterway with visible marker	□ Y Bn (46)			° km 7	Canal and distance point
	Note: ECDIS uses a magenta "km" syn	nbol to represent distance marks. Ho	wever, the distances show	wn along waterways on I	NOAA-produced ENCs are displaye	ed in statute miles.	
Symbol	ized Positions (Examples)						
30	💶 # 强 wk	Symbols in plan—position is center of primary symbol				ECDIS follows the paper of	chart convention for the ot for simplified symbols for
31		Symbols in plan—position is at bottom of symbol				buoys and beacons (see	
32	o Mast ⊙ MAST ★	Point symbols	⊙ N	MAST		Ο	Position of a point feature
33	† • Mast PA	Point symbols—approximate positions	0 1	Mast		ECDIS indicates approxin wrecks, obstructions, islet	
Units	L					Supplementary national s	ymbols <i>a–m</i>
40	km	Kilometer(s)					
41	m	Meter(s)					
42	dm	Decimeter(s)					
43	cm	Centimeter(s)					
44	mm	Millimeter(s)					
45	М	International nautical mile(s) (1852m), sea mile(s)	Mi NN	/i NM			
47	ft	Foot / Feet					
48	fm, fms	Fathom(s)					

B Positions, Distances, Directions, Compass

No.	INT		Description	NOAA	NGA	Other NGA	ECDIS
49		h	Hour(s)	hr			
50	m	min	Minute(s) of time				
51	S	sec	Second(s) of time				
52	k	kn	Knot(s)				
53		t	Ton(s), Tonnage (weight)				
54	C	cd	Candela(s)				
Magnet	ic Compass						Supplementary national symbols n
68.1		c Variation	Note of magnetic variation,				Cursor pick site for magnetic variation at a point
00.1	4°30′ W 2	2011 (8'E)	in position				Cursor pick site for magnetic variation over an area
68.2		tion at 55°N 8°W 2011 (8′E)	Note of magnetic variation, out of position				



B Positions, Distances, Directions, Compass

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
82.1	{±15°}	Local magnetic anomaly Within the enclosed area the magnetic variation may deviate from the normal by the value shown				AAAAA	Cursor pick site for magnetic anomaly along a line or over an area
82.2	Local Magnetic Anomaly (see Note)	Local magnetic anomaly Where the area affected cannot be easily defined, a legend only is shown at the position	LOCAL MAGNETIC DISTURBANCE (see note)	LOCAL MAGNETIC ANOMALY (see note)	LOCAL MAGNETIC DISTURBANCE (see note)	4	Cursor pick site for magnetic anomaly at a point
Supple	ementary National Symbols				Ι	1	
а		Square meter(s)	n	1 ²			
b		Cubic meter(s)	n	1 ³			
с		Inch(es)	iı	ו			
d		Yard(s)	у	d			
е		Statute mile(s)	St M	St Mi			
f		Microsecond(s)	µsec	μs			
g		Hertz	Н	Z			
h		Kilohertz	kŀ	łz			
i		Megahertz	М	Hz			
j		Cycles/second	cps	c/s			
k		Kilocycle(s)	k	с			
I		Megacycle(s)	N	lc			
m		Ton(s) (U.S. short ton) (2,000lbs)	٦	Г			
о		Benchmark	В	М			
р		Variation	var	VAR		Varn	Magnetic variation

Positions, Distances, Directions, Compass $\,B\,$

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS
q		Magnetic	mag			
r		Bearing	brg			
S		True	Т			


C Natural Features

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS		
Coas	tline					Supplementary national	l symbols: a–e		
Forest	Foreshore \rightarrow I, J								
1		Coastline, surveyed					Coastline		
2		Coastline, unsurveyed				00000000	Coastline or shoreline construction of low accuracy in position		
			high	low			Presence of cliffs coincident with coastline is obtained by cursor pick		
3		Cliffs, Steep coast	1	An an an a warm			Sloping ground crest line distant from coastline, radar or visually conspicuous		
			t transformer	Arst March March M.			Cliff as an area		
4	Hints Ht	Hillocks	t	0		洪	Conspicuous hill or mountain top		
5		Flat coast							
6		Sandy shore	+				Nature of coastline is obtained by cursor pick		
7	Stones Stones	Stony shore, Shingly shore	نگس ا	persiently		μ).			
8	Dunes	Sandhills, Dunes	+	e-le		洪	Conspicuous hill or mountain top		

Natural Features C

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Relie	f					Supplementary nationa	il symbols: e–g
Plane	of reference for heights \rightarrow H						
10	250 (250- (150- 50- (10)-	Contour lines with values and spot height				0 109 m	Elevation contour with spot height, contour value is obtained by cursor pick
11	-389 -189 115 mm -123 mm m m m m m m m m m m m m m m m m m	Spot heights				O 119 m	Position of an elevation or control point
12	250 (250 (150) (150) (150)	Approximate contour lines with values and approximate height					Elevation contour with spot height, contour
13	,359 t	Form lines with spot height	t t			0 109 m	value is obtained by cursor pick
14	λλα λ ^α λ αλα 160 λ αλλα λα λαλλα λα λα λαλα	Approximate height of top of trees (above height datum)		135 TT		+ Approximate obtained by	e height of trees is cursor pick
Wate	r Features, Lava						
20	Name	River, Stream				~	River
21		Intermittent river, intermittent lake					

C Natural Features



Natural Features C

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
31	Prominent trees (isolated or in groups)						
31.1	Q Q Q	Unspecified tree				ŧ	Tree
31.2	t © ^Q Q ^Q	Evergreen (except conifer)				Г	nee
31.3	£ ££	Conifer, Casuarina					
31.4	J J J J	Palm					Vegetation, line of trees
31.5	+ ★ * [★] *	Nipa Palm				± ₹	
31.6	+ 萊 萊萊萊	Casuarina				₽ + + + <i>+)</i>	Wooded area
31.7	τ Ψ ^Ψ Ψ Ψ	Filao				ŧ ŧ ₺/	wooded area
31.8	t I I I I I I I I I I I I I I I I I I I	Eucalypt				₽ ₹ ₹	
32		Mangrove, Nipa palm		ed in small areas)			Mangrove with coastline or shoreline construction of low accuracy in position
33	M a r/s h	Marsh, Swamp, Reed beds	(used in small areas)	Swamp		,。。 [*] 乔 不不 不 不 不	Marsh with coastline or shoreline construction of low accuracy in position
Supp	lementary National Symbols						
а		Chart sounding datum line (surveyed)	Uncov	/ers			
b		Approximate sounding datum line (inadequately surveyed)					
с		Foreshore; Strand (in general); Stones; Shingle; Gravel; Mud; Sand	Mud				
d		Breakers along a shore	Grades (ff	extensive)			

C Natural Features

No.	INT Description	NOAA	NGA	Other NGA	ECDIS
е	Rubble	t			
f	Hachures	+	500 ×		
g	Shading	+			
i	Deciduous woodland	t Wooded	1823		
j	Coniferous woodland	Wooded	A414		
k	Tree plantation	**************************************	0 0		
I	Cultivated fields	Cultivated			
m	Grassfields	Grass			
n	Paddy (rice) fields	Rice †			
ο	Bushes	t Bushes	A. 2. 8.		
р	Apparent shoreline	Marsh	1		
q	Vegetation or topographic (Feature Area Limit-in general)				
r	Cypress		Cypress		
s	Grass	Grass			
t	Eelgrass	Eelgrass			

Cultural Features D

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Settle	ments, Buildings						
Height	of objects \rightarrow E Landma	arks \rightarrow E					
1		Urban area					Built-up area
2		Settlement with scattered buildings					
3	o Name	Settlement (on medium and small scale charts)	÷ ۲	‡ 0		Name	Built-up area as a point
4	H Name ■ Name HOTEL	Village	Vil			Name	
5		Buildings	• 🖾 🗆			— •	Conspicuous single building
6	Hotel	Important building in built-up area					Conspicuous single building in built-up area
7		Street name, Road name				Street name	e is obtained by cursor pick
8	[Ru []	Ruin, Ruined landmark	Ruins	o Ru		Status of ru	ns is obtained by cursor
Road	s, Railways, Airfields					Supplementary Nationa	Il Symbols: a–c
10		Motorway, highway					Road, track or path as a line
11		Road (hard surfaced)					
12		Track, Path (loose or unsurfaced)					Road as an area

D Cultural Features

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
13	••••••	Railway, with station					Railway, with station
14		Cutting					Cutting
15	<u> </u>	Embankment					Embankment
							Embankment, visually or radar conspicuous
							Tunnel
16	 _=== (Tunnel					Tunnel with depth below the seabed encoded
							Airport as a point
17	Air- field	Airport, Airfield	Airport	port		\mathbf{X}	Runway as a line
	field						Airport area, with runway area and visually conspicuous runway area
18	$(\boldsymbol{\theta})$	Heliport, Helipad					
Othe	Cultural Features		1		1	Supplementary Nation	al Symbols: d–i
20.1		Fixed bridge					
20.2		Footbridge, fixed bridge on smaller scale charts					

Cultural Features D

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
21		Horizontal clearance	FIXED BRIDGE	HOR CL 8 M ⊢8 ⊣		Horizontal clearance	e is obtained by cursor pick
22		Vertical clearance (see introduction)	HOR CL 25 FT VERT CL 20 FT	VERT CL 6 M T L		cir 20.0	Bridge
23.1		Opening bridge (in general) with vertical clearance				cir ci 8.2	
23.2		Swing bridge with vertical clearance				cir op 20.0 cir ci 8.2	Opening bridge
23.3	Lifting Bridge 4:2 (open 12)	Lifting bridge with vertical clearance (closed and open))			clr op 20.0	
23.4	Bascule Bridge	Bascule bridge with vertical clearance					
23.5	Pontoon Bridge	Pontoon bridge				clr 20.0 clr 20.0	Bridge
23.6	Draw Bridge	Draw bridge with vertical clearance				clr cl 8.2 clr op 20.0 clr cl 8.2 clr op 20.0	Opening bridge
24	Transporter Bridge	Transporter bridge with vertical clearance below fixed structure				clr 20.0	Bridge

D Cultural Features


No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS		
25	• • • • • • • • • • • • • • • • • • •	Overhead transporter, Aerial cableway with vertical clearance				cir 20.0	Aerial cableway		
						cir 20.0	Aerial cableway, radar conspicuous		
26.1	$\begin{array}{c} Pyl \\ \mathfrak{o} - \bullet - s - \bullet - s - \bullet - s - \bullet - s \\ \underline{32} \\ \end{array}$	Overhead power cable with pylons and physical vertical clearance	OVERHEAD POWER CABLE AUTHORIZED CL 140 FT			Sf clr 20.0	Transmission line		
26.2		Overhead power cable with pylons and safe vertical clearance	TOWER			Sf clr 20.0	Transmission line, radar conspicuous		
	Note D26.2: The safe vertical clearance defined by the responsible authority, to avoid risk of electrical discharge, has been obtained by applying a reduction to the physical vertical clearance of the cable. The reduction is variable and depends upon the transmission voltage. See H20.								
27		Overhead cable, Telephone line,	Tel		cir 20.0	Overhead cable			
	20	with vertical clearance	• •	• •		cir 20.0	Overhead cable, radar conspicuous		
28	Overhead	Overhead pipe with vertical		OVHD PIPE VERT CL 6FT		clr 20.0	Overhead pipeline		
	Pipe	clearance				cir 20.0	Overhead pipeline, radar conspicuous		
29		Pipeline on land				-	Oil, gas pipeline, submerged or on land		
Supp	lementary National Symbols								
а		Highway markers	-20-5	<u>)</u>					
с		Abandoned railroad	+ + +	+ + +					


Cultural Features D

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
d		Bridge under construction	+-+				
f		Viaduct	1	Viaduct			
g		Fence	00	00			
h		Power transmission line	•• \$\$\$	•• \$\$			
i		Approximate vertical clearance		abt 21			



There are 25 features for which ECDIS displays either a black symbol, if the feature is visually conspicuous, or a brown symbol if is not. Only conspicuous landmarks are depicted on NOAA paper charts and ENCs. Therefore, only the conspicuous symbol versions are shown in the symbol tables of U.S. Chart No. 1. Both versions of the symbols for these features are shown on this page.





The seven symbols shown below represent features that only have a brown symbol. There is no corresponding black, conspicuous symbol. The brown symbol is displayed regardless of the conspicuousness of the feature.



Landmarks E

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Plane	of Reference for Height \rightarrow H	Lighthouses $\rightarrow P$	$Beacons \to Q$				
Genei	ral						
						Ο	Non-conspicuous point feature
1		Examples of landmarks	⊙ TANK O Tr				Non-conspicuous building
						Ī	Non-conspicuous water tower
		Examples of conspicuous landmarks (On NOAA charts,		0 00/05		Ο	Conspicuous point feature
2	◆ FACTORY ⊙ HOTEL	a large circle with dot and capitals indicates that position is accurate; a small circle with	O EMPIRE STATE BUILDING				Conspicuous building
	ជ water tr	lowercase indicates that position is approximate.)	○ RADAR MAST			Ĩ	Conspicuous water tower
3.1		Pictorial sketches (in true position)				A i 🗞	The information symbol is displayed if a supplemental image is available, which may be accessed by cursor pick
3.2		Pictorial sketches (out of position)					
4	(30)	Height of top of a structure above height datum				Height is ob	
5	↓ (30)	Height of structure above ground level					tained by cursor pick
Landr	narks						
10.1	ch the ch	Church				¥	Church as a point
10.1		Church			~ ♀ ∎		Church as an area
10.2	Tr III	Church tower					
10.3	Sp ↓ Sp	Church spire		O Spire	t Å t	¥	Church tower, spire, or dome
10.4	Cup H Cup	Church cupola (dome)		O Cup	Ŷ		
13	×	Temple, Pagoda, Shrine, Marabout, Joss house			¢	X	Religious building, non-Christian

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
17	8	Mosque, Minaret			Ł	¥.	Mosque or minaret
19		Cemetery	Cem				Landmark area, type is obtained by cursor pick
20	Д тr	Tower	TOWERTr	Tr _O		Ţ	Tower
21	Ţ	Water tower, Water tank on a tower	 STANDPIPE S'pipe 	WTR TR O Wtr Tr		Ĩ	Water tower
22	🛱 📢 Chy	Chimney	 CHIMNEY O Chy 	о сну 🛱	ů Ţ	I	Chimney
23	Å.	Flare stack (on land)	🕝 FLARE	O Flare		1	Flare stack
24	â Mon	Monument (including column, pillar, obelisk, statue, calvary cross)		O Mon	a L	<u>B</u>	Monument
25.1	×	Windmill		O Windmill	¥ *	× 🗞	Windmill, status of ruins is obtained by cursor
25.2	X Ru	Windmill (without sails)				◆ k	pick
26.1	t t t	Wind turbine, Windmotor		O Windmotor		ł	Wind motor
26.2		Onshore wind farm	• WIND FARM	O Wind Farm			Wind generator farm
27	₽ FS	Flagstaff, Flagpole	→ FS→ FP	O FS O FP		1	Flagstaff, flagpole
28	Ω,	Radio mast, Television mast	○ R MAST○ TV MAST	O R Mast O TV Mast		L	Mast
29	(^b)	Radio tower, Television tower	⊙ R TR⊙ TV TR	O R Tr O TV Tr		A	Radio, television tower
30.1	⊙ Radar Mast 🖞 Radar	Radar mast	○ RADAR MAST	O Radar Mast		L	Mast
30.2	● Radar Tr 🕺 🗍 Radar	Radar tower	🕥 RADAR TR	O Radar Tr		Ţ	Radar tower

No.	IN	т	Description	NOAA	NGA	Other NGA	EC	DIS
30.3	⊚ Rad	dar Sc	Radar scanner				μ	Radar scanner
30.4	Radome		Radome	DOME (RADAR) O Dome (Radar)	RADOMERadome		Ģ	Dome
31	S	Ž	Dish aerial	 ANT (RADAR) Ant (Radar) 			\$	Dish aerial
							0	Tank
32	⊕ ⊕ ●	Tanks	Tanks	🕤 tank 🌐	⊘ ОТК			Tank farm
33	🔿 Silo	⊙ Silo	Silo	<u> </u>	O Silo O Elevator	Å Å	•	Silo
34.1	L.		Fortified structure (on large scale charts)		Д		ß	Fortified structure
34.2	:	1	Castle, Fort, Blockhouse (on small scale charts)					
34.3	E	3	Battery, Small fort (on small scale charts)					Fortified structure
35.1	TIT		Quarry (on large scale charts)					Quarry area
35.2	\$	\$	Quarry (on small scale charts)				<u>%</u>	Quarry
36	\$	\$	Mine					
37.1	Ļ	P	Recreational vehicle site					
37.2		X	Camping site (including recreational vehicles)					
Supp	lementary Natio	nal Symbols						
а			Muslim shrine	+				
b			Tomb	† 🚅				
с			Watermill	بر +	X	\$		


E Landmarks

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS
d		Factory	₽	ြာ Facty		
е		Well	O Well			
f		School	Sch	Sch		
g		Hospital		Hosp		
h		University	Univ	Univ		
i		Gable	⊖ gab	O Gab		
k		Telegraph Telegraph office	Tel	el Off		
I		Magazine	Ma	agz		
m		Government house	Gov	rt Ho		
n		Institute	In	st		
о		Courthouse	Ct	Но		
р		Pavilion	Pa	av		
q		Telephone	-	Г		
r		Limited	Li	td		
s		Apartment	Apt			
t		Capitol	Сар			
u		Company	Со			
v		Corporation	Co	orp		

Ports F

No.	INT	Description	NOAA NGA	Other NGA	EC	DIS
Prote	ctive Structures				Supplementary nationa	l symbols: a–c
1		Dike, Levee, Berm				Dike as a line Dike as a line, conspicuous Dike as an area
2.1		Seawall (on large scale charts)			I	Seawall
2.2		Seawall (on small scale charts)				
						Causeway as a line
3	Causeway	Causeway	Cswy			Causeway, covers and uncovers as a line Causeway as an area
					7	Causeway, covers and uncovers as an area
4.1		Breakwater (in general)				Breakwater as a line
4.2	Frankling Street	Breakwater (loose boulders, tetrapods, etc.)				Breakwater as an area
4.3		Breakwater (slope of concrete or masonry)				
5	Training Wall (covers)	Training wall (partly submerged at high water)				Training wall

F Ports



Ports F

No.	INT	Description	NOAA NGA	Other NGA	ECDIS
18		Steps, Landing stairs		Steps	Landing steps
19.1	(4) (B) (A 54)	Designation of berth	3 A 3		Nr 3 Berth number
19.2	0	Visitors' berth			Yacht harbor, marina
19.3	(Dangerous cargo berth			
20	□ Dn [□] _□ Dns	Dolphin	o Dol ↑ ● Dol (Great Lakes)	Μ • •	Mooring dolphin
21	Ф	Deviation dolphin			Deviation mooring dolphin
22	•	Minor post or pile	o Pile † ● Pile (Great Lakes)		Pile or bollard
23	Ramp Patent slip	Slipway, Patent slip, Ramp			Slipway, ramp
24		Gridiron, Scrubbing grid, Careening grid			Gridiron
25		Dry dock, Graving dock			Dry dock
26	Floating Dock	Floating dock			Floating dock as a line Floating dock as an area
27	7.6m	Non-tidal basin, Wet dock			Wet dock and gate

F Ports

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
28		Tidal basin, Tidal harbor					Dock
20							Dock, under construc- tion or ruined
	·•					(X)	Floating hazard
	Log Pond	Floating barrier, e.g. security,					Boom
29.1		containment booms (ice, logs, oil), shark nets: - with supports - without supports					Floating oil barrier, oil retention (high pressure pipe)
	Barrier						Boom, floating obstruction
29.2	Bubble Curtain → → → → → → → → → →	Bubble curtain (bubbler, pneumatic pipe)					Floating oil barrier, oil retention (high pressure pipe)
30	Dock under construction (2011)	Works on land, with year date					
31	Area under reclamation (2011)	Works at sea, Area under reclamation, with year date	Under construction (2011)	Under constr			Ruin or works under construction Year and condition
32	Under construction (2011) Works in progress (2011)	Works under construction, with year date	Under (2011	constr)		*	of under construction or ruin is obtained by cursor pick
33.1	Ru	Ruin		Ruins			
33.2	==1 Pier (ru)	Ruined pier, partly submerged at high water	H==	Pier Pier			Pier, ruined and partly submerged
34	Hulk Dulk	Hulk	Hk	<i>─ H</i> k			Hulk

Ports F

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Cana	ls, Barrages					Supplementary national s	ymbol: d
Cultura	al Features \rightarrow B Cleara	nces \rightarrow D Signal S	tations \rightarrow T				
40		Canal	Canal Ditch				Canal
41.1		Lock (on large scale charts)		A Contraction of the second se			Lock gate as a line Lock gate as an area
41.2		Lock (on small scale charts)	Canal	Lock Sluice	<u>}}</u>		Navigable lock gate
42		Gate, Caisson					Non-navigable lock gate Caisson as a line Caisson as an area
43	Flood Barrage	Flood barrage					Non-navigable lock gate
44	Dam	Dam, Weir (direction of flow shown is left to right)					Flood barrage as an area Dam as a line Dam as an area

No.	INT	Description	NOAA NGA Other NGA ECDIS		DIS	
Trans	hipment Facilities		· · · · · ·		Supplementary nationa	al symbols: e–f
Roads	\rightarrow D Railways \rightarrow D	Tanks \rightarrow E				
50	RoRo	Roll-on, Roll-off Ferry Terminal (RoRo Terminal)			RoRo	RoRo terminal
51	2 3	Transit shed, Warehouse (with designation)				Conspicuous single building, designation is obtained by cursor pick
					#	Timber yard as a point
52	#	Timber yard	с- †			Timber yard as an area
		Crane with lifting capacity,	0-	**************************************	No. 1	Lifting capacity is ob- tained by cursor pick
53.1	(31)000	Traveling crane (on railway)	1	¢ + + +	T	Crane as a point
						Crane as an area
			Came Came			
53.2	d a (50 t)	Container crane (with lifting capacity)	t and the second			Crane, visually conspicuous as an area
Public	c Buildings	I			Supplementary national s	symbol: g
60	٩	Harbormaster's office	Hbr Mr			Conspicuous single building
61	⊖	Custom office	Cus Ho			Conspicuous single building
					\ominus	Customs
62.1	\oplus	Health office, Quarantine building	+ Health Office			
62.2	Hospital	Hospital	Hosp			Conspicuous single building
63	† 🖾	Post office	■ PO			


No.	INT	Description	NOAA	NGA	Other NGA	ECDIS
Supp	lementary National Symbols					
а		Jetty (partly below MHW)				
b		Submerged jetty	Subm Jetty			
с		Jetty (on small scale charts)				
d		Pump-out facilities	P			
е		Quarantine office	† 🕀 Qua	ar		
g		Conveyor		Conveyor		

H Tides, Currents

Terms Relating to Tide Levels

NT Terms			
No.	Term	Description	
1	CD	Chart Datum, Datum for sounding reduction	
2	LAT	Lowest Astronomical Tide	
3	HAT	Highest Astronomical Tide	
4	MLW	Mean Low Water	
5	MHW	Mean High Water	
6	MSL	Mean Sea Level	
8	MLWS	Mean Low Water Springs	
9	MHWS	Mean High Water Springs	
10	MLWN	Mean Low Water Neaps	
11	MHWN	Mean High Water Neaps	
12	MLLW	Mean Lower Low Water	
13	MHHW	Mean Higher High Water	
14	MHLW	Mean Higher Low Water	
15	MLHW	Mean Lower High Water	
16	Sp	Spring tide	
17	Np	Neap tide	

Supplementary National Terms (see I–t for other terms and symbols)							
No.	Term	Description					
а	HW	High Water					
b	HHW	Higher High Water					
С	LW	Low Water					
d	LWD	Low Water Datum					
е	LLW	Lower Low Water					
f	MTL	Mean Tide Level					
g	ISLW	Indian Spring Low Water					
h	HWF&C	High Water Full and Change (Vulgar establishment of the port)					
i	LWF&C	Low Water Full and Change					
j	CRD	Columbia River Datum					
k	GCLWD	Gulf Coast Low Water Datum					



H Tides, Currents

No.			INT			EC	DIS
31	Tidal stream table	-2 094 1.3 90 -1 092 1.0 0 081 0.7 0 081 0.3 +1 038 0.3 +2 291 0.6 +3 277 1.0	D.7 D.1 D.8 1.2 1.1 D.9 D.6 D.2 D.4 D.8 1.0 1.0			Point or area for which a tidal stream table is available Boundary of an area for which there is tidal information	
	Streams and Currents					Supplementary nationa	I symbols: m–t
	rers → K Tide Gauge →		NOAA	NOA	044		
No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
40	,	Flood tide stream with mean spring rate				2.5 kn ?	Flood stream, rate at spring tides Current or tidal stream whose direction is not known Boundary of an area for which there is tidal information
41	2.8 kn	Ebb tide stream with mean spring rate				2.5 kn ? Å? ? Å?	Ebb stream, rate at spring tides Current or tidal stream whose direction is not known Boundary of an area for which there is tidal information

Tides, Currents H

No.	INT	Description	NOAA	NGA	Other NGA	EC	ECDIS	
42	»»»»>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	Current in restricted waters				2.5 kn		
43	2.5 – 4.5 kn Jan – Mar (see Note)	Ocean current with rates and seasons		~~~~~	(see Note)	2.5 Ki	Non-tidal current	
44	utter Utter Utter	Overfalls, tide rips, races	Tide rips		≈*	MA MÁ	Overfalls, tide rips; ed-	
45	0 0 0 0 0 0	Eddies				(m)	dies; breakers as point, line, and area	
46	\otimes	Position of tabulated tidal stream data with designation				\diamond	Point for which a tidal stream table is available	
47	a	Offshore position for which tidal levels are tabulated						
Suppl	ementary National Symbols (Supplementary national terms r	elating to tidal leve	Is are listed after H	17)	1		
I		Stream	Ş	Str				
m		Current, general, with rate	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	2 kn →				
n		Velocity, Rate	١	vel				
0		Knots	I	ĸn				
р		Height		ht				
q		Flood		fl				
u		Gulf Stream Limits	Approximate location	of Axis of Gulf Stream				

No.	INT	Description	NOAA	NGA	Other NGA	E	CDIS
Gener	al						
1	ED	Existence doubtful				25	Sour accu
						25	Sour accu
2	SD	Sounding of doubtful depth				(212)	Unde depti mete
						•	Isola less conto
						25	Sour accu
3.1	Rep	Reported, but not confirmed				Ś	Poin Iow a
3.2	Rep (2011)	Reported (with year of report),				`	Low dem or ob
		but not confirmed					Low dema
							Obst state
						25	Sour accu
		Reported, but not confirmed				5	Unde depti less
4	184 22	sounding or danger (on small scale charts only)				(212)	Unde depti mete

Sounding of low accuracy

Sounding of low accuracy

meters

contour

Sounding of low accuracy

Underwater hazard with depth greater than 20

Isolated danger of depth less than the safety

Point feature or area of low accuracy

Low accuracy line demarking area wreck or obstruction Low accuracy line demarking foul area

Obstruction, depth not

Underwater hazard with depth of 20 meters or

Underwater hazard with depth greater than 20

Isolated danger of depth less than the safety

Point feature or area of low accuracy

Sounding of low accuracy

stated

meters

contour

•

Ś

Depths

Depths

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS			
Sound	dings					Supplementary national s	ymbols: a–c		
Plane	Plane of Reference for Depths \rightarrow H Plane of Reference for Heights \rightarrow H								
10	12 9 ₇	Sounding in true position (NOAA shows fathoms and feet with vertical numbers and meters	12 3 ₂ 2 ¹ ₂			97	Sounding shoaler than or equal to safety depth Sounding deeper than		
	with sloping numbers)				30	safety depth			
11	. (4 ₈) +(12) 3375	Sounding out of position	(23)	3375		Depths are always shown	in their true position in		
12	(47)	Least depth in narrow channel	(47)			ECDIS			
13	200	No bottom found at depth shown				200	Status of no bottom found is obtained by cursor pick		
14	12 9 ₇	Soundings which are unreliable or taken from a smaller scale source (NOAA shows unreliable soundings in fathoms and feet with sloping numbers and in meters with vertical numbers)				(12)	Sounding of low accuracy		
15	$\begin{array}{c c} & & & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & &$	Drying heights and contours above chart datum	50 <u>6</u>	ww		<u>4</u>	Drying height, less than or equal to safety depth		
16	2_5 2_5 2_5 2_6 2_6 1_7 2_6 1_7	Natural watercourse (in intertidal area)				7	Tideway		

Depths

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS				
Depth	Depths in Fairways and Areas Supplementary national symbols: a, b									
Plane	Plane of Reference for Depths \rightarrow H									
20		Limit of dredged area								
21	7.0 m 3.5 m	Dredged channel or area with minimum depth regularly maintained				*	Dredged area Depth, date of latest			
22	12m (2011) Dredged to 7.2m (2011)	Dredged channel or area with depth and year of the latest control survey	30 FEET APR 2011				survey and other information is obtained by cursor pick			
24	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Area swept by wire drag. The depth is shown at chart datum. (The latest date of sweeping is shown in parentheses.)	3 29 8 22 7 21 30 7 21	<u>7</u> 6 (1930)		swept to 9.6	Swept area			
25	Unsurveyed (see ZOC Diagram) (Depths (see Note)	Unsurveyed or inadequately surveyed area; area with	Unsurveyed		Unsurveyed (see Note) (see Note) (see Note)		Incompletely surveyed area			
23	(Inadequately surveyed) (Unsurveyed)	inadequate depth information	13 11 12 13 10 17 13 rky 22 20		Unsurveyed (see Note) (see Note) (see Note)		Unsurveyed area			

ECDIS Portrayal of Depths



ECDIS depth related symbols closely resemble their paper chart counterparts; however, ECDIS provides valuable additional information to mariners that paper charts cannot.


Soundings

ECDIS enables mariners to set their own-ship "safety depth." If no depth is set, ECDIS sets the value to 30m. Soundings equal to or shoaler than the safety depth are shown in black; deeper soundings are displayed in a less conspicuous gray. Fractional values are shown with subscript numbers of the same size.

Depth Contours & Depth Areas

Depth contours in ECDIS are portrayed with a thin gray line. Each pair of adjacent depth contours is used to create depth area features. These are used by ECDIS to tint different depth levels and to initiate alarms when a ship is headed into unsafe water.

Depth Contour Labels




ECDIS depth contour labels are not centered and oriented along isolines as they appear on paper charts. They are displayed upright and may appear either on or next to the contour lines that they describe. The labels are black and the same size as soundings, but the labels have a light "halo" to set them apart. The graphic to the left shows depth labels and soundings both deeper and shoaler than the safety depth. Note that depths on NOAA paper charts and ENCs are usually compiled in fathoms and feet. Because ECDIS displays depths in meters, soundings and contour lines often show fractional meter values. The "own-ship safety contour" (described below) is always displayed, but mariners may choose to have all other depth contours turned off.

Safety Contour

ECDIS uses a "safety contour" value to show an extra thick line for the depth contour that separates "safe water" from shoaler areas. If the mariner does not set an own-ship safety contour value, ECDIS sets the value to 30m. If the ENC being displayed does not have a contour line equal to the safety contour depth value set by the mariner, then ECDIS sets the next deeper contour as the safety contour. Depending on the contour intervals used on individual ENCs, ECDIS may set different safety contours as a ship transits from one ENC to another. ECDIS will initiate an alarm if the ship's future track will cross the safety contour within a specified time set by the mariner.


Two or Four Tints for Shading Depth Areas

ECDIS tints all depth areas beyond the (green tinted) foreshore in either one of two or one of four shades of blue. This is similar to the convention used for paper charts, but the depths used to change from one tint to another are based on the safety contour and thus "customized" for each ship. If the mariner chooses two shades to be displayed, water deeper than the safety contour is shown in an off-white color, water shoaler than the safety contour is tinted blue.




Portrayal of Depth Areas with 2 Color Settings

Some ECDIS enable mariners to define two additional depth areas for mediumdeep water and medium-shallow water by setting a "deep contour" value and a "shallow contour" value. If this option is used, the safety contour is displayed between the medium deep and medium shallow contours.



Portrayal of Depth Areas with 4 Color Setting



Some ECDIS also provide the mariner with the option of displaying a cross-hatch "shallow water" pattern over all depth areas shoaler than the safety contour.

Depths

No.	INT	Description	NOAA NGA	Other NGA	EC	DIS
Dept	n Contours					
	2 0 2 	Drying contour Low water line Blue tint, in one or more shades, or tint ribbons are shown to different limits according to the scale and purpose of the chart and the nature of the bathym-			foreshore	foreshore
30	15 25 3040 50 75 100	etry. On some charts, contours and values are printed in blue.	20 30 40 50 100 200		shallow depth	shallow water contour
30	200 300 400 500		200 300 400 500 700 800 900 1000 		deep depth all deeper	contour medium deep water deep contour deep contours deep
31		Approximate depth contours	20			Approximate depth contour Approximate safety depth contour
Supp	lementary National Symbols		·		· · · · · · · · · · · · · · · · · · ·	
а		Swept channel	<u>&</u>			
b		Swept area, not adequately sounded (shown by purple or green tint)	15 89 15 102 10 119			
с		Stream	21 5.8			

Nature of the Seabed $\ J$

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Турез	of Seabed					Supplementary nationa	l abbreviations: a–ag
Rocks	\rightarrow K						
1	S	Sand				S	Sand
2	М	Mud				м	Mud
3	Су	Clay				Су	Clay
4	Si	Silt				Si	Silt
5	St	Stones				St	Stones
6	G	Gravel				G	Gravel
7	Р	Pebbles				Р	Pebbles
8	Cb	Cobbles				Cb	Cobbles
9.1	R	Rock; Rocky	Rk;	rky		R	Rock
9.2	Во	Boulder(s)	Bi	ds		R	Boulder
						R	Lava
10	Со	Coral, Coralline algae				Co	Coral
11	Sh	Shells (skeletal remains)				Sh	Shells
12.1	S/M	Two layers, e.g. sand over mud					
12.2	fS M Sh fS.M.Sh	The main constituent is given first for mixtures, e.g. fine sand with mud and shells	f S M Sh				
13.1	Wd	Weed (including kelp)				~~~	Weed, kelp
13.2	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Kelp, Weed		- Kelp		~~~)	Weed, kelp as an area
13.3	Sg	Seagrass				`	

J Nature of the Seabed

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
						~~~	Sand waves as a point
14	$\sim$	Sandwaves	NN s	NN Sandwaves		AAA	Sand waves as a line
						Ann A Ann A	Sand waves as an area
15	1	Spring in seabed	T s	pring		T	Spring
Types	s of Seabed, Intertidal Areas		1				
20	G St St	Area with stones and gravel	Grave	1		gravel stone	Areas of gravel and stone
21	12 S * (42)	Rocky area, which covers and uncovers	E E Change and the	Rock	80		Rocky ledges or coral
22	$ \begin{array}{c} & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & $	Coral reef, which covers and uncovers	Er Coral	S. S. Market	0		reef
Qualit	fying Terms					Supplementary national	symbols: ah–bf
30	f	Fine only used in					
31	т	Medium > relation to					
32	С	Coarse Sand					
33	bk	Broken					
34	sy	Sticky					
35	so	Soft					
36	sf	Stiff					
37	V	Volcanic	v	ol			I
38	са	Calcareous	c	Sa			Rocky ledges or coral reef
39	h	Hard					

## Nature of the Seabed J

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS
Supplem	nentary National Abbreviation	IS				
а		Ground	Grd			
b		Ooze	Oz			
С		Marl	MI			
d		Shingle	Sn			
f		Chalk	Ck			
g		Quartz	Qz			
h		Schist	Sch			
i		Coral head	Co Hd			
j		Madrepores	Mds			
k		Volcanic ash	Vol Ash			
I		Lava	La			
m		Pumice	Pm			
n		Tufa	Т			
0		Scoriae	Sc			
р		Cinders	Cn			
q		Manganese	Mn			
r		Oysters	Oys			
S		Mussels	Ms			
t		Sponge	Spg			
u		Kelp	К			
v		Grass	Grs			
w		Sea-tangle	Stg			
x		Spicules	Spi			
у		Foraminifera	Fr			
z		Globigerina	GI			
aa		Diatoms	Di			
ab		Radiolaria	Rd			
ac		Pteropods	Pt			
ad		Polyzoa	Po			
ae		Cirripedia	Cir			
af		Fucus	Fu			

#### J Nature of the Seabed

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS
ag		Mattes	Ма			
ah		Small	sr	nl		
ai		Large	lr	g		
aj		Rotten	r	t		
ak		Streaky	si	r		
al		Speckled	sr	k		
am		Gritty	gt	У		
an		Decayed	de	ec		
ao		Flinty	fl	/		
ар		Glacial	gla	ac		
aq		Tenacious	te	n		
ar		White	W	h		
as		Black	bl;	bk		
at		Violet	v	i		
au		Blue	b	и		
av		Green	g	า		
aw		Yellow	у	I		
ax		Orange	0	r		
ay		Red	ro	1		
az		Brown	b	r		
ba		Chocolate	Cl	h		
bb		Gray	g.	Ý		
bc		Light	li			
bd		Dark	dk			
be		Varied	vard			
bf		Uneven	un	ev		

# Rocks, Wrecks, Obstructions and Aquaculture $\,\,\, K$

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Gene	eral					-	
						٠	Obstruction, depth not stated
	·····	Danger line: A danger line draws				•	Obstruction which covers and uncovers
1		attention to a danger which would not stand out clearly enough if represented solely by				5	Underwater hazard with depth of 20 meters or less
		its symbol (e.g. isolated rock) or delimits an area containing numerous dangers, through				$\mathbf{S}$	Isolated danger of depth less than the safety contour
		which it is unsafe to navigate					Foul area, not safe for navigation
2	<u>_7</u> 5	Depth swept by wire drag or confirmed by diver (This symbol may be combined	<u>.21</u> ,Rk . <u>35</u> ,F	Rk (46) Obstr	<u>.</u> #, (15 ₇ )	<u>4</u>	Swept sounding, less than or equal to safety depth
		with other symbols, e.g. wrecks, obstructions, wells.)	4 ₆ Wk	(1937)		.21.	Swept sounding, greater than safety depth
3	20	Safe clearance depth. The exact depth is unknown, but is estimated to have a safe clearance at the depth shown	46 Wk 35 F	Rk 46 Obstri		ECDIS displays safe clea manner as known depths	rance depths in the same
Rock	S						
Plane	of Reference for Heights $\rightarrow$ H	Plane of Reference for Dep	oths $\rightarrow$ H			1	
	(3,1)	Rock (islet) which does not		<b>^</b>		•	Land as a point at small scale
10	Height datum Chart datum	cover, height above height datum	(25)	O ₍₂₁₎	<b>A</b> (4 m)	<b>O</b> 8 m	Land as an area, with an elevation or control point
						×	Rock which covers and uncovers or is awash at low water
11	<u>ل</u> م	Rock which covers and uncovers, height above chart datum	* (2) * (2) (2) (2) (2) (4) (2) (2) (2) (3) (4) (2) (2) (2) (2) (3) (2) (3) (2) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3) (3		،	4	Underwater hazard which covers and uncovers with drying height
	Chart datum 5m			J 01000 III		8	Isolated danger of depth less than the safety contour

### K Rocks, Wrecks Obstructions and Aquaculture

No.	INT	Description	NOAA	NGA	Other NGA		ECDIS
	* *					*	Rock which covers and uncovers or is awash at low water
12		Rock awash at the level of chart datum			#		Underwater hazard which covers and uncovers
	Height datum Chart datum 5m					8	Isolated danger of depth less than the safety contour
	+ + + + + + + + + + + + + + + + + + +	Underwater rock of unknown				•	Dangerous underwater rock of uncertain depth
13	Height datum Chart datum 5m	depth, dangerous to surface navigation				⊗	Isolated danger of depth less than the safety contour
14	$\begin{array}{c} 2_{5} + (4_{8}) \\ R \\ \dot{5} \end{array} \xrightarrow{(5)} 12_{1}R \\ + (12_{1}) \\ \end{array}$	Underwater rock of known depth					
14.1	Height datum Chart datum 5m -10m 20m	inside the corresponding depth area	12 <i>Rk</i>	27 Rk 21		5	Underwater hazard with a depth of 20 meters or less
				R		- 25	Underwater hazard with depth greater than 20 meters
44.0	$\begin{array}{c} \begin{array}{c} \begin{array}{c} \\ \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \\ \end{array} \\ $	outside the corresponding depth		⁴ ₂ Rk			
14.2	Chart datum 5m 10m 20m	area, dangerous to surface navigation	(5) Rk	5 _R		$\boldsymbol{\otimes}$	Isolated danger of depth less than the safety contour
15	35	Underwater rock of known	35 <i>Rk</i>		35+(35)	10	Underwater hazard with a depth of 20 meters or less
15	35 R	depth, not dangerous to surface navigation			35 +(35) R.	25	Underwater hazard with depth greater than 20 meters

# Rocks, Wrecks, Obstructions and Aquaculture $\,\,\, K$

No.	INT		Description	NOAA	NGA	Other NGA	EC	DIS
16	(+++++++++++++++++++++++++++++++++++++	+ <del>co</del> +	Coral Reef which is always covered	$\left\langle \begin{array}{c} +Co \\ 3_1 + \end{array} \right\rangle$ Reef	line + +		$ \begin{array}{c}                                     $	Dangerous underwater rock of uncertain depth Obstruction, depth not stated Isolated danger of depth less than the safety contour Safe clearance shoaler than safety contour Safe clearance deeper than safety contour Safe clearance deeper than 20 meters
17	-335	(58) Br 18	Breakers	Breakers	Br	West Breaker PA	MA MA (MA)	Overfalls, tide rips; eddies; breakwaters as point, line, and area
Wrec	ks and Fouls							L
Plane	of Reference for Depth	ıs → H						
20	Www	Mast (1.2)	Wreck, hull never covers, on large scale charts, height above height datum		≻ Hk	Hk	<b>0</b> 1.2 m	Wreck, always dry, with height shown
21	Mast (12)       Wreck, covers and uncovers, on large scale charts, height above chart datum		Hk			12	Wreck, covers and uncovers Distributed remains of wreck	

### K Rocks, Wrecks Obstructions and Aquaculture

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
						52	Submerged wreck with depth of 20 meters or less
22	52 Wk 65 Wk	Submerged wreck, depth known, on large scale charts			<wk< td=""><td>25</td><td>Submerged wreck with depth greater than 20 meters</td></wk<>	25	Submerged wreck with depth greater than 20 meters
						X X X X X X X	Distributed remains of wreck
23	Wĸ	Submerged wreck, depth unknown, on large scale charts		5> Hk	C> Wk C> Wk	(3)	Submerged wreck with depth less than the safety contour or depth unknown
24	*	Wreck showing any portion of hull or superstructure at level of chart datum				*	Wreck showing any portion of hull or superstructure at level of chart datum
25	🌐 Masts	Wreck of which the mast(s) only are visible at chart datum	🌐 Masts	Mast (10ft) • Funnel			
						5	Underwater hazard with depth of 20 meters or less
26	Wk 29 Wk	Wreck, least depth known by sounding only			offer (11)	25	Underwater hazard with depth greater than 20 meters
							Isolated danger of depth less than the safety contour
						46	Swept sounding for underwater hazard less than safety depth
27		Wreck, depth swept by wire drag or confirmed by diver	<u>25</u> Wk			25	Swept sounding for underwater hazard greater than or equal to safety depth
						$\bigotimes$	Isolated danger of depth less than the safety contour

# Rocks, Wrecks, Obstructions and Aquaculture $\,\,\, K$

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
		Descence words don't				<b>#</b>	Dangerous wreck, depth unknown
28	<b>*</b>	Dangerous wreck, depth unknown				$\bigotimes$	Isolated danger of depth less than the safety contour
29	+++	Sunken wreck, not dangerous to surface navigation				+++	Non-dangerous wreck, depth unknown
						5	Underwater hazard with safe clearance of 20 meters or less
30	( <u>25</u> )Wk	Wreck over which the exact depth is unknown, but which is estimated to have a safe clearance at the depth shown.			<u>(</u> <b>4</b> ) <i>Wk</i>	25	Underwater hazard with safe clearance greater than 20 meters
						$\bigotimes$	Isolated danger of depth less than the safety contour
31.1	#					#	Foul area of seabed safe for navigation but not for anchoring
31.2	## ↓	Foul ground, not dangerous to surface navigation, but to be avoided by vessels anchoring, trawling, etc. (e.g. remains of wreck, cleared platform)					Foul ground
01.2						X X X X X X X X	Distributed remains of wreck
Obsti	uctions and Aquaculture						
Plane	of Reference for Depths $\rightarrow$ H	Kelp, Seaweed $\rightarrow$ J	Underwater Installa	tions $\rightarrow$ L			
						۲	Obstruction, depth not stated
40	Obstn Obstn	Obstruction, depth unknown				8	Isolated danger of depth less than the safety contour
						× × × × × ×	Safe clearance shoaler than safety contour

# K Rocks, Wrecks Obstructions and Aquaculture

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
						5	Underwater hazard with depth of 20 meters or less
41	6 Obstn (6) Obstn	Obstruction, least depth known by sounding only				25	Underwater hazard with depth greater than 20 meters
						$\boldsymbol{\otimes}$	Isolated danger of depth less than the safety contour
						swept	Less than or equal to safety depth
						21. J ^{depth}	Greater than safety depth
		Obstruction, depth swept by wire				Method of de obtained by c	pth measurement is cursor pick
42	🚯 Obstn 🛛 🙆 Obstn	drag or confirmed by diver				5 known by diver or	Underwater hazard with depth of 20 meters or less
						25 X other means	Underwater hazard with depth greater than 20 meters
						⊗	Isolated danger of depth less than the safety contour
43.1	777 Obstn	Stumps of posts or piles, wholly submerged	o ⁰ Subm piles	Piles	T 7	۲	Obstruction, depth not stated
			<ul> <li>Subm piles</li> </ul>	° Well		5	Underwater hazard with depth of 20 meters or less
43.2	ĩ	Submerged pile, stake, snag, or stump (with exact position)	<ul><li>Stakes</li><li>Snags</li></ul>	<ul> <li>Deadhead</li> <li>Stump</li> </ul>	€ ~ Ţ	8	Isolated danger of depth less than the safety contour
							Fish stakes as a point
44.1	فللتسليل	Fishing stakes		⊥⊔ Fsh stks			Fish stakes as an area
44.2		Fish trap, Fish weir, Tunny nets	Fish trap				Fish trap, fish weir, tunny net as a point

# Rocks, Wrecks, Obstructions and Aquaculture $\,\,\, K$

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
45	Fish traps   Tunny nets	Fish trap area, Tunny nets area					Fish trap, fish weir, tunny net as an area
46.1		Fish haven	Obstn Fish Haven	(actual		8	Isolated danger of depth less than the safety contour
						x × x 🐼 × x >	Safe clearance shoaler than safety contour
						5	Underwater hazard with depth of 20 meters or less
						25	Underwater hazard with depth greater than 20 meters
46.0		Fich haven with existences doubt	Obstr			8	Isolated danger of depth less than the safety contour
46.2	24	Fish haven with minimum depth	(auth min 42ft)			× × × × ×	Safe clearance shoaler than safety contour
						12 ₈	Safe clearance deeper than safety contour
							Safe clearance deeper than 20 meters
47		Shellfish beds					
							Marine farm as a point
48.1		Marine farm (on large scale charts), area of marine farms		└ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─ ─			
48.2	EQ E3	Marine farm (on small scale charts)		Obstn (Marine Farm)			Marine farm as an area
Supp	lementary National Symbols						
а		Rock which covers and uncovers, (height unknown)	* *				

#### K Rocks, Wrecks Obstructions and Aquaculture

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS
b		Shoal sounding on isolated rock or rocks	5 Rk 21 Rks		(1) (2) (2) (2) (2) (2) (2) (2) (2) (2) (2	
с		Sunken wreck covered 20 to 30 meters	+++		*	
d		Submarine volcano	( ) si	ıb vol		
е		Discolored water	( ) Di	scol water		
f		Sunken danger, least depth cleared by wire drag	<u>_21</u> .Rk 4 ₆ 3	35_Rk 46 Obstn		
g		Reef of unknown extent	R	eef		
h		Coral reef, detached (uncovers at sounding datum)	⊛∞ 💭			
i		Submerged crib	Subm Crib	[]] Crib		
j		Crib, duck blind (above water)	Duck Blir	nd 🔲 Crib		
k		Submerged duck blind	[]] Du	ck Blind		
I		Submerged platform	Subm platform	[]] Platform		
m		Coral reef which covers and uncovers		Hay Reef		
n		Sinkers		51405-134 15		
ο		Foul area, foul with rocks or wreckage, dangerous to navigation	Foul) Wikš Wreckage			
р		Unexploded ordnance	Unexploded Ordnance	Unexploded Ordnance		
q		Float	🗌 Float			
r		Stumps of posts or piles, which cover and uncover	o ⁰ Subm piles			

#### Offshore Installations L

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Gene	eral						
Areas	, Limits $\rightarrow$ N						
1	Ekofisk Oilfield	Name of oilfield or gasfield		Well 348 CORRIB Well 346 GAS FIELD / 1 Well 334			Area to be navigated with caution, name is obtained by cursor pick
2	● Z-44	Platform with designation/name		↓ "Name"			Offshore platform, name is obtained by cursor pick
3		Limit of safety zone around offshore installation					Area where entry is prohibited or restricted or to be avoided, with other cautions
4		Limit of development area					Cautionary area, navigate with caution
5.1	1 / 13	Wind turbine, floating wind turbine, vertical clearance under blade			FI.Y	۲	Wind motor visually conspicuous
5.2		Offshore wind farm				ANDA	Wind farm (offshore)
0.2		Offshore wind farm (floating)				R S A	
6		Wave farm, Renewable energy device					Wave farm
Platfo	orms and Moorings						
Moori	ng Buoys $\rightarrow$ Q						
10	Ē	Production platform, Platform, Oil derrick	•	۲		R.	Offshore platform
11	● Fla	Flare stack (at sea)		$\odot$	2	ŧ	Conspicuous flare stack on offshore platform

#### Offshore Installations

L

No.	INT	Description	NOAA	NGA	Other NGA	E	CDIS
12	I SPM	Single Point Mooring (SPM), including Single Anchor Leg Mooring (SALM), Articulated Loading Column (ALC)		● "Name"			Offshore platform, name and status of disused is
14	● Ru ● Z-44 (ru)	Disused platform with superstructure removed			• (disused)		obtained by cursor pick
16		Single Buoy Mooring (SBM), Oil or gas installation buoy including Catenary Anchor Leg Mooring (CALM)				<b>ھُ</b>	Installation buoy and mooring buoy, simplified Installation buoy, paper chart
17	<u>/</u>	Moored storage tanker, Accommodation vessel		🖧 Tanker			Offshore platform
18		Mooring ground tackle				t	Ground tackle
Unde	erwater Installations					Supplementary nationa	l symbol: a
Plane	of Reference for Depths $\rightarrow$ H	$Obstructions \to K$					
20	, Well	Submerged production well	<ul> <li>Well         (cov 21ft)         Well         (cov 83ft)         (cov 83ft)</li></ul>	🔵 Well	5 Prod Well	<b>5</b>	Underwater hazard with depth of 20 meters or less Underwater hazard with depth greater than 20 meters
			*			•	Isolated danger of depth less than the safety contour
21.1	() Well	Suspended well, depth over wellhead unknown	<ul><li>Pipe</li></ul>			$\mathbf{c}$	Isolated danger of depth less than the safety contour
			Qia a			5	Underwater hazard with depth of 20 meters or less
21.2	🚯 Well (B) Well	Suspended well, with depth over wellhead	<ul> <li>Pipe (cov 24ft)</li> <li>Pipe (cov 92ft)</li> </ul>			25	Underwater hazard with depth greater than 20 meters
			(			$\mathbf{O}$	Isolated danger of depth less than the safety contour

#### Offshore Installations L

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
22	#	Site of cleared platform				#	Foul area of seabed safe for navigation but not for anchoring
23	● Pipe (●) ^{Pipe} (1 ₈ )	Above-water wellhead (lit or unlit)	∘ Pipe				Obstruction in the water which is always above water level
24	Turbine Underwater Turbine	Underwater turbine				Ŏ	Underwater turbine or
25	ODAS	Subsurface Ocean(ographic) Data Acquisition System (ODAS)				i	subsurface ODAS
Subn	narine Cables						
30.1		Submarine cable				-~ \<	Submarine cable
30.2	+++++	Submarine cable area	†Cable Area			r 4 🗸 🗸	
31.1		Submarine power cable				¢´∠ ∢	Submarine cable area
31.2	~~++++~~\$~~++++~~~ ~~++++~~\$~~++++~~~	Submarine power cable area				× 4	
32	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Disused submarine cable				-~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Status of disused is obtained by cursor pick
Subn	narine Pipelines		<u>`</u>		` 		
40.1	$ \begin{array}{c} \hline \\ \hline $	Supply pipeline: unspecified, oil, gas, chemicals, water				-	Oil, gas pipeline, submerged or on land
40.2	$ \overrightarrow{} a$	Supply pipeline area: unspecified, oil, gas, chemicals, water	t — <u>Pipeline Area</u> —				Submarine pipeline area with potentially dangerous contents

#### Offshore Installations

L


No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
41.1	→ → → → → → → → → → → → → → → → → → →	Outfall and intake: unspecified, water, sewer, outfall, intake				<u> </u>	Water pipeline, sewer, etc.
41.2	$ \rightarrow \rightarrow$	Outfall and intake area: unspecified, water, sewer, outfall, intake	 Pipeline Area				Submarine pipeline area with generally non-dangerous contents
42.1	Buried 1.6m	Buried pipeline/pipe (with nominal depth to which buried)					Nominal depth of buried pipeline is obtained by cursor pick
42.2	$\rightarrow \rightarrow \rightarrow \rightarrow$ ) ( $\rightarrow \rightarrow \rightarrow$	Pipeline tunnel					Pipeline tunnel
43	$\rightarrow$ $\rightarrow$ $\rightarrow$ $\rightarrow$ $\rightarrow$ $\rightarrow$ $\rightarrow$ $\rightarrow$ $\rightarrow$ $32$ Obstr	Diffuser, Crib					Underwater hazard with depth of 20 meters or less Isolated danger of depth less than the safety contour
44	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Disused pipeline/pipe				*	Status of disused is obtained by cursor pick
Supp	Supplementary National Symbols						
а		Submerged well (buoyed)	🕈 Well 🖗 Well	A well			
b		Potable water intake	<i>PWI</i> <i>Depth over</i> <i>Crib 17 ft</i>	$\begin{array}{c} \hline \\ \hline \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ $			

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS	
Tracl	ks				1	Supplementary national symbols: a-c	
Tracks Marked by Lights $\rightarrow$ P Leading Beacons $\rightarrow$ Q							
1	L	Leading line (solid line is the track to be followed, <i>‡</i> means "in line")		Lights in line 090°		Leading line bearing a non-regulated, recommended track $- < ?> <$ Direction not encoded $- < ?> <$ Direction not encoded $- < ?> <$ Direction not encoded $- < ?> <$ One-way $- 270 \text{ deg}$ Two-way	
2	↓	Transit (other than leading line), clearing line		_Beacons in line 090°	Bns in line 270.5°	270 deg Clearing line; transit line	
3	090.5°-270.5°	Recommended track based on a system of fixed marks		Lights in line 090°	> >>	Non-regulated, recommended track based on fixed marks $- < ?> <$ Direction not encoded $\rightarrow$ $\rightarrow$ One-way $\leftarrow$ $270 \text{ deg}$ Two-way	
4		Recommended track not based on a system of fixed marks	-	> >		Non-regulated, recommended track not based on fixed marks $- < ? > <$ Direction not encoded $- > - 200 \text{ deg}$ One-way $- < - > - 270 \text{ deg}$ Che-way	
5.1		One-way track and DW track based on a system of fixed marks	>-	>		Based on fixed marks, one-way → 90 deg Non-regulated recommended track → <u>DW</u> → Deep water route	
5.2	270°	One-way track and DW track not based on a system of fixed marks				Not based on fixed marks, one-way $->$ $\stackrel{90 \text{ deg}}{}>$ Non-regulated $->$ $>$ $->$ Deep water route $->$ $>$ Deep water route         centerline $>$ $>$	
6	<7.0m><7.3m>	Recommended track with maximum authorized (or recommended) draft stated		$ \begin{array}{c} \hline & < 7 m \\ \hline & < 7_3 m \\ \hline \end{array} $		If encoded, the shoalest depth range value along the track is obtained by cursor pick	

#### M Tracks, Routes


No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Rout	ing Measures					Supplementary nationa	al symbols: d–e
Basic	Symbols						
10		Established (mandatory) direction of traffic flow					Traffic direction in a one-way lane of a traffic separation scheme
11	====	Recommended direction of traffic flow					Single traffic direction in a two-way route part of a traffic-separation scheme
12		Separation line (large scale, small scale)					Traffic separation line
13		Separation zone					Traffic separation zone
14	<u>+</u> +++++++++++++++++++++++++++++++++++	Limit of restricted routing measure (e.g. Inshore Traffic Zone (ITZ), Area to be Avoided (ATBA))					
15		Limit of routing measure					Traffic separation scheme boundary
						$\square$	Traffic precautionary area as a point
16	Precautionary Area	Precautionary area					Traffic precautionary area as an area
17	ASLISEE NOTED	Archipelagic Sea Lane (ASL); axis line and limit beyond which vessels shall not navigate					Axis and boundary of archipelagic sea lane
18	FAIRWAY 7.3m FAIRWAY 7.3m FAIRWAY <7.3m>	Fairway designated by regulatory authority: with minimum depth with maximum authorized draft (may be highlighted by gray tint)	SAFETY FAIRWAY 1	66.200 (see note A)		••••••	Fairway, depth is ob- tained by cursor pick

## Tracks, Routes M



## M Tracks, Routes

No.					
Exa	Examples of Routing Measures				
18	Safety fairway				
(20.1)	Traffic Separation Scheme (TSS), traffic separated by separation zone				
(20.2)	Traffic Separation Scheme, traffic separated by natural obstructions				
20.3	Traffic Separation Scheme, with outer separation zone separating traffic using scheme from traffic not using it				
21	Traffic Separation Scheme, roundabout with separation zone				
22	Traffic Separation Scheme, with "crossing gates"				
23	Traffic Separation Scheme crossing, without designated precautionary area				
24	Precautionary area				
(25.1)	Inshore Traffic Zone (ITZ), with defined end limits				
(25.2)	Inshore Traffic Zone, without defined end limits				
(26.1)	Recommended direction of traffic flow, between traffic separation schemes				
(26.2)	Recommended direction of traffic flow, for ships not needing a deep water route				
(27.1)	Deep water route (DW), as part of one-way traffic lane				
(27.2)	Two-way deep water route, with minimum depth stated				
27.3	Deep water route, centerline as recommended one-way or two-way track				
(28.1)	Recommended route, one-way and two-way (often marked by centerline buoys)				
(28.2)	Two-way route, with one-way sections				
(29.1)	Area to be Avoided (ATBA), around navigational aid				
(29.2)	Area to be Avoided, e.g. because of danger of stranding				



## M Tracks, Routes

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Rada	r Surveillance Systems						
30	o Radar Surveillance Station	Radar surveillance station	O Ra			۲	Radar station
31	Ra Cuxhaven	Radar range					Radar range
32.1	Ra	Radar reference line			—Ra ——Ra —	270 deg	Radar line
						Non-regulated re based on f	commended track ixed marks
22.0	Ra 090°–270°	Radar reference line coinciding				- <	Direction not encoded
32.2		with a leading line				$\rightarrow$ 90 deg $\rightarrow$	One-way
						$\leftrightarrow$ 270 deg $\leftrightarrow$	Two-way
Radio	o Reporting Points						
						Nr 13 ch 74	Radio calling-in point for traffic in one direction only
40.1	E T VHF 80	Radio reporting (calling-in or way) points showing direction(s) of vessel movement with designation (if any) and VHF- channel				Nr 13 ch 74	Radio calling-in point for traffic in both directions
						? ♀ ? Nr 13 ? ♀ ? ch 74	Radio calling-in point, direction not encoded
							Radio calling-in point for traffic in one direction only
40.2	\$	Radio reporting line					Radio calling-in point for traffic in both directions
						$? \bigcirc ? \stackrel{\text{Nr 13}}{\frown} ? \stackrel{\text{ch 74}}{-}$	Radio calling-in point, direction not encoded

No.	INT	Description	NOAA NGA	Other NGA	ECDIS					
Ferri	Ferries									
50		Ferry	Ferry Fe	ту	— — — — — Ferry route					
51	Cable Ferry	Cable Ferry	Cable Ferry — — — — — — –		Cable ferry route					
Supp	elementary National Symbols									
а		Recommended track for deep draft vessels (track not defined by fixed marks)	<->>_D₩<>>							
b		Depth is shown where it has been obtained by the cognizant authority	>DW 83ft<->DW	6 <i>ti</i>						
с		Alternate course								

## N Areas, Limits

No.	INT	Description	NOAA NGA	Other NGA	ECDIS				
Gene	eral *			·					
Dredg	$Dredged and Swept Areas \rightarrow I \qquad Submarine Cables, Submarine Pipelines \rightarrow L \qquad Tracks, Routes \rightarrow M$								
On mu	lti-colored charts, symbols in Section N n	nay be in green when associated with	environmental areas.						
1.1	Tint band may vary in width between 1–5 mm	Maritime limit in general usually implying permanent physical obstructions (tint band for emphasis)			Caution area, a specific caution note applies				
1.2		usually implying no permanent physical obstructions (tint band for emphasis)							
2.1		Limit of restricted area (tint band for emphasis)	+ + + + + + + + + + + + + + + + + + +		Area where entry is prohibited or restricted or to be avoided				
2.2		Limit of area into which entry is prohibited			Area where entry is prohibited or restricted or to be avoided, with other cautions Area where entry is				
	וּ וּ Entry Prohibited דֽוּ		⊦ PROHIBITED AREA ⊦		prohibited or restricted or to be avoided, with other information				
Anch	orages, Anchorage Areas								
10	Ŷ	Reported anchorage (no defined limits)		Ĵ, Ĵ	Anchorage area as a point at small scale, or anchor points of moor-ing trot at large scale				
11.1		Anchor berths	(14)	6 L No 1	Nr 6 Anchor berth				
11.2	$ \begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} \right) \right) \end{array}\right) \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} \right) \end{array}\right) \end{array}\right) \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} 0 \end{array}\right) \end{array}\right) \end{array}\right) \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} \left(\begin{array}{c} 0 \end{array}\right) \end{array}\right) \left(\begin{array}{c} \left(\begin{array}{c} 0 \end{array}\right) \left(\begin{array}{c} \left(\begin{array}{c} 0 \end{array}\right) \left(\begin{array}{c} 0 \end{array}\right) \left(\begin{array}{c} \left(\begin{array}{c} 0 \end{array}\right) \left(\begin{array}{c} 0 \end{array}\right) \left(\begin{array}{c} 0 \end{array}\right) \left(\begin{array}{c} 0 \end{array}\right) \left(\begin{array}{c} \left(\begin{array}{c} 0 \end{array}\right) \left(\begin{array}{c} 0 \end{array}) \left(\begin{array}{c} 0 \end{array}\right) \left(\begin{array}{c} 0 \end{array}) $	Anchor berths with swinging circle	O D-17		Radius of swing circle is obtained by cursor pick				

* ECDIS represents many types of area limits with just a few different symbols. Information about the type of area and its associated restrictions or prohibitions may be obtained by cursor pick.


## Areas, Limits N

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
12.1		Anchorage area in general		Anchorage			
12.2	r — — — — — — — – ,ᢤ — — — — — — — — — — — — — — — — — —	Numbered anchorage area	ANCH NO 1 110.000 (see note A)	Anchorage		-	
12.3	r — — — — — — — – ↓ — — — — — — — — — — —	Named anchorage area	SOUTH ANCH 110.000 (see note A)				
12.4	г−−−−−÷+−−−− °+→ ∣ DW.ţ.	Deep water anchorage area, Anchorage area for deep draft vessels		DW   Anchorage		Þ <u> </u> ↓	
12.5	r — — — — — —‡.— — — — — — — — — — — — — — — — — —	Tanker anchorage area		 Tanker Anchorage			Type of anchorage area is obtained by cursor pick
12.6	Γ ─ ─ ─ ─ ─ ─ ─ - ᢤ ─ ─ ─ ↔ 24 h ᢤ	Anchorage area for periods up to 24 hours					
12.7	r — — — — — — — — — — — — — — — — — — —	Dangerous cargo anchorage area		ANCHORAGE			
12.8	r ↓ • ↓   	Quarantine anchorage area	QUAR ANCH QUARANTINE QUARANTINE ANCHORAGE	Quarantine Anchorage			
12.9	┌───────-ᢤ─── 。 ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	Reserved anchorage area				-	
Note: A	nchors as part of the limit symbol are not	shown for small areas. Other types	of anchorage areas may	be shown.			
13		Seaplane operating area	LAN	PLANE   DING   REA   			Seaplane landing area
14	÷.	Anchorage for seaplanes					Type of anchorage area is obtained by cursor pick

### N Areas, Limits

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Rest	ricted Areas					Supplementary nationa	al symbols: d, e, g
On mu	Ilti-colored charts, the magenta symbols n	nay be in green when associated wit	h environmental areas.				
							Area where anchoring is prohibited or restricted
20	╓┯┯┯┯╦╦┯┯┯╬┯┯┑ ┝ ┍┯┯┯┯╕ ┉┊ ┝╶╩╴┧ ┝ ╘┷┷┷┷┙	Anchoring prohibited		ANCH PROHIB		+ Z + + + ↓ Z + • + + Z +	Area where anchoring is prohibited or restricted, with other cautions
						+ Ż + + + i + + + i + +	Area where anchoring is prohibited or restricted, with other information
							Area where fishing or trawling is prohibited or restricted
21.1		Fishing prohibited	FISH FISH PROHIBITED	FISH PROHIB + → + + + + + + + + + + + + + + + + + +		┍┯╶┯╳╱╼ ┝╶┷╱╱┷╺┤	Area where fishing or trawling is prohibited or restricted, with other cautions
							Area where fishing or trawling is prohibited or restricted, with other information

### Areas, Limits N



### N Areas, Limits

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
23.1	Explosives Dumping Ground	Explosives dumping ground, individual mine or explosive	EXPLOSIVES			i	Explosives or chemical dumping ground as a point
23.2		Explosives dumping ground (disused), Foul (explosives)	EXPLOSIVES DUMPING AREA DISUSED				Explosives or chemical dumping ground as an
24	Dumping Ground for Chemicals	Dumping ground for chemical waste		F T T T T T T T Dumping Ground			area
25	+ + Degaussing Range	Degaussing range (DG range)	DEGAUSSING   RANGE 	+ + + + + + + +			Degaussing area
27	5kn	Maximum speed					striction exists, the speed led by cursor pick
Milita	ry Practice Areas		I		I		
30		Firing practice area					Restricted area
31	Entry     Prohibited     T	Military restricted area, entry prohibited	PROHIBITED	Prohibited Area			Area where entry is prohibited or restricted or to be avoided, with other cautions
32	κ κ Ι	Mine-laying (and counter- measures) practice area					Destricted area
33		Submarine transit lane and exercise area					Restricted area
34		Minefield					Minefield
Interr	national Boundaries and Nationa	al Limits				Supplementary nationa	al symbols: a, f, h
40	CANADA + + + + + + + + + UNITED STATES	International boundary on land					Jurisdiction boundary

## Areas, Limits N

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
41	+ + - + + + UNITED STATES	International maritime boundary					Jurisdiction boundary
42		Straight territorial sea baseline with base point		·			Straight territorial sea baseline
43	++	Seaward limit of territorial sea			TERRITORIAL SEA		Territorial sea
44	+	Seaward limit of contiguous zone					Contiguous zone
45	©	Limits of fishery zones			-		Limits of fishery zone
46	Continental Shelf	Limit of continental shelf					Continental shelf area
47	EEZ	Limit of Exclusive Economic Zone (EEZ)	<u> </u>				Exclusive economic zone
48		Customs limit			⊖		Custom regulations zone
49	Harbor Limit	Harbor limit		Harbor Limit		$\frown \frown \frown \frown \frown \frown \frown \frown$	Harbor area, symbolized
Vario	us Limits					Supplementary nationa	al symbols: a, b
60.1	(2012) ᡕᠴ᠇ᠯᠬᡨᡘᠯᠴᠯᡗᠴ᠋ᠴ᠇ᠬᠯᡅᡥᡊᡕᠯᠺᡝᠴᠯᡅᡘᢛ	Limit of fast ice, Ice front (with date)		······	terte		Continuous pattern for an
60.2	(2012) ᠬᠴᠡᡗᠯᠬᡆᡗᠯ᠇᠇ᠯᡗᢇᡗᠯᡊ᠇ᡗᠯᡊᡟᠯᠺᡕᠯᠺᠬᡘᡳᢒᠬ	Limit of sea ice (pack ice) seasonal (with date)		······	terte		ice area (glacier, etc.)
62.1	     Spoil Ground	Spoil ground	   Spo 				HO information note
62.2	- — — — — — — — — — — — — — — — — — — —	Spoil ground (disused)	 				The momation note
63	Extraction Area	Extraction (dredging) area					Dredging area
64	Cargo Transhipment Area	Cargo transhipment area					HO information note
65	I Incineration Area	Incineration area					

### N Areas, Limits

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS
Supp	lementary National Symbols					
а		COLREGS demarcation line				
b		Limit of fishing area (fish trap areas)				
с		Dumping ground	Dumping   Ground			
d		Dumping area (Dump site)	Disposal Area   Depths from   of 2010	a 92   survey   85 _		
f		Reservation line (Options)				
g		Dump site		 Site		
h		Three Nautical Mile Line	THREE NAUTICAL	. MILE LINE		
i		No Discharge Zone		 GE ZONE		

# Lights P

No.	IN	r	Description	NOAA	NGA	Other NGA	E	CDIS
Light	Structures and M	ajor Floating Li	ghts					
Minor L	_ight Floats → Q30, $\ddagger$	31						
1.1	☆ ★	Lt LtHo	Position of navigation light (size and style of "star" may vary) light, lighthouse			☆ � ● ·		Light, lighthouse, paper chart
1.2	,	*	Light on standard charts		•			
1.3	×		Significant all-round light, generally for offshore navigation on multicolored charts					
2.1		•	Lighted offshore platform on standard charts	■ PLATFORM (lighted)			I,	Lighted offshore platform, paper chart
2.2	Ĩ		Lighted offshore platform on multicolored charts					
3	Ê. B¥	☆ BnTr	Lighted beacon tower	o Marker (lighted)	<b>N</b>		Д Г	Lighted beacon tower, paper chart
4	R BRB	☆ Bn	Lighted beacon		•		ſ	Lighted beacon,
5	R R	☆ Bn	Articulated light, buoyant beacon, resilient beacon	Art	<b>N</b>			paper chart
Note: N	/linor lights, fixed and	d floating, usually	conform to IALA Maritime Buoyage	System characteristics.				
7		J.	Navigational lights on landmarks or other structures					
8	Holmasoo	astrong the state of the state	Important light off chart limits					

No.	Abbre	viaton	Class of Light	Period Sh	nown		ECDIS
	INT	NOAA					
-	Characters						
Light	Characters on Ligh	t Buoys $\rightarrow$ Q	1				
10.1	F	F	Fixed			F	
	Occulting (total	duration of light lon	ger than total duration of darkness	3)			
	Oc	Oc	Single-occulting			Oc	
10.2	Oc(2) Example	Oc (2)	Group-occulting			Oc (2)	
	Oc(2+3) Example	Oc (2+3)	Composite group-occulting			Oc (2+3)	
	Isophase (durat	ion of light and dar	kness equal)		I		
10.3	Iso	Iso	Isophase			lso ~ ~ ~	
	Flashing (total c	luration of light sho	rter than total duration of darkness	3)			
	FI	FI	Single-flashing			FI	When text for lights is displayed, ECDIS uses INT abbreviations.
10.4	FI(3) Example	FI (3)	Group-flashing			FI (3)	
-	Fl(2+1) Example	FI (2+1)	Composite group-flashing			FI (2+1)	
10.5	LFI	L FI	Long-flashing (flash 2s or longer)			LFL	
	Quick (repetition	n rate of 50 to 79 - ι	usually either 50 or 60 - flashes per	minute)	<b>t</b>		
	Q	Q	Continuous quick			Q \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
10.6	Q(3) Example	Q (3)	Group quick			Q(3)	
	IQ	IQ	Interrupted quick				
						× · · · · · · · · · · · · · · · · · · ·	

# Lights P

No.	Abbre	viaton	Class of Light	Period Shown		ECDIS
NO.	INT	NOAA	Class of Light			ECDIS
	Very quick (repe	etition rate of 80 to	159 - usually either 100 or 120 - fla	shes per minute)		
	VQ	VQ	Continuous very quick		VQ	
10.7	VQ(3) Example	VQ (3)	Group very quick	АЛА АЛА АЛА АЛА АЛА I	VQ(3)	
	IVQ	IVQ	Interrupted very quick	· · · · · · · · · · · · · · · · · · ·		
	Ultra quick (repe	etition rate of 160 o	r more - usually 240 to 300 - flashe	s per minute)		
10.0	UQ	UQ	Continuous ultra quick			When text for lights is displayed, ECDIS uses INT abbreviations.
10.8	IUQ	IUQ	Interrupted ultra quick			
10.9	Mo(K) Example	Mo (K)	Morse code		Mo (K)	
10.10	FFI	F FI	Fixed and flashing		F Fl	
10.11	AI.WR	AIWR	Alternating	W R W R W R	AI WR	

### P Lights

No.	II	NT	Description	NOAA	NGA	Other NGA		ECDIS	
Color	rs of Lights								
11.1		N	White (for lights, only on sector and alternating lights)		Colors of lights sho			Default light symbol if no	
11.2		R	Red	on standard charts				color is encoded or color is other than red, green, white, yellow, amber, or	
11.3		G	Green		,			orange	
11.4	E	Bu	Blue	on multicolored charts				Red	
11.5	,	Vi	Violet					Green	
11.6		Y	Yellow		on multicolored ch			White, yellow, amber or orange	
11.7	Y	Or	Orange		at sector lights			Sector lights	
11.8	Y	Am	Amber						
Perio	d								
12	2.5s	90s	Period in seconds and tenths of a second						
Eleva	ation								
Plane	of reference for Heig	ints $\rightarrow$ H	Tidal Levels $\rightarrow$ H						
13	1:	2m	Elevation of light given in meters or feet	36ft			When text for lights is displayed,		
Rang	le		1				E	ECDIS uses INT abbreviations.	
	1	5M	Light with single range						
14	15/	10M	Light with two different ranges	10M only lesser of two ranges is charted		15/10M			
	15	-7M	Light with three or more ranges	7M only least of three ranges is charted					
Note:	Charted ranges are	nominal ranges give	en in Nautical Miles.						
Dispo	osition								
	(r	lor)	Horizontally disposed						
15	(V	ert)	Vertically disposed				Disposition of light is ob	Disposition of light is obtained by cursor pick	
	(Δ)	(▽)	3 lights disposed in the shape of a triangle				, v		

## Lights P

No.		INT	Description	NOAA	NGA	Other NGA	ECDIS	
Exam	ple of a Full L	ight Description						
		INT Exan	nple	NOAA Example		NGA Example	₩ FIR15s21m11M	
	▼ Name ☆ FI(3)WRG.15s 21m 15-11M			• FI (3) WR	G 15s 21ft 11M	Name • FI (3) WRG 15s 21m 15-11M		
	FI(3)	Class of light: group three flashes	o flashing repeating a group of	FI(3)	Class of light: group flashin flashes	ng repeating a group of three	The descriptions of non-sector lights are shown in ECDIS when the display of text is turned on,	
	WRG	Colors: white, red, colors in defined se	green, exhibiting the different ections	WRG	Colors: white, red, green, ed defined sections	exhibiting the different colors in	as shown above. (The aid to navigation or other structure that is always shown attached to a light flare in ECDIS is not depicted here.)	
16	15s	15sPeriod: the time taken to exhibit one full sequence of three flashes and eclipses: 15 seconds15sPeriod: the time taken to exhibit one full sequence of three flashes and eclipses: 15 seconds		Sector lights (as described in the INT, NOAA and NGA examples at left) are depicted graphically in ECDIS, as shown below and in P40.				
	21m	Elevation of focal p	lane above datum: 21 meters	21ft 21m	Elevation of light: 21 feet 21 meters		The description of a sector light or any other type of light may always be obtained by cursor pick.	
	15-11M Nominal range: white 15M, green 11M, red between 15 and 11M			11M 15-11M	Nominal range: shortest range of all the lig white 15M, green 11M, rec		€===]	
Lights	s Marking Fair	ways						
Leadin	ig Lights and Lig	hts in Line						
20.1	Name Oc.3s 8m 12M * Name Oc.6s 2	4m15M	Leading lights with leading line (solid line is the track to be followed) and arcs of visibility on standard charts Bearing given in degrees and tenths of a degree	-	Res and a second s		Leading lights with sectors	

### P Lights


No.	INT	Description	NOAA	NGA	Other NGA	ECDIS
20.2	Name Oc.3s Bm12M * Name Oc.6s 24m 15M	Leading lights with leading line (solid line is the track to be followed) and arcs of visibility on multi-colored charts Bearing given in degrees and tenths of a degree				
20.3	Oc.4s 12M ★ ★ ★ Oc.R ≠ 269.3° Oc.R 4s 10M	Leading lights (≠ means lights in line) on standard charts Bearing given in degrees and tenths of a degree				Oc OcR 270 deg Leading lights
20.4	Oc.4s 12M ☆ Oc & Oc.R≠ 269.3° Oc.R 4s 10M	Leading lights (≠ means lights in line) on multi-colored charts Bearing given in degrees and tenths of a degree				
20.5	Ldg.Oc.W&R ☆	Leading lights on small scale standard charts				
20.6	Ldg.Oc.W&R 🛠	Leading lights on small scale multi-colored charts				
21.1	FI.G 270°	Lights in line, marking the sides of a channel on standard charts				FIG FIG 270 deg 2FIR 270 deg 2FIR 270 deg
21.2	FI.G FI.G 270 2FI.R	Lights in line, marking the sides of a channel on multi-colored charts				
22	Rear Lt or Upper Lt	Rear or upper light				
23	Front Lt or Lower Lt	Front or lower light				

## Lights P

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
Direc	ction Lights						
		Direction light with narrow				Directional light with sector	r
30.1	FI(2)5s10m11M ☆ ≪ 0 Dir 269°	sector and course to be fol- lowed, flanked by darkness or unintensified light				<	<
						Directional light without se	ector
30.2	Oc.12s6M * Dir 255.5° * FI(2)5s11M	Direction light on standard charts with course to be followed, sector(s) uncharted				FI(2)5s11M	Oc12s6M
30.3	Dir WRG.	Direction light with narrow fairway sector flanked by light sectors of different character on standard charts					Light, directional
30.4	Dir WRG. 15-5M Co.W.4s ALWR Co.W.4s	Direction light with narrow fairway sector flanked by light sectors of different character on multicolored charts				~ = = = =	Light, directional
31	A _o Dir 2350	Moiré effect light (day and night), arrows show when course alteration needed			A _o Dir ?%	FY 270 deg	Category of light as moiré effect is obtained by cursor pick
Quot	ed bearings are always from seaward.	,					1

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS				
Sect	Sector Lights									
40.1	FLWRG.4s 21m18-12M	Sector light on standard charts				- 1				
40.2	FI.WRG.4s 21m18-12M	Sector light on multicolored charts				€ E E E E E E E E E E E E E E E E E E E				
40.3	FI.WRG.4s + 21m18-12M +	Sector light on standard charts. Sectors not charted								
40.4	FI.WRG.4s 21m18-12M	Sector lights on multicolored charts. Sectors not charted								
41.1	Oc.WRG.	Sector lights on standard charts, the white sector limits marking the sides of the fairway								
41.2	Oc.WRG. 10-6M ☆ Oc.WRG. 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-5M 0-	Sector lights on multicolored charts, the white sector limits marking the sides of the fairway								

## Lights P



### P Lights

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS				
45.1	¢Q.14m5M	Light with faint sector				1	Light, faint				
46.1	Oc.R.8s7M	- Light with intensified sector				Intensified I cursor pick	ght visibility is obtained by Light, intensified				
Light	Lights with Limited Times of Exhibition										
50	<b>F.R.</b> (occas)	Lights exhibited only when specially needed (for fishing vessels, ferries) and some private lights	Occas	F R (occas)							
51	FI.10s40m27M * (F.37m11M Day)	Daytime light (charted only where the character shown by day differs from that shown at night)		F Bu 9m 6M (F by day)							
52	Name ☆ Q.WRG.5m 10-3M (FI.5s Fog)	Fog light (exhibited only in fog, or character changes in fog)				Status and obtained by	condition of light is cursor pick				
53	† ↓ FI.5s (U)	Unwatched (unmanned) light with no standby or emergency arrangements									
54	(temp)	Temporary									
55	(exting)	Extinguished									
56	(man)	Manually activated									
Spec	cial Lights	· · · · · · · · · · · · · · · · · · ·									
Flare	Stack (as sea) $\rightarrow$ L Fla	are Stack (on land) $\rightarrow$ E	Signal Stations	→ T							
60	☆ Aero Al.Fl.WG.7.5s11M	Aero light (may be unreliable)	AERO	AERO AI WG 7.5s 108m 13M	♦ ★ AERO	AeroAlFIWG7.5s11M	Light				

## Lights P

No.	INT	Description	NOAA	NGA	Other NGA		ECDIS		
61.1	<b>Aero F.R.313m 11M</b> <b>*</b> RADIO MAST (353)	Air obstruction light of high intensity (e.g. on radio mast)		AERO F R 77m 11M		AeroF	R313m11M	Conspicuous mast with light	
61.2	(89) ↓ (R Lts)	Air obstruction light of low intensity (e.g. on radio mast)		• TR (RLts)					
62	Fog Det Lt	Fog detector light					Category of pick	light is obtained by cursor	
63	(Illuminated)	Floodlit, floodlighting of a structure				0É	Floodlight		
64		Strip light				M	Strip light		
On m	ulticolored charts, P63 and P64 may I	be any appropriate color.				1			
65	(priv)	Private light other than one exhibited occasionally	Priv	FR (priv)	♦ ● Priv maintd	× A	Status of private is obtained by curs		
66	(sync)	Synchronized light							
Supp	plementary National Symbols								
а		Riprap surrounding light	$\mathbf{c}$						
b		Short-Long Flashing			S-L FI				
с		Group-Short Flashing			G-S FI				
d		Fixed and Group Flashing			F Gp Fl				
е		Unmanned light-vessel; light float		<i>F</i>	FLOAT				
f		LANBY, superbuoy as navigational aid		<u></u> д					



### Simplified and Traditional Paper Chart Symbols

ECDIS can be set to display aids to navigation with either traditional paper chart or simplified symbols. The two symbol sets are shown below. Some ECDIS color fill the paper chart buoy shapes, but this is not required by IHO ECDIS portrayal specifications.

#### **Floating Marks**

Paper Chart	Simplified	Simplified Symbol Name				
* 🔺		Cardinal buoy, north				
* 🜩		Cardinal buoy, east				
* 🗸		Cardinal buoy, south				
* 👗		Cardinal buoy, west				
<b>Q</b> ?	⊙?	Default symbol for buoy (used when no defining attributes have been encoded in the ENC)				
* •	•	Isolated danger buoy				
<b>A</b>		Conical lateral buoy, green				
<b>A</b>	<u> </u>	Conical lateral buoy, red				
	<u>·</u>	Can shape lateral buoy, green				
	· · ·	Can shape lateral buoy, red				
ےًـ						
ዄ		Installation buoy and mooring buoy				
பீ						
**	$\overline{\mathbf{\cdot}}$	Safe water buoy				
Q	$\overline{\mathbf{\cdot}}$	Special purpose buoy, spherical or barrel shaped, or default symbol for special purpose buoy				
4	<u> </u>	Special purpose TSS buoy marking the starboard side of the traffic lane				
Ģ		Special purpose TSS buoy marking the port side of the traffic lane				
ፈ រ	<u>/</u>	Special purpose ice buoy or spar or pillar shaped buoy				
		Super-buoy ODAS & LANBY				
5		Light float				
Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z		Light vessel				

#### **Fixed Marks**

Paper Chart	Simplified	Simplified Symbol Name
* 🔺		Cardinal beacon, north
* 🖨	$\Leftrightarrow$	Cardinal beacon, east
* 🔻	$\mathbf{a}$	Cardinal beacon, south
* 👗	$\mathbf{X}$	Cardinal beacon, west
₽?	• ?	Default symbol for a beacon (used when no defining attributes have been encoded in the ENC)
	•	Isolated danger beacon
Ţ	·	Major lateral beacon, red
	·	Major lateral beacon, green
-0-	·	Minor lateral beacon, green
Λ	•	Major safe water beacon
τοτ	•	Minor safe water beacon
8	•	Major special purpose beacon
₩ Å	·	Minor special purpose beacon

* Paper chart symbols display various buoy or beacon shape symbols in conjunction with the topmark. Simplified portrayal only displays the topmark.

** Several different paper chart symbols correspond to this simplified symbol.

#### Day Marks

Paper Chart	Simplified	Simplified Symbol Name			
Ţ	<b>L</b>	Square or rectangular daymark			
$\bigwedge_{\clubsuit}$	$\Diamond$	Triangular daymark, point up			
∑ _	$\bigtriangledown$	Triangular daymark, point down			
Ħ	Ħ	Retro reflector			

No.	INT	Description	NOAA	NGA	Other NGA		ECDIS
Buoys	and Beacons						
IALA Ma	aritime Buoyage System, which include	es Beacons $\rightarrow$ Q 130					
		Default buoy symbol if no other				<b>Q</b> ?	Default symbol for buoy, paper chart
		defining attribution is provided				•?	Default symbol for buoy, simplified
		Default beacon symbol if no oth-				<b>1</b> ?	Default symbol for a beacon, paper chart
		er defining attribution is provided				•?	Default symbol for a beacon, simplified
1	-0-	Position of buoy or beacon		0		with a circle at the both	ition of buoys and beacons from of paper chart symbols. , the position of the aid center of the symbol.
Colors	of Buoys and Beacon Topmarks	3				Supplementary nation	al symbols: p
Abbrevi	iations for Colors $\rightarrow$ P						
2		Green and black (symbols filled black)	👂 G	* _			
3		Single color other than green and black	₿ R	\$ <u>1</u>			
4	A A A A A A A A A A A A A A A A A A A	Multiple colors in horizontal bands, the color sequence is from top to bottom	🕏 F	RG 🛤			
5		Multiple colors in vertical or diagonal stripes, the darker color is given first	\$ RV 	/ @ _/			
6		Retroreflecting material					
Lighte	d Marks		I			Supplementary nationa	al symbols: p
Marks w	with Fog Signals $\rightarrow$ R					Supplementary nationa	al symbols: p
7	FI.G	Lighted marks on standard charts	FIG FIR	FIR FIR			
8	FI.R Q. Iso	Lighted marks on multicolored charts		·			
Note: 0	On standard charts, the light flares of b	uoys and beacons are shown in ma	agenta. On multicolore	d charts, the light flares	are shown in the colors of the app	ropriate light	

### Q Buoys, Beacons

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS		
Topma	arks and Radar Reflectors							
For Ap	plication of Topmarks within the IAL	A System $\rightarrow$ Q 130 F	or other topmarks (spec	cial purpose buoys and b	eacons) → Q			
					Paper chart symbols for topmarks (on the left, below are always displayed above a buoy or beacon shap symbol, as in Q 10 and Q 11. Simplified symbols (on the right, below) for cardinal marks, isolated dangers and safe water consist of only the topmark without the buoy shape symbol. Simplified symbology for marks with any other type of topmark will display only the simplified buoy or beacon shape symbol without a topmark.			
								2 cones point upward
						*	<b>7</b> <b>7</b>	2 cones point downward
	t t t t t t t t t t t t t t t t t t t				\$		2 cones base to base	
					X		2 cones point to point	
		IALA System buoy topmarks				•	•	2 spheres
9	+ <b>F F </b>	(beacon topmarks shown upright)				•	$\mathbf{\bullet}$	Sphere
								Cone point up
					•		Cone point down	
						٥		Cylinder, square, vertical rectangle
						*		X-shape
						/		Flag or other shape
						•		Board, horizontal rectangle
						0		Cube point up
						+		Upright cross over a circle
								T-shape
10	y⊓ No2	Beacon with topmark, color, radar reflector and designation	■ G Ra	"3" a Ref		bn N	• 2 <b>D</b>	Beacon in general with topmark, paper chart

### Buoys, Beacons Q

No.	INT	Description	NOAA	NGA	Other NGA		EC	DIS
11	G No3	Buoy with topmark, color, radar reflector and designation	₿ G N "3"	A No 3		by No	Å	Conical buoy with topmark, paper chart
Note: F	Radar reflectors on floating marks usually	are not charted. ECDIS does not dis	play radar reflectors on t	fixed or floating aids; this	information is obtained by cursor p	ick.		
Buoy	S							
Shap	es of Buoys							
Featur	res Common to Buoys and Beacons $\rightarrow$	Q 1–11						
						Paper Chart	Simplified	
20	A A	Conical buoy, nun buoy, ogival buoy	§n ⊅			A		Conical buoy
21	<i>□</i> . <b>₽</b>	Can buoy or cylindrical buoy	§c 2					Can buoy
22	<u>م</u>	Spherical buoy	SP ନ			Q	$\overline{\mathbf{\cdot}}$	Spherical buoy
23		Pillar buoy; Buoy with no distinctive shape	Ø₽ ⊿			<b>ਪ</b>	/	Pillar buoy
24	l	Spar buoy, spindle buoy	§s ↓			L	<u>-</u>	Spar buoy
25	<u>љ</u> .	Barrel buoy, tun buoy	\$ re			b	$\overline{\mathbf{\cdot}}$	Barrel buoy
26	- <u>-</u>	Superbuoy	4	<u>ل</u> ے				Super-buoy Lanby, super-buoy Super-buoy odas & lanby
Light	Vessels and Minor Light Floats	· · · · · · · · · · · · · · · · · · ·						
30.1	FI.G.3s G G FI.G.3s	Light float on standard charts	<u>*</u>		*	म्ब	-	Light float
30.2	FI.G.3s Name	Light float on multi-colored charts			•			
31	t ∓∓ Fl.10s	Light float not part of IALA System	8			121	~	Light float
32		Light vessel		*	*	T T T		Light vessel, paper chart

### Q Buoys, Beacons

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS	
Moori	ng Buoys	· · ·		- <u>-</u>		1	
Oil or G	Gas Installation Buoy $\rightarrow$ L						
						ےًـ	Mooring buoy, can shape, paper chart
40	க் க் க்	Mooring buoys	<b>.</b>			ዄ	Mooring buoy, barrel shape, paper chart
						<b>_</b>	Istallation buoy and mooring buoy, simplified
41.1	å, Fl.Y.2.5s	Lighted mooring buoy (example) on standard charts	w.	Fl Y 2s		ዄ	Mooring buoy with light
41.2	∰ Fl.Y.2,5s	Lighted mooring buoy (example) on multi-colored charts					flare, barrel shape, paper chart
42	⁷ ₆₀ − 1 − − 2 − − 2 − − 4	Trot, mooring buoys with ground tackle and berth numbers					Trot, mooring buoys with ground tackle and berth numbers
43	<b>Å</b>	Mooring buoy with telephonic communication		$Tel \qquad Tel \\ Tel \\ Tel = telegraphic$		<b>፲</b> ፰-~\$~- ፟፟፟፟፟፟፟፟፟፟-~\$~-	Mooring buoy, can shape, paper chart Mooring buoy, barrel shape, paper chart
				T = telephonic		-~ < ~ -	Installation buoy and mooring buoy, simplified
44		Numerous moorings (example)	Numerous mooring buoys	(5 buoys) Moorings			Small-craft mooring area
45	¢.	Visitors' mooring					Availability of visitor mooring at marina is obtained by cursor pick

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS					
Speci	Special Purpose Buoys										
Note: S	Note: Shapes of buoys are variable. Lateral or Cardinal buoys may be used in some situations.										
				of buoy and other information d by cursor pick							
Purpos	e of buoy may be shown by label.										
50	င္ရို DZ	Firing danger area (Danger Zone) buoy				Å	Conical buoy with topmark, paper chart				
54	<i>ф</i> ́DG	Degaussing Range buoy				$\odot$	Special purpose buoy, spherical or barrel shaped, or default symbol for special purpose buoy, simplified				
58	යා ODAS ධූ ODAS	ODAS buoy (Ocean Data Acquisition System), data collecting buoy	اللہ ODAS	쇼 ODAS			Super-buoy, paper chart Super-buoy odas & lanby, simplified Spherical buoy, paper chart Spherical buoy, simplified				

### Q Buoys, Beacons

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
70	$\hat{\mathbf{Q}}_{\mathbf{v}}^{\mathbf{X}}$ (priv)	Buoy privately maintained (example)	§ F	Priv	ດີ (occas) ດີ (01.04.– Y 31.10.)	Status as private is obtained by cur	
71	${\displaystyle \mathop{\mathbf{G}}_{Y}^{ imes}}$ (Apr–Oct)	Seasonal buoy (example)				Status as per stop dates a	eriodic and period start and re obtained by cursor pick
Beaco	ons					1	
Lighted	Beacons $\rightarrow$ P Feature	es Common to Beacons and Buoys	→ Q1–11				
		Beacon in general,				₽?	Default symbol for a beacon, paper chart
80	_l ⊙ Bn	characteristics unknown or chart scale too small to show	🗆 Bn	★ Bn ⊚ Bn G R		•?	Default symbol for a beacon, simplified
						L.	Beacon in general, paper chart
81	₽. Bŵ	Beacon with color, no distinctive topmark	▲ R ■ G Bn			Beacon color is obtained by cursor pick	
						Beacon colo	or is obtained by cursor pick
						See note at Q 9 for inform ECDIS simplified symbole	nation about topmarks and ogy
						□ ↓	Beacon in general with topmark, paper chart
						·	Major red lateral bea- con, simplified
82		Beacons with colors and topmarks (examples)				, Î	Beacon in general with topmark, paper chart
							Cardinal beacon, north, simplified
						J	Beacon in general with topmark, paper chart
						•	Isolated danger beacon, simplified


### Buoys, Beacons Q

No.	INT Description		NOAA	NGA		Other NGA		ECDIS	
83	4 BR	<b>1</b> 00	Beacon on submerged rock with colors (topmark as appropriate)		₽ BRB			• L	Beacon in general with topmark, paper chart
	п	15			внв			•	Isolated danger beacon, simplified
Minor	Impermanent N	larks Usually	in Drying Areas (Lateral Marks	of Minor Channe	ls)				
Minor F	$Pile \to F$								
90	-	ļ	Stake, pole	+ ∘ Stake • Sta + ∘ Pole • Po		4		T	Minor, stake or pole beacon, paper chart
91	Port Hand	Starboard Hand	Perch, withy		Р			T	Minor, stake or pole beacon, paper chart
51	Y	1			R R	-		•	Minor red lateral bea- con, simplified
92	⊈ †	± †	Withy					•	Minor green lateral beacon, simplified
Minor	Marks, Usually	on Land				I	·		
Landma	arks $\rightarrow$ E								
100	٤	\$	Cairn	o Cairn				\$	Conspicuous cairn
									Square or rectangular day mark, paper chart
								<b>L</b>	Square or rectangular day mark, simplified
101		Mk	Colored or white mark					$\bigwedge_{-\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!\!$	Triangular day mark, point up, paper chart
101		WIR.						4	Triangular day mark, point up, simplified
								$\sum$	Triangular day mark, point down, paper chart
								$\mathbf{\nabla}$	Triangular day mark, point down, simplified


### Q Buoys, Beacons

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS					
102.1	<b>Ì Ì Ì Ì Ì</b> ₩ ₽₩ †	Colored topmark (color known or unknown) with function of a beacon										
102.2	₽₽_ ₽₩ ₽₩ †	Painted boards with function of leading beacons										
Beaco	Beacon Towers											
110		Beacon towers without and with topmarks and colors (examples)	□ ^{RW} Bn			ム 点 点 点	Beacon tower, paper chart Beacon tower with topmarks, paper chart					
						·	Major red lateral bea- con, simplified					
							Major green lateral beacon, simplified					
111	₿	Lattice beacon				A	Lattice beacon, paper chart					
Specia	al Purpose Beacons		1									
Leading	g Lines, Clearing Lines $\rightarrow$ M											
Note: T	opmarks and colors shown where scal	e permits.										
120	łł	Leading beacons		Bns in Lline 270°		▶ 270 deg	Leading beacons					
121	.JJJJJJJJJJJJJJJJJJJJJJJJJJJJJ.JJ.JJ.JJ.JJJJJJJJJJJJJ	Beacons marking a clearing line		Bns in 		270 deg	Beacons marking a clearing line or transit					
122	Measured Distance 1852m 090°-270°	Beacons marking measured distance with quoted bearings	O MARKERS			<b>J J</b> <u>270 deg</u>	Beacons marking measured distance					
123	<b>\$</b> ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Cable landing beacon (example)		₽~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		<b>ý</b> - ~ < ~ -	Cable landing beacon (example)					


### Buoys, Beacons Q



### Q Buoys, Beacons



### Buoys, Beacons Q



### Q Buoys, Beacons

No.	IN	іт	Description	NOAA	NGA	Other NGA	ECDIS	
124	A Ref	_L Ref	Refuge beacon				Purpose as refuge or firing danger are beacon is obtained by cursor pick	
126	Ē	2	Notice board				<b>一</b>	Notice board
130.4	Isolated Danger	Marks stationed ov	er dangers with navigable water arour	nd them. Body: black	with red horizontal band(s	s) Topmark: two black spheres	Light: white	
	J BRB	₿Ř₿	Unlit Marks					Pillar buoy with 2 spheres topmark
	A BRB	∫ BRB FI(2)	Lighted Marks on standard charts	BR			i	Spar buoy with 2 spheres topmark
	BRB -	<b>FI (2)</b>	Unlit Marks on multicolored charts				*	Isolated danger buoy, simplified
130.5	Safe Water Mark	<b>s</b> , including mid-cha	annel and landfall marks. Body: re	ed and white vertical stripe	es Topmark (if any): re	ed sphere Light: white		
			Unlit marks				Q	Spherical buoy, paper chart
		Iso or Oc or LFI.10s or RW Mo (A)	Lighted Marks on standard charts	₿ _{RW}			Å	Pillar buoy with sphere topmark
	Rw Rw	OC or ↓ OC or ↓ LFI.10s or Fw Mo (A)	Lighted Marks on multicolored charts				į	Spar buoy with sphere topmark
							<b>e</b>	Safe water buoy, simplified
130.6	Special Marks no	ot primarily to assist	navigation but to indicate special feat	ures. Body (shape op	tional): yellow* Topm	ark (if any): yellow X or upright cros	s Light: yellow, rhyth	nm optional*
		à Î	Unlit Marks				Q	Spherical buoy, paper chart
	F - L	FIY	Lighted Marks on standard charts	Ş Y			Ę	Can buoy
	Pr Pr		Lighted Marks on multicolored charts				A	Conical buoy
							ž	Spar buoy with x-shape topmark
							Q	Special purpose buoy, simplified
	* In special cases	, yellow may be use	d in conjunction with another color					

No.	INT	Description	NOAA NGA	Other NGA	ECDIS
130.7	New Danger Marks. Body (shape	e optional): yellow and blue Topm	ark: yellow cross		
		Unlit marks			Pillar buoy with upright cross topmark
	Buy Buy	Lighted Marks on standard charts			
		Lighted Marks on multicolored charts			Spar buoy with upright cross topmark
Suppl	ementary National Symbols				
а		Bell buoy	8 bell 🖉 bell		
b		Gong buoy	8 GONG & GONG	3	
с		Whistle buoy	🖇 whis 🖉 whis	3	
d		Fairway buoy (red and white vertical stripe)	[®] RW		
е		Mid-channel buoy (red and white vertical stripe)	₿ _{RW}		
f		Starboard-hand buoy (entering from seaward - US waters)	₿ "2"		
g		Port-hand buoy (entering from seaward - US waters)	§ ^G _{"1} " § "1"		
h		Bifurcation/Junction buoys	🕏 RG 🕏 GR		
h		Isolated danger, Wreck or Obstruction buoy	BR		
i		Fish trap (area) buoy	Ø Y		
j		Anchorage buoy (marks limits)	8 Y		
		Triangular shaped beacons	$\mathbf{A} R \qquad \triangle \underset{Bn}{RG}$		
I		Square shaped beacons	■G □GR □W □B Bn Bn Bn		
		Beacon, color unknown	🗆 Bn		
о		Lighted beacon	! /	Bn D	
q		Security barrier	Security barrier		
r		Scientific mooring buoy	\$		
S		Float (unlighted)	Ş		
t		White and blue buoy	И		

### R Fog Signals

No.	INT	Description	NOAA	NGA	Other NGA	E	ECDIS	
Gene	eral							
Fog D	etector Light $\rightarrow$ P Fo	$\log$ Light $\rightarrow$ P						
1	H [®] H ^I (III) AIS	Position of fog signal, type of fog signal not stated	Fog Sig M	M			Position of a conspicuous point feature with fog signal Lighted pillar buoy, paper chart with fog signal Lighted super-buoy, paper chart with fog signal	
2	(man)	Manually activated						
Туре	s of Fog Signals, with Abbrevi	ations				Supplementary natio	nal symbol: a	
10	Explos	Explosive	G	UN				
11	Dia	Diaphone	D	IA				
12	Siren	Siren	SI	REN		Type of fo	g signal and its	
13	Horn	Horn (nautophone, reed, tyfon)	H	ORN		Type of fog signal and its characteristics are obtained by curso pick		
14	Bell	Bell	BI	ELL				
15	Whis	Whistle	W	HISTLE				
16	Gong	Gong	G	ONG				
Exam	nples of Fog Signal Descriptio	ns						
Note:	The fog signal symbol will usually be	e omitted when a description of the sig	gnal is given.					
20	FI.3s70m29M Siren Mo(N)60s	Siren at a lighthouse, giving a long blast followed by a short one (N), repeated every 60 seconds	FI 3s 70m 29M SIREN Mo(N) 60s	FI 3s 70m 29M SIREN		le l	Light with fog signal	
21	Двен	Wave-actuated bell buoy	🕏 BELL	A BELL		A	Pillar buoy, paper chart with fog signal	
22	∫ Q(6)+LFI.15s YB Horn(1)15sWhis	Light buoy, with horn giving a single blast every 15 seconds, in conjunction with a wave-actuated whistle	Q(6)+LFI 15s HORN(1) 15s WHIS	∬ Q(6)+LFI 15s YB HORN WHIS		Paper Chart Simplifie	Lighted pillar buoy, paper chart with fog signal	
Supp	lementary National Symbol	1	1	I		I I	1	
а	,, <del>-</del> -,	Morse Code fog signal		Мо				
u			/					

## Radar, Radio, Satellite Navigation Systems $\,\,$ S

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS					
Radar											
Radar	Structures Forming Landmarks $\rightarrow$ E	Radar Surveillance	Systems $\rightarrow$ M								
1	© Ra	Coast radar station, providing range and bearing service on request		Ra		$\bigcirc$	Radio station				
2	• Ramark	Ramark, radar beacon transmitting continuously		Ramark							
3.1	* (a) Racon (Z) (3 cm)	Radar transponder beacon, with morse identification, responding within the 3 cm (X) band	t (C								
3.2	† (************************************	Radar transponder beacon, with morse identification, responding within the 10 cm (S) band									
3.3	• Racon(Z)	Radar transponder beacon, with morse identification			(3 & 10 cm)						
2.4	A Racon (Z)	Radar transponder beacon with sector of obscured reception				0	Radar transponder beacon				
3.4	Racon(Z)	Radar transponder beacon with sector of reception									
0.5	$\textcircled{\textbf{e}}_{\text{rescons}} = \overbrace{-\textbf{e}}^{\text{Racons}} - \overbrace{-\textbf{e}}^{\text{Racons}} \stackrel{\neq}{=} 270^{\circ}$	Leading radar transponder beacons (‡: objects in line)									
3.5	$\begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \\ \end{array} \end{array} \\ \hline \end{array} \\ \begin{array}{c} \begin{array}{c} \\ \end{array} \\ \hline \end{array} \\ \begin{array}{c} \begin{array}{c} \\ \end{array} \\ \hline \end{array} \\ \begin{array}{c} \begin{array}{c} \\ \end{array} \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \end{array} \\ \\ \end{array} \\ \\ \end{array} \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \end{array} \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \end{array} \\ \\ \\ \end{array} \\ \\ \\ \end{array} \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \end{array} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	Leading radar transponder beacons coincident with leading lights									
3.6	Racon Racon	Radar transponder beacons on floating marks	RACON (-) R "2" FI R 4s	Racon		Paper Chart Simplified	Radar transponder on floating mark				
4	يعنر		Sumbal indiantian								
Radar r	eflectors are not charted on buoys in r	_ ×	Symbol indicating this object is radar conspicuous								
5	ىىد	Radar conspicuous feature					conspicuous				

### S Radar, Radio, Satellite Navigation Systems

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS							
Radi	כ												
Radio	Radio Structures Forming Landmarks $\rightarrow$ E       Radio Reporting (Calling-in or Way) points $\rightarrow$ M												
10	†	Circular (non-directional) marine or aeromarine radiobeacon	t 💮 RC	† 💮 R Bn									
11	t RD 269.5°	Directional radiobeacon with bearing line	† ()	RD 270°		$\bigcirc$	Radio station						
11	t RD 270°	Directional radiobeacon coincident with leading lights				$\bigcirc$							
12	t o rw	Rotating pattern radiobeacon	t C	RW			Additional information regarding radio,						
13	t O Consol	Consol beacon	t CONSOL Bn 190 kHz MMF ==	t o CONSOL			such as category of radio station, signal frequency, communication channel, call sign, estimated signal range, periodicity and status may be						
14	e RG	Radio direction-finding station	0	RDF			The presence of an AIS transmitted signal intended for use as an aid to navigation associated with a physical aid, including the AIS MMSI Number, can be obtained by cursor pick on the						
15	t • R	Coast radio station providing QTG service	o R Sta	† 💿 R									
16	† ero RC	Aeronautical radiobeacon	t 💿 A	ERO R Bn			physical aid.						
17.1	o AIS	Automatic Identification System transmitter											
17.2	AIS AIS	Automatic Identification System transmitter on floating marks (examples)											
18.1	•         V-AIS	Virtual AIS (with unknown IALA- defined function)											
	V-AIS					V-AIS	North cardinal virtual aid						
18.2	V-AIS V-AIS	Virtual AIS (with known IALA-				V-AIS	East cardinal virtual aid						
	V-AIS	defined function)				V-AIS	South cardinal virtual aid						
						V-AIS	West cardinal virtual aid						

## Radar, Radio, Satellite Navigation Systems $\,\,$ S

No.	INT	Description	NOAA	NGA	Other NGA	ECDIS		
18.3	V-AIS	Virtual AIS with lateral mark function				V-AIS	Port Lateral (IALA B) virtual aid	
	Image: Second	Tunction				V-AIS	Starboard Lateral (IALA B) virtual aid	
18.4	V-AIS	Virtual AIS with isolated danger mark function				V-AIS	Isolated Danger virtual aid	
18.5	8 V-AIS	Virtual AIS with safe water mark function				V-AIS	Safe Water virtual aid	
18.6	V-AIS	Virtual AIS with special purpose mark function				V-AIS	Special Purpose virtual aid	
18.7	V-AIS	Virtual AIS with new danger mark function				V-AIS	Emergency Wreck virtual aid	
Satel	lite Navigation Systems							
50	WGS WGS72 WGS84	World Geodetic System, 1972 or 1984						
50	50 Note: A note may be shown to indicate the shifts of latitude and longitude, to one, two or three decimal places of a minute, depending on the chart scale, which should be made to satellite-derived positions (which are referred to WGS 84) to relate them to the chart.							
51	o DGPS	Station providing DGPS corrections				DGPS	DGPS reference station	

23

• SS (Port Control)

Port control signal station

Service	es						
IN	т	Description	NOAA	NGA	Other NGA	EC	DIS
age							
٢		Boarding place, position of a pilot cruising vessel	Pilots			٢	Pilot boarding place
() Na	me	Boarding place, position of a pilot cruising vessel, with name (e.g. District, Port)		Name			
No	te	Boarding place, position of a pilot cruising vessel, with note (e.g. Tanker, Disembarkation)		(see note)			Pilot boarding area
🜔 н		Pilots transferred by helicopter					
† Pilot	Lookout	Pilot office with pilot lookout, Pilot lookout station					
Pilots	3	Pilot office	○ PIL STA	Pilots			
		Port with pilotage service (boarding place not shown)					
t Guard, Rescue	9			·			
■CG of	са Дса	Coast Guard station	•	- CG O R TR CG WALLIS SANDS		CG	Coast guard station
■CG✦ ⊙C	s✦ ֲcg✦	Coast Guard station with Res- cue station					Coast guard station Rescue station
-	+	Rescue station, Lifeboat station, Rocket station		- LSS			
ಡೆ✦	+	Lifeboat lying at a mooring					Rescue station
Ref	Ref	Refuge for shipwrecked mar- iners					
al Stations				t		1	
⊙ SS		Signal station in general	$\overline{\bigcirc}$	) ss	↔ Sig Sta		
SS (IN	T)	Signal station, showing international port traffic signals				SS	Signal station
● SS (Tr	affic)	Traffic signal station, Port entry and departure signals					
	IN age () () () () () () () () () ()	Image: Second system         Image: Second system <td>INT       Description         age       Boarding place, position of a pilot cruising vessel         Image       Boarding place, position of a pilot cruising vessel, with name (e.g. District, Port)         Image       Boarding place, position of a pilot cruising vessel, with name (e.g. Tanker, Disembarkation)         Image       Boarding place, position of a pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Boarding place, position of a pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Boarding place, position of a pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Boarding place, position of a pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Pilot office         Image       Pilot office         Port name       Pilot office         Port name       Port with pilotage service (boarding place not shown)         Image       Coast Guard station         Image       Image       Coast Guard station         Image       Image       Coast Guard station, Lifeboat station, Rocket station         Image       Image       Image       Image         Image       Image       Ref       Ref       Ref         Ima</td> <td>INT       Description       NOAA         age       Boarding place, position of a plot cruising vessel          <ul> <li>Plots</li> <li>Plots</li> </ul>            Image         Boarding place, position of a plot cruising vessel, with name (e.g. District, Port)              <li>Plots</li>             Image         Boarding place, position of a plot cruising vessel, with note (e.g. Tanker, Disembarkation)          <ul> <li>Image: Plot cruising vessel, with note (e.g. Tanker, Disembarkation)</li> <li>Image: Plot Lookout</li> <li>Plot office with pilot lookout, Plot lookout, Plot lookout station</li> </ul>      Plot cruising vessel, with note (e.g. Tanker, Disembarkation)           Image: Plot Lookout         Plot office with pilot lookout, Plot floce         Image: Plot lookout           Image: Plot Lookout         Plot office         Image: Plot Plut STA           Port name         Port with pilotage service (boarding place not shown)         Image: Plot Station           Image: Plot Plots         Port with pilot get a mooring         Image: Plot Plut Station           Image: Plot Plot Plot Plot Plot Plot Plot Plot</td> <td>INT       Description       NOAA       NGA         age       Boarding place, position of a plot cruising vessel, with name (e.g. Ostich, Port)          <ul> <li>Plots</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Plot cruising vessel, with name (e.g. Ostich, Port)</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Plot cruising vessel, with name (e.g. Tanker, Disembarkation)</li> <li>Name</li> <li>Name</li> <li>Plot office with plot tookout, plot tookout, plot tookout station</li> <li>Plot office</li> <li>Plot with plotage service (boarding place not shown)<td>INT       Description       NOAA       NGA       Other NGA         age       Boarding place, position of a plot orusing vessel       Image: Plot Lossed       Image: Plot Cost         Image: Plot orusing vessel, with name (c.g. Datif, Port)       Image: Plot Cost       Image: Plot Cost       Image: Plot Cost         Image: Plot orusing vessel, with name (c.g. Tanker, Disembankation)       Image: Plot Cost       Image: Plot Cost       Image: Plot Cost         Image: Plot Lossed       Plot office with plot lockout, Plot office (Cost office with plot plot of shown)       Image: Plot Lossed       Image: Plot office with plot lockout, Plot office with plot lockout, Plot office (Cost of shown)       Image: Plot Lossed       Image: Plot Lossed       Image: Plot office with plot plot plot lockout, Plot plot plot plot plot plot plot plot p</td><td>INT       Description       NOAA       NGA       Other NGA       EC         3ge</td></li></ul></td>	INT       Description         age       Boarding place, position of a pilot cruising vessel         Image       Boarding place, position of a pilot cruising vessel, with name (e.g. District, Port)         Image       Boarding place, position of a pilot cruising vessel, with name (e.g. Tanker, Disembarkation)         Image       Boarding place, position of a pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Boarding place, position of a pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Boarding place, position of a pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Boarding place, position of a pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Pilot cruising vessel, with note (e.g. Tanker, Disembarkation)         Image       Pilot office         Image       Pilot office         Port name       Pilot office         Port name       Port with pilotage service (boarding place not shown)         Image       Coast Guard station         Image       Image       Coast Guard station         Image       Image       Coast Guard station, Lifeboat station, Rocket station         Image       Image       Image       Image         Image       Image       Ref       Ref       Ref         Ima	INT       Description       NOAA         age       Boarding place, position of a plot cruising vessel <ul> <li>Plots</li> <li>Plots</li> </ul> Image         Boarding place, position of a plot cruising vessel, with name (e.g. District, Port) <li>Plots</li> Image         Boarding place, position of a plot cruising vessel, with note (e.g. Tanker, Disembarkation) <ul> <li>Image: Plot cruising vessel, with note (e.g. Tanker, Disembarkation)</li> <li>Image: Plot Lookout</li> <li>Plot office with pilot lookout, Plot lookout, Plot lookout station</li> </ul> Plot cruising vessel, with note (e.g. Tanker, Disembarkation)           Image: Plot Lookout         Plot office with pilot lookout, Plot floce         Image: Plot lookout           Image: Plot Lookout         Plot office         Image: Plot Plut STA           Port name         Port with pilotage service (boarding place not shown)         Image: Plot Station           Image: Plot Plots         Port with pilot get a mooring         Image: Plot Plut Station           Image: Plot Plot Plot Plot Plot Plot Plot Plot	INT       Description       NOAA       NGA         age       Boarding place, position of a plot cruising vessel, with name (e.g. Ostich, Port) <ul> <li>Plots</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Plot cruising vessel, with name (e.g. Ostich, Port)</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Name</li> <li>Plot cruising vessel, with name (e.g. Tanker, Disembarkation)</li> <li>Name</li> <li>Name</li> <li>Plot office with plot tookout, plot tookout, plot tookout station</li> <li>Plot office</li> <li>Plot with plotage service (boarding place not shown)<td>INT       Description       NOAA       NGA       Other NGA         age       Boarding place, position of a plot orusing vessel       Image: Plot Lossed       Image: Plot Cost         Image: Plot orusing vessel, with name (c.g. Datif, Port)       Image: Plot Cost       Image: Plot Cost       Image: Plot Cost         Image: Plot orusing vessel, with name (c.g. Tanker, Disembankation)       Image: Plot Cost       Image: Plot Cost       Image: Plot Cost         Image: Plot Lossed       Plot office with plot lockout, Plot office (Cost office with plot plot of shown)       Image: Plot Lossed       Image: Plot office with plot lockout, Plot office with plot lockout, Plot office (Cost of shown)       Image: Plot Lossed       Image: Plot Lossed       Image: Plot office with plot plot plot lockout, Plot plot plot plot plot plot plot plot p</td><td>INT       Description       NOAA       NGA       Other NGA       EC         3ge</td></li></ul>	INT       Description       NOAA       NGA       Other NGA         age       Boarding place, position of a plot orusing vessel       Image: Plot Lossed       Image: Plot Cost         Image: Plot orusing vessel, with name (c.g. Datif, Port)       Image: Plot Cost       Image: Plot Cost       Image: Plot Cost         Image: Plot orusing vessel, with name (c.g. Tanker, Disembankation)       Image: Plot Cost       Image: Plot Cost       Image: Plot Cost         Image: Plot Lossed       Plot office with plot lockout, Plot office (Cost office with plot plot of shown)       Image: Plot Lossed       Image: Plot office with plot lockout, Plot office with plot lockout, Plot office (Cost of shown)       Image: Plot Lossed       Image: Plot Lossed       Image: Plot office with plot plot plot lockout, Plot plot plot plot plot plot plot plot p	INT       Description       NOAA       NGA       Other NGA       EC         3ge

o HECP

No.	INT	Description	NOAA	NGA	Other NGA	EC	DIS
24	<ul> <li>SS (Lock)</li> </ul>	Lock signal station					
25.1	● SS (Bridge)	Bridge passage signal station					
25.2	t F Traffic-Sig	Bridge lights including traffic signals					
28	<ul> <li>SS (Storm)</li> </ul>	Storm signal station	S Się	g Sta			
29	SS (Weather)	Weather signal station, Wind signal station, National Weather Service (NWS) signal station	• NWS SIG STA				
30	SS (Ice)	Ice signal station				SS	Signal station
31	SS (Time)	Time signal station				33	Signal station
32.1	ŧ	Tide scale or gauge		O Tide Gauge			
32.2	○ Tide Gauge	Automatically recording tide gauge					
33	◦ SS (Tide)	Tide signal station					
34	<ul> <li>SS (Stream)</li> </ul>	Tidal stream signal station					
35	<ul> <li>SS (Danger)</li> </ul>	Danger signal station					
36	<ul> <li>SS (Firing)</li> </ul>	Firing practice signal station					
Supp	lementary National Symbols		•			<u>.</u>	
а		Bell (on land)	O BELL				
b		Marine police station	O MARINE POLICE				
с		Fireboat station	O FIREBOAT STATION				
d		Notice board		₹			
е		Lookout station; Watch tower	(	O LOOK TR			
f		Semaphore	s	em			
g		Park Ranger station		9			

## U Small Craft (Leisure) Facilities

No.		INT	Desc	cription			NOAA			NG	A			Ot	er NG	Α		ECDI	S	
Sma	Small Craft (Leisure) Facilities																			
Traffic	Traffic Features, Bridges $\rightarrow$ DPublic Buildings, Cranes $\rightarrow$ FPilots, Coast Guard, Rescue, Signal Stations $\rightarrow$ T																			
	Marina facilities																			
а	THE LOC THE TAB	TIDES DEPTH	URS EARLIER E FACILITIES ARE SHO DI AS FACILITIES ANA	80 20 80 15 80 80 15 80 80 15 35 35 00 10 00 40 00 40 00 LABLE FROM	K A HUMAN HANNA HA	HM HM M ARGE PL	JRPLE NUMBERS. RAL OR DREDGE	M M M M M	HER STRONG	FC FL FLC FLC FC FC	A CLARING T P T P T SL P TSL P TSL P TSL P	WD C	: WI : WI	GH E GH E GH E	T G DG T G T G T G G					

Α		
abt	About	Di
Accom	Accommodation vessel	L 17
AERO, <b>Aero</b>	Aeronautical light	P 60-61.1
Aero R Bn	Aeronautical radiobeacon	S 16
Aero RC	Aeronautical radiobeacon	S 16
AIS	Automatic Identification System	S 17.1-17.2
AI	Alternating	P 10.11
ALC	Articulated Load Column	L 12
Am	Amber	P 11.8
anc	Ancient	
ANCH, Anch	Anchorage	N 20
ANT, Ant	Antenna	E 31
approx	Approximate	
Apprs	Approaches	
Apr	April	
Apt	Apartment	Es
Arch	Archipelago	
ASL	Archipelagic Sea Lane	M 17
ATBA	Area To Be Avoided	M 29.1
Aug	August	
auth	Authorized	K 46.2
Ave	Avenue	
В		
В	Bay, bayou	
В	Black	Q 2
Bdy Mon	Boundary mark (monument)	B 24
Bk	Bank	
bk	Black	J as
bk	Broken	J 33
Bkw	Breakwater	F 4.1
bl	Black	J as
BM	Bench Mark	B 23
Bn, Bns	Beacon(s)	M 2, P 4-5, Q 80-81
BnTr, BnTrs	Beacon tower(s)	P 3, Q 110
Во	Boulder(s)	J 9.2
Bol	Bollard	

Br	Breakers	K 17
br	Brown	J az
brg	Bearing	B 62
brk	Broken	J 33
Bu	Blue	P 11.4
С		
С	Can, cylindrical	Q 21
С	Саре	
С	Cove	
c	Coarse	J 32
Са, <b>са</b>	Calcareous	J 38
CALM	Catenary Anchor Leg Mooring	L 16
Сар	Capitol	Et
Cas	Castle	E 34.2
Cb	Cobbles	J 8
cbl	Cable	B 46
cd	Candela	B 54
Cem	Cemetery	E 19
CG	Coast Guard station	T 10
Ch	Chocolate	J ba
Ch	Church	E 10.1
Chan	Channel	
Chem	Chemical	L 40.1-40.2
CHY, Chy, Chys	Chimney(s)	E 22
Cir	Cirripedia	J ae
Ck	Chalk	J f
CL	Clearance	D 20–21, 26, 28
CI	Clay	J 3
cm	Centimeter(s)	B 43
Cn	Cinders	Jp
Со	Company	Eu
Co	Coralline Algae	J 10, K 16
Co Hd	Coral Head	Ji
Co rf	Coral reef	
COLREGS	International Regulations for Preventing Collisions at Sea	Na
Consol	Consol Beacon	S 13
constr	Construction	F 32

Corp	Corporation	Ev
COV	Covers	L 21.2
cps	Cycles per second	Вj
Cr	Creek	
CRD	Columbia River Datum	Нj
crs	Coarse	J 32
c/s	Cycles per second	Вj
Cswy	Causeway	F 3
Ct Ho	Courthouse	Еo
Cup	Cupola	E 10.4
Cus Ho	Customs house	F 61
Су	Clay	J 3
D		
D	Destroyed	
dec	Decayed	J an
Dec	December	
Deg	Degree(s)	Bn
Destr	Destroyed	
dev	Deviation	B 67
DF	Direction Finder	
DG	Degaussing Range	N 25, Q 54
DGPS	Differential Global Positioning System	S 51
Di	Diatoms	J aa
DIA, <b>Dia</b>	Diaphone	R 11
Dir	Direction light	P 30-31
Discol	Discolored	Ke
dist	Distant	
dk	Dark	J bd
dm	Decimeter(s)	B 42
Dn, Dns	Dolphin(s)	F 20
Dol	Dolphin(s)	F 20
DW	Deep Water Route	M 27.1, N 12.4
DZ	Danger Zone	Q 50
E		
E	East	B 10
ED	Existence Doubtful	I 1
EEZ	Exclusive Economic Zone	N 47

Entr	Entrance	
ESSA	Environmentally Sensitive Sea Area	N 22
Est	Estuary	
exper	Experimental	
Explos	Explosive	R 10
Exting, exting	Extinguished	P 55
F		
f	Fine	J 30
F FI	Fixed and flashing	P 10.10
F Gp Fl	Fixed and Group Flashing	Ρd
Facty	Factory	Ed
FAD	Fish Aggregating Device	
Fd	Fjord	
FISH	Fishing	N 21
FI	Flashing	P 10.4
fl	Flood	Нq
Fla	Flare stack	L 11
fly	Flinty	J ao
fm, fms	Fathom(s)	B 48
fne	Fine	J 30
Fog Det Lt	Fog detector light	P 62
Fog Sig	Fog Signal	R 1
FP	Flagpole	E 27
FPSO	Floating Production, Storage and Offloading Vessel	L 17
Fr	Foraminifera	Jу
Fs, <b>FS</b>	Flagstaff	E 27
Fsh stks	Fishing stakes	K 44.1
FT, <b>ft</b>	Foot, Feet	B 47, D 20
Fu	Fucus	J af
G		
G	Gravel	J 6
G	Green	P 11.3, Q 2
G	Gulf	
GAB, Gab	Gable	Ei
GCLWD	Gulf Coast Low Water Datum	Hk
GI	Globigerina	Jz

glac	Glacial	J ap
gn	Green	J av
Govt Ho	Government House	Em
Gp Fl	Group flashing	P 10.4
Gp Oc	Group occulting	P 10.2
GPS	Global Positioning System	
Grd	Ground	Ja
Grs	Grass	Jv
grt	Gross Register Tonnage	
GT	Gross Tonnage	
gty	Gritty	J am
gy	Gray	J bb
н		
н	Helicopter	T 1.4
h	Hard	J 39
h	Hour	B 49
HAT	Highest Astronomical Tide	H 3
Hbr Mr	Harbormaster	F 60
HHW	Higher High Water	Hb
Hk	Hulk	F 34, K 20–21
Но	House	
hor	Horizontally disposed	P 15
Hor CL	Horizontal clearance	D 21
Hosp	Hospital	E g, F 62.2
hr	Hour	B 49
hrd	Hard	J 39
ht	Height	Нр
HW	High Water	На
HWF&C	High Water Full & Change	Hh
Hz	Hertz	Вg
I		
IALA	International Association of Lighthouse Authorities*	Q 130
IHO	International Hydrographic Organization	
illum	Illuminated	P 63
IMO	International Maritime Organization	

In	Inlet	
in, ins	Inch(es)	Вс
Inst	Institute	En
INT	International	A 2, T 2 ⁻
Intens	Intensified	P 46
IQ	Interrupted quick	P 10.6
ISLW	Indian Spring Low Water	Нg
lso	Isophase	P 10.3
ITZ	Inshore Traffic Zone	M 25.1
IUQ	Interrupted ultra quick	P 10.8
IVQ	Interrupted very quick	P 10.7
J		
Jan	January	
Jul	July	
Jun	June	
к		
к	Kelp	Ju
kc	Kilocycle	Βk
kHz	Kilohertz	Βh
km	Kilometer(s)	B 40
kn	Knot(s)	B 52
L		
L	Lake, loch, lough	
L FI	Long-flashing	P 10.5
La	Lava	JI
Lag	Lagoon	
LANBY	Large Automatic Navigational Buoy	Pf
LASH	Lighter Aboard Ship	
LAT	Lowest Astronomical Tide	H 2
Lat	Latitude	B 1
Ldg	Landing	F 17
Ldg	Leading Lights	P 20.3
Le	Ledge	
LLW	Lower Low Water	Нe
Lndg	Landing for boats	F 17
LNG	Liquified Natural Gas	

*Now known as the International Association of Marine Aids to Navigation and Lighthouse Authorities. The organization, formerly called the International Association of Lighthouse Authorities/Association Internationale de Signalisation Maritime (IALA/AISM), continues to use IALA as an abbreviation for its full name.

LoLo	Load-on, Load-off	
Long	Longitude	B 2
LPG	Liquified Petroleum Gas	
Lrg	Large	Ja
LS S	Life saving station	T 12
lt	Light	J bc
Lt Ho	Light house	P1
Lt, Lt(s)	Light(s)	P 1
Ltd	Limited	Er
LW	Low Water	Нс
LWD	Low Water Datum	Ηd
LWF&C	Low Water Full and Change	Hi
М		
Μ	Mud, muddy	J 2
Μ	Nautical mile(s)	B 45
m	Medium (in relation to sand)	J 31
m	Meter(s)	B 41
m	Minute(s) of time	B 50
Ма	Mattes	J ag
mag	Magnetic	B 61
Magz	Magazine	EI
Maintd	Maintained	P 65
man	Manually activated	P 56, R 2
Mar	March	
Мс	Megacycles	BI
Mds	Madrepores	Jj
MHHW	Mean Higher High Water	H 13
MHLW	Mean Higher Low Water	H 14
MHW	Mean High Water	H 5
MHWN	Mean High Water Neaps	H 11
MHWS	Mean High Water Springs	H9
Mi	Nautical mile(s)	B 45
min	Minimum	K 46.2
min	Minute(s) of time	B 50
Mk	Mark	Q 101
MI	Marl	Jc
MLHW	Mean Lower High Water	H 15
MLLW	Mean Lower Low Water	H 12

MLW	Mean Low Water	H 4
MLWN	Mean Low Water Neaps	H 10
MLWS	Mean Low Water Springs	H 8
mm	Millimeter(s)	B 44
Mn	Manganese	Jq
Мо	Morse Code	P 10.9, R 20
MON, Mon	Monument	E 24
MR	Marine Reserve	N 22
MRCC	Maritime Rescue and Coordination Center	
Ms	Mussels	Js
MSL	Mean Sea Level	H 6
Mt	Mountain, Mount	
Mth	Mouth	
MTL	Mean Tide Level	H 1
Ν		
Ν	North	В9
Ν	Nun	Q 20
NE	Northeast	B 13
NGA	National Geospatial-Intelligence Agency	
NM	Nautical miles(s)	B 45
NMi	Nautical mile(s)	B 45
No	Number	N 12.2
NOAA	National Oceanic and Atmospheric Administration	
NOS	National Ocean Service	
Nov	November	
Np	Neap tide	H 17
NT	Net Tonnage	
NTM	Notice to Mariners	
NW	Northwest	B 15
NWS SIG STA	National Weather Service signal station	T 29
0		
Obs Spot	Observation spot	B 21
OBSC, Obscd	Obscured	P 43
Obstn	Obstruction	K41
Oc	Occulting	P 10.2

Occas	Occasional	P 50
Oct	October	
ODAS	Ocean Data Acquisition System	Q 58
Or	Orange	P 11.7
OVHD	Overhead	D 28
Oys	Oysters	Jr
Р		
Р	Pebbles	J 7
Ρ	Pillar	Q 23
(P)	Preliminary (NTM)	
PA	Position approximate	B 7
Pass	Passage, Pass	
Pav	Pavilion	Ер
PD	Position doubtful	B 8
Pk	Peak	
PLT STA	Pilot station	Т3
Pm	Pumice	Jm
PO	Post office	F 63
Po	Polyzoa	J ad
pos, posn	Position	
Post Off	Post office	F 63
Priv, <b>priv</b>	Private	P 65, Q 70
Prod well	Production well	L 20
PROHIB	Prohibited	N 2.2
PSSA	Particularly Sensitive Sea Area	N 22
Pt	Pteropods	J ac
Pyl	Pylon	D 26
Q		
Q	Quick	P 10.6
QTG	Service producing DF signals	S 15
Quar	Quarantine	Fe
Qz	Quartz	Jg
R		
R	Coast radio station providing QTC service	S 15
R	Radio Station	S 15
R	Red	P 11.2
R, r	Rock, Rocky	J 9.1, K b

R Bn	Circular radiobeacon	S 10
R Lts	Air obstruction lights	P 61.2
R Mast	Radio mast	E 28
R Sta	Radio Station	S 15
R Tower	Radio tower	E 29
R TR, R Tr	Radio tower	E 29
Ra	Radar	M 31-32, S 1
Ra	Radar reference line	M 32.1
Ra (conspic)	Radar conspicuous point	S 5
Ra Ref	Radar reflector	S 4
Racon	Radar transponder beacon	S 3
Radar Sc	Radar scanner	E 30.3
Radar Tr, RADAR TR	Radar tower	E 30.2
Ramark	Radar marker beacon	S 2
RC	Circular radiobeacon	S 10
RD	Directional radiobeacon	S 11
Rd	Radiolaria	J ab
Rd	Road, roadstead	
rd	Red	J ay
RDF	Radio direction finding station	S 14
Ref	Refuge	Q 124
Rep	Reported	13
Rf	Reef	
RG	Radio direction finding station	S 14
Rk	Rocks	J 9.1, K b
Rky	Rocky	J 9.1
RoRo	Roll-on, Roll-off Ferry (RoRo Terminal)	F 50
rt	Rotten	J aj
Ru, (ru)	Ruin, ruined	D 8, E 25.2, F 33
RW	Rotating-pattern radiobeacon	S 12
S		
S	Sand	J 1
S	South	B 11
S	Spar, spindle	Q 24
s	Second(s) of time	B 51, P 12
SALM	Single Anchor Leg Mooring	L 12

SBMSingle Budy MooringE 16ScScannerE 30.3ScScoriaeJoSchSchistJhSchSchoolE fSDSailing DirectionsSdSdSoundI2SESoutheastB 14secSeconds of timeB 51SepSeptemberSfSfStiffJ 36sftSoftJ 33ShShellsJ 11Sh1ShoalT20Sig StaSignal stationT 20Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahShtSemountJ 4SpSphericalJ 35SpChurch spireE 10.3SpSpireL 10.3SpSpireJ 13SpSpireJ 2SpSpireJ 2SpSpireJ 35SpChurch spireJ 35SpSpireL 10.3SpSpireJ 35SpSpireJ 35SpSpireJ 4SpireSpireZ 2SpSpireJ 35SpSpireJ 35SpSpireJ 35SpSpireJ 35SpSpireJ 35SpireSpireJ 35SpireSpireJ 35Spire	0.014	Oin als Durau Manain a	1.40
ScScoriaeJ oSchaSchistJ hSchSchoolE fSchSailing DirectionsESdSoundI2SdSounding doubtfulI 2SESoutheastB 14secSeconds of timeB 51SepSeptemberJ 36SfSoftJ 36SfSoftJ 35SgSeagrassJ 13.3ShShoalJ 4SigSignalT 20Sig StaSignal stationT 20S/MSand over mudJ 12.1smlSmoutheastingP bS/MSand over mudJ 12.1smlSingleJ adShSeamountJ 4SpSoftJ 35SpChurch spireE 10.3SpSphericalQ 22SpSpiregideJ tSpigSpiregideJ tSpipe, S'pipeSpongeJ tSpipe, S'pipeSpeckledJ alSpipe, S'pipeSignal stationI 21Spipe, S'pipeSpeckledJ alSpipe, S'pipeSpeckledJ alSpipe, S'pipeSingle Point MooringL 12SSSignal stationT 20-36Spipe, S'pipeSignal stationT 20-36Spipe, S'pipeSignal stationJ 3Spipe, S'pipeSingle Point MooringL 12SSSignal stationJ 20-36Spipe, S'pipeSignal st	SBM	Single Buoy Mooring	L 16
SchSchistJ hSchoolE fSchoolE fSDSailing DirectionsSdSoundSDSounding doubtful12SESoutheastB 14secSeconds of timeB 51SepSeptemberJ 36SfSoftJ 35SgSeagrassJ 13.3ShShellsJ 11ShIShoalJ 11ShiSignalR 1, T 25.2Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSignal stationJ 35SpSoftJ 35SpSoftJ 36S/MSand over mudJ 12.1smlShingleJ dS/MSeamountJ 12.1SmlShingleJ dSpSoftJ 35SpChurch spireE 10.3SpSphericalQ 22SpspireE 10.3SpSping tideH 16SpgSping tideJ 4Spipe, S'pipeStandpipeJ 2Spipe, S'pipeStandpipeJ 2Spipe, S'pipeStandpipeJ 20.36Spipe, S'pipeSignal stationJ 20.36Spipe, S'pipeStandpipeJ 20.36Spipe, S'pipeStandpipeJ 20.36Spipe, S'pipeStandpipeJ 20.36SpipeSignal stationJ 20.36			
SchSchoolE fSDSailing DirectionsSdSoundSdSounding doubtful12SESoutheastB 14secSeconds of timeB 51SepSeptemberJ36sfSoftJ35SgSeagrassJ 13.3ShShellsJ 11ShIShoalJ4SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1SmlShingleJ ahShingSeagnasJ 35SpSoftJ 35SymShingleJ ahShingShingleJ dShingSignalJ 4SigSing StaJ 35SpSpongeJ dShingleSoftJ 35SpChurch spireE 10.3SpSphericalQ 22SpspireSping 14Spipe, S'pipeSping tideH 16Spipe, S'pipeSpiculesJ alSpipe, S'pipeStandpipeL 12SsSignal stationT 20-36SpitetSignal stationT 20-36SpitetSpiculesJ 35Spipe, S'pipeSpignal stationJ 35SpipeSping tideH 16Spipe, S'pipeStandpipeJ 21SpipeSignal stationJ 20-36SpitetSpignal station			
SDSailing DirectionsSdSoundSdSounding doubtful12SDSounding doubtful12SESoutheastB 14secSeconds of timeB 51SepSeptember5sfStiffJ 36sftSoftJ 35SgSeagrassJ 13.3ShShellsJ 11ShlShoalJ 11ShlSignalR 1, T 25.2Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahShtiSeamountJ 12.1SnShingleJ dShtSoftJ 35SpChurch spireJ 35SpSphericalQ 22SpSpire(all conspire)E 10.3SpSpireg tideH 16SpgSpireg tideJ xSpipe, S'pipeStandpipeJ 2Spipe, S'pipeStandpipeJ 2SpSpiculesJ alSpipe, S'pipeStandpipeL 12SSSignal stationT 20-36SpitelSingle Point MooringL 12SpSingle Point MooringL 12SpSingle Point MooringL 12StStoresJ 5			-
SdSoundSdSounding doubtful12SDSounding doubtful12SESoutheastB 14secSeconds of timeB 51SepSeptemberImage: SeptembersfStiffJ 36SftSoftJ 35SgSeagrassJ 13.3ShShellsJ 11ShlShoalImage: Sig StaSig StaSignal stationT 20S-L FlShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahShtSeamountImage: Sig StaSnShingleJ dsoSoftJ 35SpChurch spireE 10.3SpSphericalQ 22SpspireSpingSping tideJ tSpiSpongeJ tSpie, S'pipeStandpipeJ xSpipe, S'pipeStandpipeJ alSPMSpicelesJ alSpipe, S'pipeStandpipeE 21SpSpiceledJ alSPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5			Ef
SDSounding doubtful1 2SESoutheastB 14secSeconds of timeB 51SepSeptemberJ 36sfStiffJ 36sfSoftJ 35SgSeagrassJ 13.3ShShellsJ 11Sh1ShoalJ 4SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ 4SnShingleJ dSpChurch spireJ 10.3SpSphericalQ 22SpSpireSpineSpieSping tideH 16SpigSping tideJ 1Spie, S'pipeStandpipeE 10.3Spipe, S'pipeStandpipeJ 2Spipe, S'pipeStandpipeI 12Spipe, S'pipeStandpipeI 12Spipe, S'pipeStandpipeI 20-36StStonesJ 5	-		
SESoutheastB 14secSeconds of timeB 51sepSeptemberFsfStiffJ 36sfSoftJ 35SgSeagrassJ 13.3ShShellsJ 11Sh1ShoalFSiSignalR 1, T 25.2Sig StaSignal stationT 20S-L FlShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ 4SnShingleJ dSpChurch spireE 10.3SpSphericalQ 22SpSpine ideJ 1SpieSping ideH 16SpgSping ideJ tSpipe, S'pipeStandpipeE 21spkSpeckledJ alSPMSingle Point MooringL 12SpSingle Point MooringL 12StStonesJ 5			
secSeconds of timeB 51SepSeptembersfStiffJ 36sftSoftJ 35SgSeagrassJ 13.3ShShellsJ 11ShlShoalJ 11ShiSiltJ 4SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ 4SpChurch spireJ 10.3SpChurch spireE 10.3SpSphericalQ 22SpSping tideH 16SpgSping tideJ tSpipe, S'pipeSpiculesJ xSpipe, S'pipeStandpipeE 21spkSpeckledJ alSPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	-		
SepSeptembersfStiffJ 36sf1SoftJ 35SgSeagrassJ 13.3ShShellsJ 11ShlShoalJ 11Sh1ShoalTSigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FlShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ dShSoftJ 35SpChurch spireE 10.3SpSphericalQ 22SpspireE 10.3SpSping tideH 16SpigSping tideJ xSpipe, S'pipeSpiculesJ xSpipe, S'pipeStandpipeE 21SpKSpeckledJ alSPMSingle Point MooringL 12SpSingle Point MooringL 12StStonesJ 5	SE	Southeast	B 14
sfStiffJ 36sftSoftJ 35SgSeagrassJ 13.3ShShellsJ 11ShlShoalJ4SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FlShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ 4SnShingleJ dSnShingleJ 35SpChurch spireE 10.3SPSphericalQ 22SpSping tideH 16SpgSpongeJ tSpieSpongeJ tSpieSpiculesJ xSpieSpiculesJ alSPMSpiculesJ alSPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	sec	Seconds of time	B 51
sftSoftJ 35SgSeagrassJ 13.3ShShellsJ 11Sh1ShoalJ4SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FlShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ dSnShingleJ dSpChurch spireE 10.3SpSphericalQ 22SpspireE 10.3SpSpring tideJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21SpKSingle Point MooringL 12SSSingle Point MooringL 12StStonesJ 5	Sep	September	
SgSeagrassJ 13.3ShShellsJ 11Sh1ShoalJSiSiltJ 4SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ dSnShingleJ dSpChurch spireE 10.3SpSphericalQ 22SpSpire giveJ tSpiSpire giveJ tSpiSpire giveJ tSpiSpire giveJ tSpiSpire giveJ tSpiSpire giveJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21SpKSingle Point MooringL 12StSignal stationT 20-36	sf	Stiff	J 36
ShShellsJ 11ShlShoalJ4SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ ahShSoftJ 35SpChurch spireE 10.3SPSphericalQ 22SpSping tideH 16SpgSpongeJ tSpipe, S'pipeStandpipeE 21spkSigelePoint MooringL 12SSSignal stationT 20-36StStonesJ 5	sft	Soft	J 35
ShiShoalSiSiltJ4SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FlShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ dSnShingleJ dspChurch spireE 10.3SPSphericalQ 22SpSpring tideH 16SpigSpongeJ tSpie, S'pipeSpiculesJ xSpipe, S'pipeStandpipeE 21spkSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Sg	Seagrass	J 13.3
SiSiltJ 4SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ dSnShingleJ dsoSoftJ 35SpChurch spireE 10.3SPSphericalQ 22SpSpring tideH 16SpgSpongeJ tSpieSpongeJ tSpie, S'pipeStandpipeE 21spkSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Sh	Shells	J 11
SigSignalR 1, T 25.2Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ dSnShingleJ dsoSoftJ 35SpChurch spireE 10.3SPSphericalQ 22SpSping tideH 16SpgSpongeJ tSpiSpiculesJ xSpie, S'pipeStandpipeE 21spkSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Shl	Shoal	
Sig StaSignal stationT 20S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ dSnShingleJ dsoSoftJ 35SpChurch spireE 10.3SPSphericalQ 22SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21spkSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Si	Silt	J 4
S-L FIShort-Long FlashingP bS/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ dSnShingleJ dsoSoftJ 35SpChurch spireE 10.3SPSphericalQ 22SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpie, S'pipeStandpipeE 21spkSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Sig	Signal	R 1, T 25.2
S/MSand over mudJ 12.1smlSmallJ ahSMtSeamountJ dSnShingleJ dsoSoftJ 35SpChurch spireE 10.3SPSphericalQ 22SpspireE 10.3SpgSpongeJ tSpiSpiculesJ xSpie, S'pipeStandpipeE 21spkSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Sig Sta	Signal station	T 20
smlSmallJ ahSMtSeamountSnShingleJ dsoSoftJ 35SpChurch spireE 10.3SPSphericalQ 22SpspireE 10.3SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21spkSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	S-L FI	Short-Long Flashing	Рb
SMtSeamountSnShingleJ dsoSoftJ 35SpChurch spireE 10.3SPSphericalQ 22SpspireE 10.3SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpike, S'pipeStandpipeE 21SpKSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	S/M	Sand over mud	J 12.1
SnShingleJ dsoSoftJ 35spChurch spireE 10.3SPSphericalQ 22SpspireE 10.3SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21spkSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	sml	Small	J ah
soSoftJ 35SpChurch spireE 10.3SPSphericalQ 22SpspireE 10.3SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpikSpeckledJ alSPMSingle Point MooringL 12SSStonesJ 5	SMt	Seamount	
SpChurch spireE 10.3SPSphericalQ 22SpspireE 10.3SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21spkSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Sn	Shingle	J d
SPSphericalQ 22SpspireE 10.3SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21spkSpeckledJ alSPMSingle Point MooringL 12SSStonesJ 5	so	Soft	J 35
SpspireE 10.3SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21spkSpeckledJ alSPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Sp	Church spire	E 10.3
SpSpring tideH 16SpgSpongeJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21spkSpeckledJ alSPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	SP	Spherical	Q 22
SpgSpongeJ tSpiSpiculesJ xSpipe, S'pipeStandpipeE 21spkSpeckledJ alSPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Sp	spire	E 10.3
SpiSpiculesJ xSpipe, S'pipeStandpipeE 21spkSpeckledJ alSPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Sp	Spring tide	H 16
Spipe, S'pipeStandpipeE 21spkSpeckledJ alSPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Spg	Sponge	J t
spkSpeckledJ alSPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Spi	Spicules	Jх
SPMSingle Point MooringL 12SSSignal stationT 20-36StStonesJ 5	Spipe, S'pipe	Standpipe	E 21
SSSignal stationT 20-36StStonesJ 5	spk	Speckled	J al
St Stones J 5	SPM	Single Point Mooring	L 12
	SS	Signal station	T 20-36
St M, St Mi Statute mile(s) B e	St	Stones	J 5
	St M, St Mi	Statute mile(s)	Ве

STA, Sta	Station	F 41.1, S 15, T 3
stf	Stiff	J 36
Stg	Sea-tangle	Jw
stk	Sticky	J 34
Str	Strait	
Str	Stream	ні
str	Streaky	J ak
sub	Submarine	K d
Subm	Submerged	K 43.1
SW	Southwest	B 16
sy	Sticky	J 34
т		
Т	Short ton(s)	Bm
Т	Telephone	Eq
Т	TRUE	B 63
Т	Tufa	Jn
t	Ton(s), Tonnage (weight)	B 53, F 53
Tel	Telegraph	D 27
Tel off	Telegraph office	Ek
Temp, temp	Temporary	P 54
ten	Tenacious	J aq
Tk	Tank	E 32
TR, Tr, Trs	Tower(s)	E 10.2, E 20
TSS	Traffic Separation Scheme	M 20.1
TT	Tree tops	C 14
TV Mast	Television mast	E 28
TV Tower	Television tower	E 29
U		
ULCC	Ultra Large Crude Carrier	
Uncov	Uncovers	K 11
unev	Uneven	J bf
Univ	University	Eh
UQ	Ultra quick	P 10.8
UTC	Coordinated Universal Time	
UTM	Universal Transverse Mercator	
V		
v	Volcanic	J 37

var, VAR	Variation	B 60
vard	Varied	J be
vel	Velocity	Hn
vert	Vertically disposed	P 15
Vert CL	Vertical clearance	D 20, 28
Vi	Violet	P 11.5
Vil	Village	D 4
VLCC	Very Large Crude Carrier	G 187
vol	Volcanic, Volcano	J 37
Vol Ash	Volcanic ash	Jk
VQ	Very quick	P 10.7
VTS	Vessel Traffic Service	
w		
w	West	B 12
w	White	P 11.1
Wd	Weed	J 13.1
Well	Wellhead	L 21
WGS	World Geodetic System	S 50
Wh	White	J ar
Whf	Wharf	F 13
WHIS, Whis	Whistle	R 15
Wk, Wks	Wreck(s)	K 20
Wtr Tr, WTR TR	Water tower	E 21
Y		
Y	Yellow, Orange, Amber	P 11.6-11.8
yd, yds	Yard(s)	Вd
yl	Yellow	J aw
μ		
µs, µsec	Microsecond(s)	Bf

Α	
Abandoned railroad	Dc
Accommodation vessel	L 17
Accurate position	B 32, E 2
Aerial cableway dish	D 25 E 31
Aero light	P 60
Aeronautical radiobeacon	S 16
Air obstruction light	P 61.1–61.2
Airfield	D 17
Airport	D 17
AIS	S 17.1–17.2
All-round light	P 42.1–43.2
Alternate course	Мс
Alternating light	P 10.11
Amber	P 11.8
Anchor berth	N 11.1–11.2
Anchorage areas buoy for sea-planes	N 10–14 Q j N 14
Anchoring prohibited	N 20
Annual change	B 70
Anomaly, magnetic	B 82.1–82.2
Antenna	E 31
Apparent shoreline	Ср
Approximate depth contour height of top of trees position topographic contour vertical clearance	I 31 C 14 B 7, 33, E 2 C 12 D i
Aquaculture	K 44.1–48.2
Archipelagic Sea Lane (ASL)	M 17
Areas pipeline restricted to be avoided wire drag	N L 40.2, L 41.2 M 14, N 2.1 M 14, 29.1–29.2 I 24
Articulated Loading Column (ALC)	L 12
Ash, volcanic	Jk
Astronomical tide	H 2–3

Automatic Identification System (AIS) transmitter	S 17.1–17.2
Awash, rock	K 12
В	
Band, S & X	S 3.1–3.2
Bar code	Ad
Barrage, flood	F 43
Barrel buoy	Q 25
Barrier floating oil retention security Bascule bridge	F 29.1 F 29.2 F 29.1, Q q D 23.4
Basin	F 27–28
Battery	E 34.3
Battery (fortification)	E 34.3
Battery (fortification) Beacon articulated buoyant leading lighted marking a clearing line marking measured distance on submerged rock radar radio resilient topmarks towers Bearing Being reclaimed Bell buoy on land Benchmark	Q 80–126 P 5 P 5 Q 102.2, 120 Q 102.2, 120 Q 121 Q 122 Q 83 S 2–3.6 S 10–16 P 5 Q 9–11, 82, 102.1 P 3, Q 110–111 B r F 31 R 14 Q a, R 21 T a B 0
Berth anchor dangerous cargo designation visitors yacht	N 11.1–11.2 F 19.3 F 19.1, N 11.1–11.2, Q 42 F 19.2 F 11.2
Bifurcation buoy	Q h
Black	J as, Q 2
Blind, duck	K j–k
Blockhouse	E 34.2
Blue	J au, P 11.4

Board (leading beacon)	Q 102.2
Boarding place, pilot	T 1.1–1.4
Boat harbor, marina	F 11.1
Boom	F 29.1
Boulders international	J 9.2 N 40–41
Boundary IALA region	Q 130
Breakers	C d, K 17
Breakwater	F 4.1–4.3
Bridge bascule draw fixed lifting light (traffic signal) passage signal station pontoon swing transporter under construction	D 20.1–24 D 23.4 D 23.6 D 20.1 D 23.3 T 25.2 T 25.1 D 23.5 D 23.2 D 24 D d
Broken	J 33
Brown	J az
Bubbler curtain, bubbler	F 29.2
Buildings	D 2, 5–6, 8
Buoyage system, IALA	Q 130–130.7
Buoyant beacon	P 5
Buoy cardinal isolated danger lateral mooring new danger safe water scientific mooring special	Q 20–71 Q 130.3 Q 130.4 Q 130.1 Q 40–45 Q 130.7 Q 130.5 Q r Q 130.6
Buried pipeline	L 42.1
Bushes	Со
C	
Cable ferry landing beacon overhead submarine	M 51 Q 123 D 26–27, H 20 L 30.1–32
Cableway (aerial)	D 25
Cairn	Q 100

CALM (Catenary Anchor Leg Mooring)	L 16
Caisson	F 42
Calcareous	J 38
Calling-in point	M 40.1
Calvary cross	E 24
Camping site	E 37.1–37.2
Can buoy	Q 21
Canal distance mark	F 40 B 25.1–25.2
Candela	B 54
Cardinal marks	Q 130.3
Careening grid	F 24
Cargo transhipment area	N 64
Castle	E 34.2
Casuarina	C 31.6
Causeway	F 3
Cautionary notes	A 16
Cemetery	E 19
Centimeter	B 43
Chalk	J f
Channel	l 20–22
Chart datum dimension number reference to another scale title	A 3, C a, H 1, 20 A 8 A1–2 A 18–19 A 13 A 10
Chemical dumping ground	N 24
Chemical pipeline	L 40.1–40.2
Chimney	E 22
Chocolate	J ba
Church dome spire tower	E 10.1 E 10.4 E 10.3 E 10.2
Cinders	Jр
Circular (non-directional) aeromarine radiobeacon	S 10
Circular (non-directional) marine radiobeacon	S 10
Cirripedia	J ae

Clay	J 3
Clearance horizontal safe vertical vertical	D 21 D 26, i D 22, 23.1, 23.4, 23.6–28
Cleared platform	L 22
Clearing line	M 2
Clearing line beacon	Q 121
Cliffs	C 3
Coal head	Ji
Coarse	J 32
Coast flat radar station radio station providing QTG service steep	C 5 S 1 S 15 C 3
Coast Guard station	T 10–11
Coastline surveyed unsurveyed	C 1–8 C 1 C 2
Cobbles	J 8
Colored mark	Q 101
Colored topmark	Q 102.1
Colors beacons buoys lights topmarks	Q 2–5 Q 2–5 P 11.1–11.8 Q 2–5
COLREGS demarcation line	Na
Columbia River Datum	Нj
Column	E 24
Compass rose	A c, B 70
Composite group-flashing group-occulting	P 10.4 P 10.2
Conical buoy	Q 20
Conifer	C 31.3, j
Consol beacon	S 13
Conspicuous landmark	E 2
Conspicuous, radar	S 5
Container crane	F 53.2
Contiguous zone	N 44
Continental shelf	N 46

Continuous quick ultra quick very quick	P 10.6 P 10.8 P 10.7
Contour depth drying topographic	I 30–31 I 15, 30 C 10, 12, H 20
Control point	B 20–24
Conversion scales	Aa
Conveyor	Fg
Copyright note	A 5
Coral	J 10, 22, K 16, h, m
Coral reef always covers covers and uncovers detached	K 16 J 22, K m K h
Coralline algae	J 10
Corner coordinates	A 9
Covers	J 21–22, K 11, 16, 21
Crane	F 53.1–53.3
Crib	K i–j, L 43, b
Crossing gates	M 22
Crossing, traffic separation	M 23
Cubic meter	Вb
Cultivated fields shellfish	C I K 47
Cultural features	D
Cupola	E 10.4
Current diagram in restricted waters	H 42–43, m, t H t H 42
Customs	F 61
house limit office	N 48 F 61
limit	N 48
limit office	N 48 F 61
limit office Cutting	N 48 F 61 D 14

D	
Dam	F 44
Danger firing area isolated mark line signal station zone	N 30, Q 50, 125 Q 130.4 K 1 T 35 Q 50
Dangerous cargo berth <i>rock</i> wreck	F 19.3 K 10–13, 14.2 K 28
Dark	J bd
Data collection buoy	Q 58
Datum chart sounding reduction	H 1, 20 H 1
Daymark (dayboard)	Q 10, 80–81, 110, I
Daytime light	P 51
Deadhead	K 43.2
Decayed	J an
Deciduous woodland	Ci
Decimeter	B 42
Deep water anchorage area route	N 12.4 M 27.1–27.3
Degaussing range buoy	N 25 Q 54
Degree	B 4
Depth	
charted contours minimum observed	H 20 I 30 K 46.2, M 27.2 H 20
out of position	I 11
safe clearance	K 3, 30, f
swept	I 24, a, b, K 2, 27, 42, f
units used for	Ab K3 13 23 28 30 40 a
unknown	K 3, 13, 23, 28, 30, 40, a, L 21.1
Depths	I
Derrick, oil	L 10

Designation of	
beacon	Q 10
berth	F 19.1
buoy platform	Q 11 L 2
reporting point	M 40.1
tidal stream, position of tabulated data	H 46
transit shed	F 51
Detector light	P 62
Development area	L 4
Deviation	
dolphin	F 21
DGPS correction transmitter	S 51
Diaphone	R 11
Diatoms	Jaa
Diffuser	L 43
Dike	F 1
Direction	
of buoyage	Q 130.2
finding, radio station of flow	S 14 F 44
light	P 30.1–31
of traffic	M 10, 11, 26.1–26.2, 40.1
Directional radiobeacon	S 11
Directions, compass	В
Discolored water	Ke
Dish aerial	E 31
Disposition of lights	P 15
Distance	В
along waterway	B 25.1–25.2
measured, beacons marking	Q 122
Disused	
pipeline/pipe	L 44
platform submarine cable	L 14 L 32
Diurnal tide	H 30
	п эu
Dock dry, graving	F 25
floating	F 26
wet	F 27
Dolphin	F 20–21
Dome	E 30.4
Doubtful	
depth	12
existence	11
position	B 8

Draft area channel	M 6, N 12.4 I 20–22 I 20–22
Dredging (extraction) area	N 63
Drying contour height	l 30 H 20, I 15
Duck blind	K j–k
Dumping ground chemical waste explosives	N c, d, g N 24 N 23.1–23.2
Dunes	C 8
E	
East cardinal mark	B 10 Q 130.3
Ebb tide stream	H 41
Eddies	H 45
Edition note	A 6
Eelgrass	Ct
Elevation of light	H 20, P 13
Ellipsoid	A 3
Embankment	D 15
Entry prohibited area	N 2.2, 31
Environmentally Sensitive Sea Area (ESSA)	N 22
Established (mandatory) direction of traffic flow	M 10
Eucalypt	C 31.8
Evergreen	C 31.2
Example of conspicuous landmarks fog signal descriptions full light description landmarks routing measures	E 2 R 20–22 P 16 E 1 M 18–29.2
Exclusive Economic Zone (EEZ)	N 47
Exercise area, submarine	N 33
Existence doubtful	I 1
Explanatory notes	A 11, 16
Explosive fog signal	R 10
Explosives anchorage area dumping ground	N 12.7 N 23.1–23.2
Extinguished light	P 55

Extraction area	N 63
F	
Factory	E d
Faint sector	P 45.1–45.2
Fairway	M 18
Farm marine wave wind	K 48.1–48.2 L 6 L 5.2
Fast ice, limit	N 60.1
Fathom(s)	B 48
Feet	B 47
Fence	Dg
Ferry <i>terminal, RoRo</i>	M 50–51 F 50
Filao	C 31.7
Fine	J 30
Fireboat station	Тс
Firing danger area danger area buoy practice signal station	N 30 Q 50 T 36
Fish haven marine farm trap weir	K 46.1–46.2 K 48.1–48.2 K 44.2–45, Q i K 44.2
Fishery zone limit	N 45
Fishing harbor limit (fish trap area) prohibited stakes	F 10 N b N 21.1 K 44.1
Fixed bridge flashing, and light point	D 20.1 P 10.10, d P 10.1 B 22
Flagstaff, Flagpole	E 27
Flare stack	E 23, L 11
Flashing light	P 10.4
Flat coast	C 5
Flinty	J ao
Float	Kq,Qs

Floating barrier dock	F 29.1 F 26
oil barrier	F 29.1
wind farm wind turbine	L 5.2 L 5.1
Flood	Hq
barrage	F 43
tide (stream)	H 40
Floodlit, floodlight	P 63
Fog	D 00
detector light light	P 62 P 52
signals	R
Foot	B 47
Footbridge	D 20.2
Foraminifera	Jу
Foreshore	Сс
Form lines	C 13
Fort	E 34.2
Fortified structure	E 34.1
Foul	
area ground	K o K 31.1–31.2
Front light	P 23
Fucus	Jaf
G	
Gable	Ei
Gas	
pipe line	L 40.1
pipeline area	L 40.2
Gasfield name	L1
Gate	F 42
Geographical positions	B 1–16
Glacial	J ap
Glacier	C 25
Globigerina	J z
Glossary	Ae
Gong	R 16, Q b
Grass	C s, J v
Grassfields area with	C m J 20

Graving dock	F 2
Gray	J b
Green	J av, P 11.3, Q
Gridiron	F 2
Gritty	J ar
Groin	F
Ground tackle	J Q 4
Group fixed and flashing flashing occulting quick short flashing very quick	P P 10. P 10. P 10. P 10. P 10.
Gulf Coast Low Water Datum	Н
Gulf Stream limits	Н
Gun	R 1
н	
Hachures	C
Harbor installations limit master's office	F 10–3 N 4 F 6
Harbors	
Hard	J 3
Health office	F 62.
Height datum drying light (elevation of) rocks spot of structure tide of top of trees of wellhead	H H 20, I 1 H 20, I 1 H 20, P 1 K 10–1 C 10–11, 13, H 2 E 4– H 20, P 1 C 1 L 2
Heliport, Helipad	D 1
Hertz	В
High water	H 20,
High Water Full and Change	Н
Higher High Water	H 20,
Highest Astronomical Tide (HAT)	Н
Highway markers	D 1 D

Hillocks	C 4
Horizontal	D 46
light clearance	P 15 D 21
Horizontally disposed	P 15
Horn	R 13
Hospital	E g, F 62.2
Hour	B 49
Hulk	F 34, K 20–21, 23
I	
IALA Maritime Buoyage System	Q 130
Ice	
boom	F 29.1
fast (ice front)	N 60.1 N 60.2
sea ice (pack ice) seasonal signal station	T 30
Illuminated	P 63
Imprint	A 4
Inadequately surveyed area	l 25
Inch	Вс
Incineration area	N 65
Indian Spring Low Water	Нg
Inshore traffic zone	M 25.1–25.2
Installations, offshore	L
Intake pipe	L 41.1–41.2, b
Intense	P 46.1–46.2
Intensified sector	P 46.1–46.2
Intermittent river	C 21
International	
boundary chart number	N 40–41 A 2
nautical mile, sea mile	B 45
Interrupted light	2.10
quick	P 10.6
ultra quick	P 10.8
very quick	P 10.7
Intertidal area	J 20–22
Isogonic lines (Isogonals)	B 71
Isolated danger mark	Q 130.4
Isophase light	P 10.3
J	
Jetty	F 14, a–c

Joss house	E 13
к	
Kelp	J 13.1–13.2, u
Kilocycle	Bk
Kilohertz	Bh
Kilometer	B 40
Knot	B 52, H o
L	
Lake intermittent	C 21, 23 C 21
LANBY	Pf
Landing beacon (cable) boats, for seaplanes, for stairs	Q 123 F 17 N 13 F 18
Landmarks	E
Lane, submarine transit	N 33
Large	J ai
Large Automatic Navigational Buoy (LANBY)	Pf
Lateral marks (IALA System)	Q 130.1
Latitude	B 1
Lattice beacon	Q 111
Lava	C 26, J 9, I
Layout of chart	A
Leading beacons lights line	Q 120 P 20.1–23 M 1
Least depth in narrow channel	K 26–27, 30 I 12
Leisure facilities	U
Levee	F 1
Lifeboat mooring station	T 12–13 T 13 T 12
Lifting bridge	D 23.3
Light	J bo
arc of visibility, with restricted character chart limits, off color	P 44.1–44.2 P 10.1–11.8 P 8 P 11.1–11.8

direction	P 30.1–31
disposition	P 15
elevation	P 13
exhibited only when specially needed	P 50
faint sector, with	P 45.1–45.2
float	Q 30.1–31
in line	P 21.1–21.2
intensified sector, with	P 46.1–46.2
landmarks, on	P 7
leading	P 20.1–23
marking fairway	P 20.1–23
Moiré effect	P 31 P 12
period	P 12 P 14
range sector	P 40.1–46.2
special	P 40.1–40.2 P 60–66
structures	P 1–7
synchronized	P 66
times of exhibition	P 50–55
vessel	P e, Q 32
Light characters	P 10.1–10.11
Lighted beacon	P 4, Q 0
beacon tower	P3
marks	Q 7–8
mooring buoy	Q 41
offshore platform	P 2.1–2.2
Lighthouse	P 1
Lights	Р
Lights exhibited only when specially	P 50
needed	
Lights in line	P 21.1–21.2
Lights Marking Fairways	P 20.1–23
Lights with limited times of exhibition	P 50–55
Limit of	
area feature in general	Сq
area into which entry is prohibited	N 2.2, 31
contiguous zone	N 44
continental shelf	N 46
danger line	K 1
development area	L 4
dredged area	I 20
Exclusive Economic Zone (EEZ)	N 47
fast ice	N 60.1
fishery zone	N 45
fishing area	Nb
Gulf Stream	Hu
nature reserve	N 22
no discharge zone	Ni
restricted area	M 14, N 2.1
routing measure	M 14–15
	101

safety zone	L 3
sea ice (pack ice) seasonal	N 60.2
unsurveyed area	l 25
Linear scale	A 14–15
Local magnetic anomaly	B 82.1–82.2
Lock	F 41.1–41.2
signal station	T 24
Log pond	F 29.1
Logo	A 12
Long-flashing light	P 10.5
Longitude	B 2
Lookout	
pilot station	T 2 T e
Low water line	H 20, c I 30
Lower light	P 23
Lower low datum	H d
Lower low water	Не
Lower water full & change	Hi
Lowest Astronomical Tide (LAT)	H 2
Μ	
Madrepores	Jj
Magnetic	Вq
anomaly	B 82.1–82.2
compass variation	B 68.1–71 B 68.1–71, p
Main light visible all-round	P 42.1–42.2
	F 42.1-42.2
Major light	P 1
light off chart limits	P 8
Manganese	ΡĹ
Mangrove	C 32
Manually activated	P 56, R 2
Marabout	E 13
Marginal notes	A
Marina	F 11.1
facilities	U a
Marine	K 10 1 10 0
farm reserve	K 48.1–48.2 N 22
Maritime limit	N 1.1–1.2
	IN 1.1-1.2

Marks	
cardinal	Q 130.3
colored	Q 101
isolated danger lateral	Q 130.4 Q 130.1
lighted	Q 130.1 Q 7–8
minor	Q 90–102.2
new danger	Q 130.7
safe water	Q 130.5
special	Q 130.6
wreck (new danger)	Q 130.7
Marl	Jc
Marsh	C 33
Mast	E 00 4
radar radia television	E 30.1
radio, television wreck	E 28 K 25
wreck Mattes	
	J ag
Maximum authorized draft	M 6
speed	N 27
Mean	
High Water (MHW)	H 5, 20, 30
High Water Neaps (MHWN)	H 11
High Water Springs (MHWS)	H 9
Higher High Water (MHHW)	H 13, 30
Higher Low Water (MHLW) Low Water (MLW)	H 14 H 4, 20, 30
Low Water Neaps (MLWN)	H 10
Low Water Springs (MLWS)	H 8
Lower High Water (MLHW)	H 15
Lower Low Water (MLLW)	H 12, 20, 30
Sea Level (MSL)	H 6, 20
tide level	H f
Measured Distance	Q 122
Medium	J 31
Megacycle	BI
Megahertz	Bi
Meter	B 41
Microsecond	Bf
Mid-channel buoy	Qe
Mile	
nautical (sea mile)	A 15, B 45
statute three nautical mile line	B 25.1–25.2, e
	N h
Military area	N 30–34
Millimeter	B 44
Minaret	E 17
Mine (explosive)	N 23.1

Mine (ore extraction)	E 36
Minefield	N 34
Mine-laying practice area	N 32
Minor impermanent marks light light floats marks pile post	Q 90–92 P 1, note after P 5 Q 30.1–31 Q 100–102.2 F 22 F 22
Minute of arc of time	B 5 B 50
Mixed bottom	J 12.1–12.2
Moiré effect light	P 31
Mole	F 12
Monument	E 24
Moored storage tanker	L 17
Mooring berth number canal ground tackle life boat numerous scientific mooring buoy Single Buoy (SBM) Single Point (SPM) trot visitors' buoy lighted tanker telegraphic telephonic Morse Code for signal	Q 42 F f L 18, Q 42 T 13 Q 44 Q r L 16 L 12 Q 42 Q 45 Q 40–45 Q 40–45 Q 41 L 16 Q 43 Q 43
fog signal light	R a P 10.9
Mosque	E 17
Motorway	D 10
Mud	C c, J 2
Muslim shrine	Ea
Mussels	Js
Ν	
National limits park	N 40–49 N 22
Natural features watercourse	C I 16

of the seabedNautical mileBNautophoneRNeap tideH 10–11, 17, 30–Nets, tunnyK 44.2–Newedition datedanger markQ 130Nipa palmC 31.5,No anchoring areaNNo bottom foundINo discharge zoneINon-dangerous wreckK 15,Non-directional radiobeaconSNorthEcardinal markQ 130NortheastBNotthesA 11,Notice boardQ 126, 1Notice to marinersANun buoyQOIObservation spotBObstructionK 40–48light, airP 61.1–61Occasional lightP 10Occasional lightP 10ODAS buoyL 25, QOfficeCcustomsFharbormaster'sFhealthF 62		
NautophoneRNeap tideH 10–11, 17, 30–Nets, tunnyK 44.2–Newdanger markedition dateAdanger markQ 133Nipa palmC 31.5,No anchoring areaNNo bottom found1No discharge zone1Non-dangerous wreckK 15,Non-directional radiobeaconSNon-tidal basinFNorthEcardinal markQ 130NotheestBNottee boardQ 126, TNotice to marinersANun buoyQOSObservation spotBObservation spotBObstructionK 40–48light, airP 61.1–67Occasional lightP 10Occasional lightP 10OLAS buoyL 25, QOfficeFcustomsFharbormaster'sFhealthF 62	reserve	N 22 J
Neap tideH 10–11, 17, 30–Nets, tunnyK 44.2–New edition date danger markQ 133Nipa palmC 31.5,No anchoring areaNNo bottom foundINo discharge zoneINon-dangerous wreckK 15,Non-directional radiobeaconSNorthEcardinal markQ 130NortheastBNothesA 11,Notice boardQ 126, TNotice to marinersANun buoyQOIObservation spotBObstructionK 40–48light, airP 61.1–61Occasional lightP 10Ocean currentHODAS buoyL 25, QOffice customsFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sF	Nautical mile	B 45
Nets, tunnyK 44.2-New edition date danger markAQ 130Nipa palmC 31.5,No anchoring areaNNo bottom foundINo discharge zoneINon-dangerous wreckK 15,Non-directional radiobeaconSNon-tidal basinFNorth cardinal markBNortheeastBNotesA 11,Notice boardQ 126, TNun buoyQOCObservation spotBObservation spotBObstructionK 40-48light, airP 61.1-61Occasional lightP 10Occasional lightP 10OtAS buoyL 25, QOffice customsFharbormaster'sFharbormaster'sFhealthF 62	Nautophone	R 13
New edition date danger markA Q 130Nipa palmC 31.5, No anchoring areaNNo bottom foundINo discharge zoneINon-dangerous wreckK 15, Non-directional radiobeaconNon-tidal basinFNorth cardinal markBNortheastBNotesA 11, Notice boardNotice to marinersANun buoyQOCObeliskEObservation spotBObstructionK 40–48 light, airOccasional lightPOccasional lightPODAS buoyL 25, QOffice customsFharbormaster's harbormaster'sFharbormaster's harbormaster'sFfallFCodeFAlthornersFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfallFfall<	Neap tide	H 10–11, 17, 30–31
edition date danger markA Q 130Nipa palmC 31.5,No anchoring areaNNo bottom foundINo discharge zoneINon-dangerous wreckK 15,Non-directional radiobeaconSNon-tidal basinFNorthEcardinal markQ 130NortheastBNotresA 11,Notice boardQ 126, 1Notice to marinersANun buoyQOCObscured sectorP 43.1-43Observation spotBObstructionK 40-48light, airP 61.1-61Occasional lightP 10Occasional lightP 10ODAS buoyL 25, QOfficeF <i>customs</i> F <i>harbormaster's</i> F <i>harbormaster's</i> F <i>harbormaster's</i> F <i>harbormaster's</i> F <i>harbormaster's</i> F	Nets, tunny	K 44.2–45
No anchoring areaNNo bottom foundINo bottom foundINo discharge zoneINon-dangerous wreckK 15,Non-directional radiobeaconSNon-tidal basinFNorthEcardinal markQ 133NortheastBNorthwestBNotesA 11,Notice boardQ 126, 1Notice to marinersANun buoyQOIObservation spotBObservation spotBObstructionK 40-48light, airP 61.1-64OCasional lightP 10Ocean currentHODAS buoyL 25, QOfficeFnather'sFharbormaster'sFharbormaster'sFhealthF 62	edition date	A 6 Q 130.7
No bottom foundINo discharge zoneINon-dangerous wreckK 15,Non-directional radiobeaconSNon-tidal basinFNorthEcardinal markQ 130NortheastBNorthwestBNotesA 11,Notice boardQ 126, 1Notice to marinersANun buoyQOOObscured sectorP 43.1-43Observation spotBObstructionK 40-48light, airP 61.1-64Occasional lightPOccuting lightP 10Ocean currentHODAS buoyL 25, QOfficeFnathbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFNotice to sectorFNoticeFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNoticeFNo	Nipa palm	C 31.5, 32
No discharge zoneINon-dangerous wreckK 15,Non-directional radiobeaconSNon-tidal basinFNorthEcardinal markQ 130NortheastBNorthwestBNotice boardQ 126, TNotice to marinersANun buoyQOOObeliskEObscured sectorP 43,1-43Observation spotBObstructionK 40-48light, airP 61,1-67Occasional lightP 10Ocean currentHODAS buoyL 25, QOfficeFnathbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFharbormaster'sFNotexFNotexFNotexFNotexFNotexFNotexFNotexFNotexFNotexFNotexFNotexFNotexFNotexFNotexFNotex	No anchoring area	N 20
Non-dangerous wreckK 15,Non-directional radiobeaconSNon-tidal basinFNorthEcardinal markQ 133NortheastBNorthwestBNotesA 11,Notice boardQ 126, TNotice to marinersANun buoyQOOObeliskEObservation spotBObstructionK 40–48light, airP 61.1–61Occasional lightP 10Ocean currentHODAS buoyL 25, QOffice customsFharbormaster's harbormaster'sFhaalthF 62	No bottom found	I 13
Non-directional radiobeaconSNon-tidal basinFNorthEcardinal markQ 133NortheastBNorthwestBNotesA 11,Notice boardQ 126, TNotice to marinersANun buoyQOOObeliskEObscured sectorP 43,1-43Observation spotBObstructionK 40-48light, airP 61,1-64Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOfficeFnationaster'sFharbormaster'sFhealthF 62	No discharge zone	Ni
Non-tidal basinFNorthEcardinal markQ 130NortheastBNorthwestBNotesA 11,Notice boardQ 126, 1Notice to marinersANun buoyQOOObeliskEObscured sectorP 43.1–43Observation spotBObstructionK 40–48light, airP 61.1–61Occasional lightP 10Ocean currentHODAS buoyL 25, QOfficeFnathormaster'sFharbormaster'sFhalthF 62	Non-dangerous wreck	K 15, 29
North cardinal markE Q 130NortheastBNorthwestBNotesA 11,Notice boardQ 126, TNotice to marinersANun buoyQOOObeliskEObscured sectorP 43.1–43Observation spotBObstructionK 40–48light, airP 61.1–61Occasional lightP 10Ocean currentHODAS buoyL 25, QOffice customsF harbormaster'shathormaster's healthF 62	Non-directional radiobeacon	S 10
cardinal markQ 130NortheastBNorthwestBNotesA 11,Notice boardQ 126, 1Notice to marinersANun buoyQOOObeliskEObscured sectorP 43.1-43Observation spotBObstructionK 40-48light, airP 61.1-61Occasional lightP 10Occean currentHODAS buoyL 25, QOfficeFnarbormaster'sFharbormaster'sFhealthF 62	Non-tidal basin	F 27
NorthwestBNotesA 11,Notice boardQ 126, TNotice to marinersANun buoyQOOObeliskEObscured sectorP 43.1–43Observation spotBObstructionK 40–48light, airP 61.1–61Occasional lightPOccutting lightP 10Occean currentHODAS buoyL 25, QOfficeFnarbormaster'sFharbormaster'sFhealthF 62		B 9 Q 130.3
NotesA 11,Notice boardQ 126, TNotice to marinersANun buoyQOOObeliskEObscured sectorP 43.1–43Observation spotBObstructionK 40–48light, airP 61.1–61Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOfficeF <i>customs</i> F <i>harbormaster's</i> F <i>harbormaster's</i> F	Northeast	B 13
Notice boardQ 126, TNotice to marinersANun buoyQOQOCObeliskEObscured sectorP 43.1–43Observation spotBObstructionK 40–48light, airP 61.1–61Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOfficeFnationsFnationsFharbormaster'sFhealthF 62	Northwest	B 15
Notice to marinersANun buoyQOOObeliskEObscured sectorP 43.1–43Observation spotBObstructionK 40–48light, airP 61.1–61Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOfficeFharbormaster'sFhealthF 62	Notes	A 11, 16
Nun buoyQOQOCObseliskEObscured sectorP 43.1-43Observation spotBObstructionK 40-48light, airP 61.1-61Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOfficeFcustomsFharbormaster'sFhealthF 62	Notice board	Q 126, T d
OObeliskObscured sectorObscured sectorObservation spotBObstructionIght, airP 61.1-61Occasional lightPOcculting lightODAS buoyL 25, QOfficecustomscustomsharbormaster'sFhealthF 62	Notice to mariners	Α7
ObeliskEObscured sectorP 43.1-43Observation spotBObstructionK 40-48light, airP 61.1-61Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOffice customsF harbormaster'shealthF 62	Nun buoy	Q 20
Obscured sectorP 43.1-43Observation spotBObstructionK 40-48light, airP 61.1-61Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOfficeFcustomsFharbormaster'sFhealthF 62	0	
Observation spotBObstructionK 40–48light, airP 61.1–61Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOfficeFnarbormaster'sFhealthF 62	Obelisk	E 24
ObstructionK 40–48light, airP 61.1–64Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOfficeFcustomsFharbormaster'sFhealthF 62	Obscured sector	P 43.1–43.2
light, airP 61.1–61Occasional lightPOcculting lightP 10Ocean currentHODAS buoyL 25, QOffice customs harbormaster'sFhealthF 62	Observation spot	B 21
Occulting lightP 10Ocean currentHODAS buoyL 25, QOffice customs harbormaster'sFhealthF 62		K 40–48.2 P 61.1–61.2
Ocean current     H       ODAS buoy     L 25, Q       Office     Customs       customs     F       harbormaster's     F       health     F 62	Occasional light	P 50
ODAS buoyL 25, QOffice customsFharbormaster's healthF62F	Occulting light	P 10.2
Office customs F harbormaster's F health F 62	Ocean current	H 43
customs F harbormaster's F health F 62	ODAS buoy	L 25, Q 58
	customs harbormaster's health pilot	F 61 F 60 F 62.1 T 2–3 F e

Offshore Installations platform, lighted position, tidal levels	L P 2.1–2.2 H 47
Ogival buoy	Q 20
Oil barrier derrick installation buoy, Catenary Anchor Leg Mooring (CALM) pipeline	F 29.1–29.2 L 10 L 16 L 40.1
pipeline area	L 40.2
Oilfield with name	L1
One-way track Ooze	M 5.1–5.2, 27.3 J b
	D 23.1
Opening bridge	J ax, P 11.7
Orange Ordnance, unexploded	јах, Р П.7 Кр
Outfall pipe	L 41.1–41.2
Overfalls	H 44
Overhead cable pipe transporter Oysters	D 27 D 28 D 25 J r
P	01
Pack ice, limit	N 60.2
Paddy field	C n
Pagoda	E 13
Painted board	Q 102.2
Palm	C 31.4
Park ranger station	Τg
Particularly Sensitive Sea Area (PSSA)	N 22
Patent slip	F 23
Path	D 12
Pebbles	J 7
Perch	Q 91
Period of light	P 12
Pictorial sketches	E 3.1–3.2
Pier promenade ruined	F 14 F 15 F 33.2

Pile submerged	F 22 K 43.1–43.2
Pillar	
buoy	Q 23
monument	E 24
Pilot	T 1–4
boarding place	T 1.1–1.3
helicopter transfer	T 1.4
look out	T 2
office	T 2–3
Pilotage	T 1–4
Pipe	
intake	L 41.1–41.2, b
outfall	L 41.1–41.2
overhead	D 28
pneumatic (bubbler)	F 29.2
Pipeline	1 40 4
buried land. on	L 42.1 D 29
overhead	D 29 D 28
submarine	L 40.1–44
tunnel	L 42.2
Platform	L 2, 10, 13–14, 22, P 2
cleared	L 22
submerged	K
Point	
base point for territorial sea baseline	
fixed	B 22
fixed Single Point Mooring (SPM)	B 22 L 12
fixed Single Point Mooring (SPM) symbols, position	B 22 L 12 B 32–33
fixed Single Point Mooring (SPM) symbols, position triangulation	B 22 L 12 B 32–33 B 20
fixed Single Point Mooring (SPM) symbols, position triangulation Pole	B 22 L 12 B 32–33 B 20 Q 90
fixed Single Point Mooring (SPM) symbols, position triangulation Pole	N 42 B 22 L 12 B 32–33 B 20 Q 90 T b
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine	B 22 L 12 B 32–33 B 20 Q 90 T b
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon	B 22 L 12 B 32–33 B 20 Q 90 T b J ad
fixed Single Point Mooring (SPM) symbols, position	B 22 L 12 B 32–33 B 20 Q 90 T b J ac F 16
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port	B 22 L 12 B 32–33 B 20 Q 90 T t J ac F 16 D 23.5
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port pilotage service, with	B 22 L 12 B 32–33 B 20 Q 90 T b J ad F 16 D 23.5
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port	B 22 L 12 B 32–33 B 20 Q 90 T b J ac F 16 D 23.5
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port pilotage service, with	B 22 L 12 B 32–33 B 20 Q 90 T t J ac F 16 D 23.5 T 4 T 21–23
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port pilotage service, with signal station Ports Position	B 22 L 12 B 32–33 B 20 Q 90 T t J ac F 16 D 23.5 T 2 T 21–23 F
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port pilotage service, with signal station Ports Position accurate	B 22 L 12 B 32–33 B 20 Q 90 T t J ac F 16 D 23.5 T 4 T 21–23 F B 2, E 2
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port pilotage service, with signal station Ports Position accurate approximate	B 22 L 12 B 32–33 B 20 Q 90 T t J ac F 16 D 23.5 T 21–23 F B 2, E 2 B 7, E 2
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port pilotage service, with signal station Ports Position accurate approximate of buoy or beacon	B 22 L 12 B 32–33 B 20 Q 90 T t J ac F 16 D 23.5 T 21–23 F B 2, E 2 B 7, E 2 Q 1
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port pilotage service, with signal station Ports Position accurate approximate of buoy or beacon doubtful	B 22 L 12 B 32-33 B 20 Q 90 T b J ac F 16 D 23.5 T 4 T 21-23 B 2, E 2 B 7, E 2 G 7, E 2 G 7, E 2 B 7, E 2 B 8
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port pilotage service, with signal station Ports Ports Position accurate approximate of buoy or beacon doubtful of fog signal	B 22 L 12 B 32–33 B 20 Q 90 T t J ac F 16 D 23.5 T 4 T 21–23 F B 2, E 2 B 7, E 2 B 7, E 2 R 7
fixed Single Point Mooring (SPM) symbols, position triangulation Pole Police station, marine Polyzoa Pontoon bridge Port pilotage service, with signal station Ports Position accurate approximate of buoy or beacon doubtful	B 22 L 12 B 32–33 B 20 Q 90 T t J ac F 16 D 23.5

Positions symbolized	В В 30–33
Post covers and uncovers office submerged	F 22, K 43.1 K r F 63 K 43.1
Power overhead cable submarine cable transmission line	D 26, H 20 L 31.1–31.2 D h
Practice area (military)	N 30–34
Precautionary area	M 16, M 24
Preferred channel buoy	Q 130.1
Private buoy light	Q 70 P 50, 65
Production platform well	L 10 L 20
Prohibited anchoring area diving fishing	N 20 N 2.2, 31 N 21.2 N 21.1
Promenade pier	F 15
Protective structures	F 1–6.3
Pteropods	J ac
Public Buildings	F 60–63
Publication note	A 4
Pumice	Jm
Pump-out facilities	Fd
Pylon	D 26, E 29
Q	
QTG service	S 15
Qualifying Terms	J 30–39
Quarantine anchorage area building, health office office	N 12.8 F 62.1 F e
Quarry	E 35.1–35.2
Quartz	Jg
Quay	F 13
Quick light	P 10.6

<b>D</b>	
Races	H 44
Racon	S 3.1–3.6
Radar	
beacon	S 2–3.6
conspicuous feature	S 5
dome (radome)	E 30.4
mast	E 30.1
range	M 31
reference line	M 32.1–32.2
reflector	Q 10–11, S 4
scanner	E 30.3
station	S1
surveillance system tower	M 30–32.2 E 30.2
transponder beacon, racon	S 3.1–3.6
transponder beacons on floating	S 3.1–3.0 S 3.6
marks	5 5.0
tower	E 29
Radio	S 10–18.7
direction-finding station	S 14
mast	E 28
repoting line	M 40.2
reporting point, calling-in or way point	M 40.1
station, QTG service	S 15
Radiobeacon	S 10–16
Radiolaria	J ab
Radome	E 30.4
Railway	D 13, b
station	D 13
Ramark	S 2
Ramp	F 23
Range	P 14
Rapids	C 22
Rate	Hn
Rear light	P 22
Reclamation area	F 31
Recommended	
deep water track	M 27.3, a–b
direction of traffic flow	M 11, 26.1–26.2, 28.1
route	M 28.1
track	M 3–4, 6
Red	J ay, P 11.2, Q 3
Reed beds	C 33
Reef	J 22, K 16, g–h, m

Reference to adjoining chart charted units	A 19 A b
larger-scale chart	A 18
Reflector, radar	Q 10–11, S 4
Refuge beacon for shipwrecked mariners	Q 124 T 14
Regions, IALA	Q 130.1
Relief	C 10–14
Reported anchorage danger depth	N 10   4   3.1–4
Reporting, radio	M 40.1–40.2
Rescue station	T 11–12
Reservation line	N f
Reserve fog signal	R 22
Reserved anchorage area	N 12.9
Resilient beacon	P 5
Restricted area light sector	M 14, N 2.1, 20–27 P 44.1–44.2
Retroreflecting material	Q 6
Rice paddy	C n
Riprap	Pa
River intermittent	C 20 C 21
Road	D 10–11
Rock	J 9.1, K 10–15, a–b
Rocket station	T 12
Rocky area which covers and uncovers	J 9.1 J 21
Roll-on, Roll-off ferry terminal (RoRo)	F 50
Rotating-pattern radiobeacon	S 12
Rotten	J aj
Roundabout	M 21
Route	M 27.1–28.2
Routing Measures	M 18–29.2
Rubble	Ce
Ruin	D 8, F 33.1

Ruined <i>landmark</i> <i>pier</i>	D 8 F 33.2
S	
Safe clearance depth vertical clearance water mark	K 3, 30, f D 26, i Q 130.5
Safety fairway zone	M 18 L 3
Sailing club	F 11.3
Salt pans	C 24
Sand	C c, J 1
Sandhills	C 8
Sandwaves	J 14
Sandy shore	C 6
Satellite Navigation System	S 50–51
Scale	A 13–15
Scanner, radar	E 30.3
Schist	Jh
School	Ef
Scoriae	Jo
Scrubbing grid	F 24
Sea mile (nautical mile)	A 15, B 45
Seabed, types of	J 1–15, a–bf
Seagrass	J 13.3
Seal chart producer sanctuary	A 12 N 22
Seaplane anchorage landing area, operating area	N 14 N 13
Seasonal buoy sea ice limit	Q 71 N 60.2
Sea-tangle	Jw
Seawall	F 2.1–2.2
Seaward limit of contiguous zone territorial sea	N 44 N 43
Second of arc of time	B 6 B 51

Sector lights	P 40.1–46.2
See adjoining chart	A 19
Semaphore	T1
Semi-diurnal tide	H 30
Separation line scheme zone	M 12 M 10–13, 20.1–29.2 M 13
Services	Т
Settlements	D 1–8
Sewer	L 41.1–41.2
Shading	C g
Shapes of buoys	Q 20–26
Shark nets	F 29.1
Shed, transit	F 51
Shellfish bed	K 47
Shells	J 11
Shingle	C c, J c
Shingly shore	C 7
Shoal sounding on rock	Kt
Shore, shoreline	C 1–8
Short-long flashing	Pt
Shrine	E 13
Signal fog stations	F T 20–36
Silo	E 33
Silt	J 4
Single Anchor Leg Mooring (SALM) Buoy Mooring (SBM) Point Mooring (SPM)	L 12 L 16 L 12
Sinker	K r
Siren	R 12
Sketches	E 3.1–3.2
Slack water	H 31
Slipway	F 23
Small	J ał
Small craft leisure facilities mooring	L Q 44
Snag	K 43.2

Soft	J 35
Sounding	I 10–16
datum	Ca,b,Kh [2
doubtful depth out of position	1
unreliable	I 14
Source diagram	A 17
South	B 11
cardinal mark	Q 130.3
Southeast	B 14
Southwest	B 16
Spar buoy	Q 24
Special	
lights marks	P 60–66 Q 130.6
purpose beacon	Q 130.0
purpose buoy	Q 50–71
Speckled	Ja
Speed limit	N 27
Spherical buoy	Q 22
Spicules	J>
Spindle buoy	Q 24
Spire	E 10.3
Spoil ground	N 62.1–62.2
Sponge	J
Spot height	C 10–11, 13, H 20
Spring	
tide	H 16, 30–31
seabed	J 15
Square meter	Ba
shaped beacon	Q
Stake	K 43.2, Q 90
Station	
Coast Guard coast radar	T 10–11 M 30, S 1
DGPS, providing corrections	S 51
QTG, providing radio service	S 15
radar surveillance	M 30
radio direction finding	S 14
railway	D 13
rescue	T 11–12
signal	Т 20–36
tide	H 30
Statute	E 24
Statute mile	Be

Steep coast	C 3
Steps	F 18
Sticky	J 34
Stiff	J 36
Stock number	Ad
Stones area with	C 7, J 5 J 20
Stony shore	C 7
Storage tanker	L 17
Storm signal station	T 28
Straight territorial sea baseline	N 42
Strand	Сс
Streaky	J ak
Stream Gulf tidal signal station tidal table tide	C 20, H I, I C H u T 34 H 31, 46 H 40–41
Street	D 7
Strip light	P 64
Stumps of piles/posts	K 43.1–43.2
Submarine cable cable area exercise area pipeline power cable power cable area transit lane volcano	L 30.1–32 L 30.2 N 33 L 40–44 L 31.1 L 31.2 N 33 K d
Submerged crib duck blind jetty platform production well rock, beacon on well (buoyed) wreck	Ki Kk Fb Kl L 20 Q 83 La K 22–23, 26–30
Subsidiary light	P 42.1–42.2
Subsurface Ocean Data Acquisition System (ODAS)	L 25
Sunken danger (swept) wreck	K f K c
Superbuoy	Q 26
Supply pipeline	L 40.1–40.2

Surveyed coastline inadequately	C 1 I 25
Suspended well	L 21.1–21.2
Swamp	C 33
Swept area channel wire drag, by	l 24, b I a K 2, 27, 42, f
Swing bridge	D 23.2
Swinging circle	N 11.2
Symbolized positions	B 30–33
Synchronized light	P 66
т	
Tanker anchorage area CALM storage, moored	N 12.5 L 16 L 17
Tank	E 32
Telegraphic mooring buoy	Q 43
Telephone line	E q D 27
Telephonic mooring buoy	Q 43
Television mast station tower	E 28 E 27 E 29
Temple	E 13
Temporary buoy (seasonal) light	Q 71 P 54
Tenacious	J aq
Terms relating to tidal levels	H 1–17, a–k
Territorial Sea	N 42–43
Tidal basin harbor levels stream signal station station table streams and currents table	F 28 F 28 H 1–17, 20 H 1 T 34 H 46 A g, H 31 H 40–47 H 30
Tide gauge level terms rips	T 32.1–32.2 H 1–17, a–k H 44


scale signal station	T 32.1 T 33
table	A g, H 30–31
Timber yard	F 52
Time	
signal station units of	T 31 B 49–51
Tomb	Eb
Ton, tonnage, tonne (weight)	B 53, m
Topmark	Q 9–11, 82, 102.1
Tower beacon church radar radio television water	E 20 P 3, Q 110–111 E 10.2 E 30.2 E 29 E 29 E 21
Track	D 12, M 1–6, 27.3
Traffic separation scheme (TSS) basic symbols example signal station surveillance station	M 10–15, 20–26.2 M 10–15 M 18–29.2 T 21–22, 25.1 M 30
Training wall	F 5
Transhipment area facilities	N 64 F 50–53.2
Transit Iane (submarine) Iine shed	N 33 M 2 F 51
Transmission line	D 26–27, h
Transmitter, AIS	S 17.1–17.2
Transponder beacon	S 3.1–3.6
Transporter bridge overhead (aerial cableway)	D 24 D 25
Trap, fish	K 44.2–45, Q i
Traveling crane	F 53.1
Trees height of top types of	C 14 C 31–32, i–k
Triangular shaped beacon	QI
Triangulation point	B 20
Trot, mooring	Q 42
True (compass)	Bs

Tufa	Jn
Tun buoy	Q 25
Tunnel pipeline	D 16 L 42.2
Tunney nets area	K 44.2–45 K 45
Turbine wind underwater	E 26.1, L 5.1 L 24
Two-way route track	M 27.2, 28.1–28.2 M 4, 5.2
Tyfon	R 13
Types of fog signals seabed, intertidal areas	R 10–16 J 20–22
U	
Ultra quick light	P 10.8
Uncovers	K 11, 21, h
Under construction	D d, F 30–32
Underwater installations rock turbine	L 20–25 K 13–15 L 24
Uneven	J bf
Unexploded ordinance	Кр
Units	A b, B 40–54
University	Eh
Unsurveyed coastline depths	C 2   25
Unwatched, unmanned light	P 53, e
Update	Α7
Upper light	P 22
Urban area	D 1
٧	
Variation, magnetic	B 68.1–71, p
Varied	J be
Various limits	N 60.1–65
Vegetation	C 30–33, i–t
Velocity	Hn


Vertical clearance	D 22, 23.1, 23.4, 23.6–28
color striped lights	Q 5 P 15
Vertically disposed	P 15
Very quick light	P 10.7
Vessel, light	Ρe
Viaduct	D
Views	E 3.1–3.2
Village	D 4
Violet	J at, P 11.5
Virtual AIS	S 18.1–18.7
Visitor's berth mooring	F 19.2 Q 45
Volcanic ash	78 L I L
Volcano	Ko
W	
Wall, training	F٤
Warehouse	F 51
Water discolored features intake pipeline pipeline area tank tower	K e C 20–25 L 41.1–41.2, t L 40.1, 41.7 L 40.2, L 41.2 E 2 ⁻ E 2 ⁻
Waterfalls	C 22
Watermill	E
Wave actuated fog signal farm	R 21–22 L 6
Way point	M 40.1
Weather signal station	T 29
Weed	J 13.1–13.2
Weir, fish	K 44.2
Well submerged suspended production	E€ La L2 ⁻ L20
Wellhead	L 21.1–21.2, 23
West cardinal mark	B 12 Q 130.3

Wet dock	F 27
Wharf	F 13
Whistle buoy	R 15 Q 0
White	J ar, P 11.1
Wind	
farm	E 26.2, L 5.2
signal station	T 29
turbine	E 26.1, L 5.1
Windmill	E 25.1–25.2
Withy	Q 91–92
Woodland	
coniferous	C
deciduous	C
Woods, wooded	C 30
Works	
at sea, (reclamation area) on land	F 3
on land under construction, works in progress	F 30 F 32
	S 50
World Geodetic System (WGS)	
Wreck	K 20–30,
buoy (marking new danger)	Q 130. K 2
mast	K 2
Y	
Yacht berths without facilities	F 11.2
club	F 11.
Yard	B
timber	F 52
Yellow	J aw, P 11.6
Z	
Zone	
Exclusive Economic Zone (EEZ)	N 4
fishing	N 4 M 25.1–25.1
inshore traffic seaward, contiguous	N 44


#### Appendix 1 IALA Maritime Buoyage System



red	Color	green
cylindrical (can), pillar, spar	Buoy	conical (nun), pillar, spar
single red cylinder (can)	Topmark (if any)	single green cone, point upward









red with one green horizontal band	Color	green with one red horizontal band
cylindrical (can), pillar, spar	Buoy	conical (nun), pillar, spar
single red cylinder (can)	Topmark (if any)	single green cone, point upward


Lights (if a	any) are composite grou	ıp flashing
	FI (2+1)	

#### IALA Maritime Buoyage System Appendix 1



green	Color	red
cylindrical (can), pillar, spar	Buoy	conical (nun), pillar, spar
single green cylinder (can)	Topmark (if any)	single red cone, point upward






Lights (if a	any) are composite grou	p flashing
	FI (2+1)	



#### Appendix 1 IALA Maritime Buoyage System



Cardinal Marks in Regions A and B

Lights, when fitted, are white

## IALA Maritime Buoyage System Appendix 1




Color	black with one or more red horizontal band(s)
Buoy	optional, but not conflicting with lateral marks; pillar or spar preferred
Topmark (if any)	always fitted with double spheres

Lights (if any)		
Color	white	
Rhythm	group flashing	

Safe Water Marks

Regions A and B



red and	white vertical stripes
spheric	al, pillar or spar
single r	ed sphere

white	
ISO	
Oc	
L FI 10s	
Morse "A"	



Special Marks

yellow
optional, but not conflicting with lateral marks
single yellow "X" shape


yellow	
FLY	
FI (4) Y	

May have any rhythm other than those used for white lights on cardinal, isolated danger or safe water marks.

New Danger Marks



blue and yellow vertical stripes
pillar or spar
vertical/perpendicular yellow cross



#### **Record of Corrections**

Notice No.	Corrected on	Corrected by	Notice No.	Corrected on	Corrected by	Notice No.	Corrected on	Corrected

#### **Section Key**

Α	NYT 500	Chart Number, Title and Marginal Notes	INT 500 Mercator Projection 412 Scale 1:100,000 at Lat. 59°30' 53rd Ed., Feb. 2019 DEPTHS IN METERS
В		Positions, Distances, Directions and Compass	
С	※ 沈	Natural Features	359 Warsh Marsh 49 mb
D	20 ctr 20.0	Cultural Features	Tel 12 H Name Ru +++++++ FIXED BRIDGE HOR CL 25 FT VERT CL 20 FT
Ε	"í" <b>Í</b>	Landmarks	⊙ TANK II 🏦 Ø  🖾 ୪ 🛔 Ì 🖞 🎉 (202) Î 🌣 🛓
F		Ports	
Η	3.0 41 2.5	Tides and Currents	2.5 kn (see Note)
	97 <b>9</b> 7	Depths	$\begin{array}{c c c c c c c c c c c c c c c c c c c $
J	Le I	Nature of the Seabed	Consel
Κ	* *	Rocks, Wrecks and Obstructions	🐻 Wk 🔨 35 Rk 7 T 7 🐻 Obstn 🥖 Wk 🏶 Masts 🐱 🙆 Obstn # 🔘 🗆 Crib
L	! 4	Offshore Installations	E z-44 & FLY Prod Well Pipe Crib Well & Well
Μ	IF I	Tracks and Routes	$ \begin{array}{c} \hline DW \rightarrow & \hline \\ \hline DW \rightarrow & \hline \\ \hline$
Ν	÷	Areas and Limits	$\neg \neg \bigcirc \neg \neg \neg \downarrow (\bigcirc \bigcirc $
Ρ		Lights	(89) (R Lts) (89)
Q		Buoys and Beacons	$ \begin{array}{c} \bullet \\ \bullet $
R	4° (1)	P Fog Signals	8 BELL         Image: Constraint of the second
S	() Ra	Radar, Radio and Satellite Navigation Systems	$\textcircled{O} \qquad \textcircled{O} \qquad \textcircled{O} \qquad \swarrow \qquad AIS \qquad \textcircled{O} \qquad \textcircled{O}$
Τ	•	Services	
U		Small Craft (Leisure) Facilities	



U.S. Chart No. 1 Certificate of Authenticity U.S. Chart No. 1, Symbols, Abbreviations and Terms used on Paper and Electronic Navigational Charts is prepared jointly by the National Oceanic and Atmospheric Administration (NOAA) and the National Geospatial-Intelligence Agency (NGA). It is the authoritative source of information on U.S. nautical chart symbology. This copy of U.S. Chart No. 1 was printed and distributed under the authority of NOAA and is an official publication of NOAA and NGA.